



High Productivity Cooking Electric Tilting Boiling Pan, 500lt Hygienic Profile, Freestanding with Stirrer

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



586039 (PBOT50RDEO)

Electric tilting Boiling Pan
500lt (h) prearranged for
stirrer, GuideYou panel,
freestanding

Short Form Specification

Item No.

AISI 304 stainless steel construction. Deep drawn vessel in AISI 316 stainless steel. Insulated and counterbalanced lid. Motorized tilting with variable speed control. Pan can be tilted beyond 90° to completely empty the food. Stirring rotation speed 21rpm. Stirrer drive shaft included, stirrer blades to be ordered separately. Food is uniformly heated via the base and the side walls of the pan by an indirect heating system using integrally generated saturated steam at a maximum temperature of 125° C in a jacket with an automatic deaeration system. Safety valve avoids overpressure of the steam in the jacket. Safety thermostat protects against low water level in the double jacket. TOUCH control panel. SOFT function. Possibility to store recipes in single or multiphase cooking process, with different temperature settings. Built in temperature sensors for precise control of cooking process. IPX6 water resistant. Configuration: Free-standing or Standing against a wall. Installation options (not included): floor mounted on 200mm high feet or a plinth which can be either steel or masonry construction.

Main Features

- Kettle is suitable to boil, steam, poach, braise or simmer all kinds of produce.
- Kettle is jacketed up to 134 mm from upper rim.
- Isolated upper well rim avoids risk of harm for the user.
- Ergonomic vessel dimensions, with a large diameter and shallow depth facilitates stirring and gentle food handling.
- Edge of the large pouring lip can be equipped with a strainer (option).
- Motorized, variable pan tilting with "SOFT STOP". Tilting and pouring speeds can be precisely adjusted. Pan can be tilted over 90° to facilitate pouring and cleaning operations.
- Built in temperature sensor to precisely control the cooking process.
- USB connection to easily update the software, upload/download recipes and download HACCP data.
- IPX6 water resistant.
- Max pressure of inner jacket at 1.7 bar; minimum working pressure at 1 bar. Allows temperature control between 50 and 110°C.

Construction

- Cooking vessel in 1.4435 (AISI 316L) stainless steel featuring directional pouring lip. Double-jacket in 1.4404 (AISI 316L) stainless steel designed to operate at a pressure of 1.5 bar.
- External panelling and internal frame made of 1.4301 (AISI 304) stainless steel.
- Double-lined insulated lid in 1.4301 (AISI 304) stainless steel mounted on the cross beam of the unit, counterbalanced by a hinge that remains open in all positions.
- Safety valve avoids overpressure of the steam in the double jacket.
- Safety thermostat protects against low water level in the double jacket.
- Water mixing tap is available as optional accessory to make water filling and pan cleaning easier.
- Ergonomic and user friendly thanks to the high tilting position and the pouring lip design which allow to easily fill containers.
- Front-mounted inclined led "TOUCH" control panel with recessed deep drawn casing, features self-explanatory display functions which guide operator throughout the cooking process: simultaneous display of actual and set temperature as well as set cooking time and remaining cooking time; real time clock; "SOFT" control for gentle heating up for delicate food; 9 power simmering levels from gentle to heavy boiling; timer for deferred

APPROVAL:



Experience the Excellence
www.electroluxprofessional.com

start; error display for quick trouble-shooting.

- Minimised presence of narrow gaps for easier cleaning of the sides to meet the highest hygiene standards.
- Can be prearranged for energy optimisation or external surveillance systems (optional).
- Possibility to store recipes in single or multiphase cooking process, with different temperature settings.
- 98% recyclable by weight; packaging material free of toxic substances.
- Stirrer with rotation speed of 21 RPMs.
- GuideYou Panel - activated by the user via settings - to easily follow the multiphase recipes, granting a proper and controlled cooking and a better appliance optimization. The system will provide maintenance reminders, in line with ESSENTIA program, helping the user to properly take care of the product, avoiding downtimes.
- Highly-visible and bright led TOUCH control panel features user-friendly icons and intuitive self-explanatory command options. Display visualizes:
 - Actual and set temperature
 - Set and remaining cooking time
 - Pre-heating phase (if activated)
 - GuideYou Panel (if activated)
 - Deferred start
 - Soft Function to reach the target temperature smoothly
 - 9 Power Control levels from simmering to fierce boiling
 - Pressure mode (in pressure models)
 - Stirrer ON/OFF settings (in round boiling models)
 - Error codes for quick trouble-shooting
 - Maintenance reminders

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Included Accessories

- 1 of Emergency stop button - factory fitted

PNC 912784

Optional Accessories

- Strainer for 300, 400 and 500lt tilting boiling pans
- Food tap strainer rod for stationary round boiling pans
- Stainless steel plinth for tilting units - against wall - factory fitted
- Stainless steel plinth for tilting units - freestanding - factory fitted
- Drip stop KWC
- FOOD TAP STRAINER - PBOT
- C-board (length 1500mm) for tilting units - factory fitted

 PNC 910006

 PNC 910162

 PNC 911812

 PNC 911813

 PNC 911933

 PNC 911966

 PNC 912187

- Power Socket, CEE16, built-in, 16A/400V, IP67, red-white - factory fitted
- Power Socket, CEE32, built-in, 32A/400V, IP67, red-white - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP68, blue-white - factory fitted
- Power Socket, TYP23, built-in, 16A/230V, IP55, black - factory fitted
- Power Socket, TYP25, built-in, 16A/400V, IP55, black - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP55, black - factory fitted
- Power Socket, CEE16, built-in, 16A/230V, IP67, blue-white - factory fitted
- Power Socket, TYP23, built-in, 16A/230V, IP54, blue - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP54, blue - factory fitted
- Power Socket, TYP25, built-in, 16A/400V, IP54, red-white - factory fitted
- Panelling for plinth recess (depth from 70 to 270mm) for tilting units - factory fitted (Deutschland, Austria, Switzerland) - factory fitted
- Manometer for tilting boiling pans - factory fitted
- Rear closing kit for tilting units - against wall - factory fitted
- Automatic water filling (hot and cold) for tilting units - to be ordered with water mixer - factory fitted
- Kit energy optimization and potential free contact - factory fitted
- Mainswitch 80A, 16mm² - factory fitted
- Rear closing kit for tilting units - island type - factory fitted
- Lower rear backpanel for tilting units with or without backsplash - factory fitted
- Spray gun for tilting units - freestanding (height 700mm) - factory fitted
- Food tap 2" for tilting boiling pans (PBOT) - factory fitted
- Mixing tap with two knobs, 520mm height, 600mm swivelling depth for PXXT- KWC - factory fitted
- Mixing tap with one lever, 564mm height, 450mm swivelling depth for PXXT- KWC - factory fitted
- Grid stirrer for boiling pans 500lt

 PNC 912468

 PNC 912469

 PNC 912470

 PNC 912471

 PNC 912472

 PNC 912473

 PNC 912474

 PNC 912475

 PNC 912476

 PNC 912477

 PNC 912479

 PNC 912490

 PNC 912707

 PNC 912735

 PNC 912737

 PNC 912741

 PNC 912747

 PNC 912771

 PNC 912776

 PNC 912779



 PNC 913567

 PNC 913568


 PNC 913569


- Grid stirrer and scraper boiling pans 500lt PNC 913570
- Measuring rod for 500lt tilting boiling pans PNC 913573
- Connectivity kit for ProThermic Boiling and Braising Pans ECAP - factory fitted PNC 913577



Front

Side


CWII = Cold Water inlet 1 (cleaning)
 EI = Electrical inlet (power)
 HWI = Hot water inlet

Top

Electric

Supply voltage: 400 V/3N ph/50/60 Hz
Total Watts: 48.6 kW

Installation:

FS on concrete base;FS on feet;On base;Standing against wall

Key Information:

Working Temperature MIN:	50 °C
Working Temperature MAX:	110 °C
Vessel (round) diameter:	900 mm
Vessel (round) depth:	880 mm
External dimensions, Width:	1500 mm
External dimensions, Depth:	1000 mm
External dimensions, Height:	700 mm
Net weight:	560 kg
Configuration:	Round;Tilting;Pre-arranged for stirrer
Net vessel useful capacity:	500 lt
Tilting mechanism:	Automatic
Double jacketed lid:	✓
Heating type:	Indirect