

Accessories

Elbow operated Tap with Spray Arm and Spout with Single Hole

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

**855324 (SHTEBO3M)**Elbow operated tap with
spray arm and spout, single
hole

Main Features

- Heat-insulating and limescale-resistant thermoplastic components.
- All pre-rinse unit are equipped with check valves in compliance with EN 1717.
- Mounting hole: 29mm.
- Lever reinforced by elastic and unbreakable glass fiber. Material selected to meet the needs of professional kitchens in accordance with food standards. Its light weight allows a precise positioning and prevents the accidentally closing. The mixing cartridge is highly resistant to limestone.
- Water flow: spray gun 16 l/min, supply spout 24 l/min with 3 bar.

Construction

- Flexible hose in EPDM rubber, certified for portable water; reinforced with stainless steel double braid and transparent thermoplastic coating.
- The spray gun allows a progressive water flow with internal components in stainless steel and EPDM rubber certified for food.
- Faucet body made in hard chromium-plated brass, massive heavy-duty construction and it is resistant to temperature up to 85°C. Mounting shank: G3/4", 50mm long and ring nut for maximum stability and ease of installation.
- Hydraulic connection MG 1/2 male-threaded compression coupling.
- Stainless steel spray gun bracket with fiberglass body.
- 150mm long wall bracket in fiberglass.
- Riser pipe in AISI 316 stainless steel.
- Swivel spout chrome plated brass.

Sustainability

- Support spring in harmonic steel.



APPROVAL: _____



Electrolux
PROFESSIONAL

Accessories Elbow operated Tap with Spray Arm and Spout with Single Hole

Key Information:

External dimensions, Width:

855324 (SHTEBO3M) 800 mm

External dimensions, Depth: 465 mm

External dimensions, Height: 1400 mm

Accessories
Elbow operated Tap with Spray Arm and Spout with Single Hole

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.04.26