

SkyLine Premium Electric Combi Oven 10GN2/1

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



217813 (ECOE102B2C0)

SkyLine Premium Combi Boiler Oven with digital control, 10x2/1GN, electric, programmable, automatic cleaning

217823 (ECOE102B2A0)

SkyLine Premium Combi Boiler Oven with digital control, 10x2/1GN, electric, programmable, automatic cleaning

Short Form Specification

Item No.

Combi oven with digital interface with guided selection

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored);
 Manual (steam, combi and convection cycles);
 EcoDelta cooking cycle;
 Regeneration cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

Main Features

- Digital interface with LED backlight buttons with guided selection.
- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- USB port to download HACCP data, share cooking programs and configurations.
 USB port also allows to plug-in sous-vide probe (optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 10 GN 2/1 or 20 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all

APPROVAL:





SkyLine Premium Electric Combi Oven 10GN2/1

• Kit universal skewer rack and 6 short

• 4 flanged feet for 6 & 10 GN, 2",

Grease collection tray, GN 2/1, H=60

Grid for whole duck (8 per grid - 1,8kg

Wall mounted detergent tank holder

• Tray rack with wheels 10 GN 2/1, 65mm

• Tray rack with wheels, 8 GN 2/1, 80mm

• IoT module for SkyLine ovens and blast PNC 922421

Thermal cover for 10 GN 2/1 oven and

ovens

mm

Universal skewer rack

• 6 short skewers

100-130mm

each), GN 1/1

blast chiller freezer

Tray support for 6 & 10 GN 2/1

disassembled open base

• USB single point probe

chiller/freezers

Multipurpose hook

skewers for Lengthwise and Crosswise

 \Box

 \Box

PNC 922325

PNC 922326

PNC 922328

PNC 922348

PNC 922351

PNC 922357

PNC 922362

PNC 922366

PNC 922384

PNC 922386

PNC 922390

PNC 922603

PNC 922604

rounded corners for easy cleaning.

- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- $\bullet \ \ Wing\text{-}shaped \ handle \ with \ ergonomic \ design \ and \ hands\text{-}free$ opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related
- $\bullet \ \ Reduced power function for customized slow cooking cycles.$

Ontional Accessories

(Optional Accessories				itch	1110 /22004	_
	External reverse osmosis filter for single tank Dishwashers with atmosphere	PNC 864388			ide-in rack with handle for 6 & 10 GN /1 oven	PNC 922605	
	boiler and Ovens			• Bo	akery/pastry tray rack with wheels	PNC 922609	
	Water softener with cartridge and flow meter (high steam usage)	PNC 920003		bl	00x600mm for 10 GN 2/1 oven and last chiller freezer, 80mm pitch (8 unners)		
•	Water filter with cartridge and flow meter for 6 & 10 GN 1/1 ovens (low- medium steam usage - less than 2hrs	PNC 920004		• 0	pen base with tray support for 6 & 10 N 2/1 oven	PNC 922613	
	per day full steam)				upboard base with tray support for 6	PNC 922616	
•	Water softener with salt for ovens with	PNC 921305			10 GN 2/1 oven	DNIC 000/10	
	automatic regeneration of resin	DNIC 000007			xternal connection kit for liquid etergent and rinse aid	PNC 922618	
•	Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003		• St	tacking kit for 6 GN 2/1 oven placed n electric 10 GN 2/1 oven	PNC 922621	
•	Pair of AISI 304 stainless steel grids, GN 1/1	PNC 922017		• Tr	rolley for slide-in rack for 10 GN 2/1 ven and blast chiller freezer	PNC 922627	
•	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922036			rolley for mobile rack for 6 GN 2/1 on 6 r 10 GN 2/1 ovens	PNC 922631	
•	AISI 304 stainless steel grid, GN 1/1	PNC 922062			tainless steel drain kit for 6 & 10 GN	PNC 922636	
•	AISI 304 stainless steel grid, GN 2/1	PNC 922076			ven, dia=50mm	DNC 000/77	
•	External side spray unit (needs to be mounted outside and includes support	PNC 922171			lastic drain kit for 6 &10 GN oven, ia=50mm	PNC 922637	
	to be mounted on the oven)				rolley with 2 tanks for grease	PNC 922638	
•	Pair of AISI 304 stainless steel grids,	PNC 922175			ollection	DVIC 000 (70	
	GN 2/1	DVIC 000100			rease collection kit for GN 1/1-2/1 pen base (2 tanks, open/close device	PNC 922639	
•	Baking tray for 5 baguettes in perforated aluminum with silicon	PNC 922189			or drain)		
	coating, 400x600x38mm				anquet rack with wheels holding 51	PNC 922650	
•	Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190		cł	lates for 10 GN 2/1 oven and blast hiller freezer, 75mm pitch		
•	Baking tray with 4 edges in aluminum,	PNC 922191			ehydration tray, GN 1/1, H=20mm	PNC 922651	
	400x600x20mm	DNIC 000070			at dehydration tray, GN 1/1 pen base for 6 & 10 GN 2/1 oven,	PNC 922652 PNC 922654	
	Pair of frying baskets	PNC 922239 PNC 922264			isassembled - NO accessory can be	FINC 722034	_
•	AISI 304 stainless steel bakery/pastry grid 400x600mm	FINC YZZZO4	_	fit	ted with the exception of 922384		
•	Double-step door opening kit	PNC 922265			eat shield for 10 GN 2/1 oven	PNC 922664	
	Grid for whole chicken (8 per grid -	PNC 922266			eat shield-stacked for ovens 6 GN 2/1	PNC 922667	

on 10 GN 2/1

• Kit to fix oven to the wall



1,2kg each), GN 1/1







SkyLine Premium Electric Combi Oven 10GN2/1

PNC 922687



SkyLine Premium Electric Combi Oven 10GN2/1

				600	Classica Tab Disassable	DNIC	00705	
•	Tray support for 6 & 10 GN 2/1 oven base	PNC 922692		dete	Cleaning Tab Disposable rgent tablets for SkyLine oven: essional detergent for new		0S2395	
•	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693		gene	eration ovens with automatic hing system. Suitable for all typ	nes of		
•	Detergent tank holder for open base	PNC 922699			er. Packaging: 1 drum of 100 65			
•	Mesh grilling grid, GN 1/1	PNC 922713			ets. each	J		
•	Probe holder for liquids	PNC 922714						
	Odour reduction hood with fan for 6 & 10 GN 2/1 electric ovens	PNC 922719						
•	Odour reduction hood with fan for 6+6 or 6+10 GN 2/1 electric ovens	PNC 922721						
•	Condensation hood with fan for 6 & 10 GN 2/1 electric oven	PNC 922724						
•	Condensation hood with fan for stacking 6+6 or 6+10 GN 2/1 electric ovens	PNC 922726						
•	Exhaust hood with fan for 6 $\&$ 10 GN 2/1 GN ovens	PNC 922729						
•	Exhaust hood with fan for stacking 6+6 or 6+10 GN 2/1 ovens	PNC 922731						
•	Exhaust hood without fan for 6&10x2/1 GN oven	PNC 922734						
	Exhaust hood without fan for stacking 6+6 or 6+10 GN 2/1 ovens	PNC 922736						
	4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	_					
	Tray for traditional static cooking, H=100mm	PNC 922746	_					
	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747						
	Trolley for grease collection kit	PNC 922752						
	Water inlet pressure reducer	PNC 922773						
•	Kit for installation of electric power peak management system for 6 & 10 GN Oven	PNC 922774						
•	Extension for condensation tube, 37cm	PNC 922776						
•	Non-stick universal pan, GN 1/1, H=20mm	PNC 925000						
•	Non-stick universal pan, GN 1/1, H=40mm	PNC 925001						
	Non-stick universal pan, GN 1/1, H=60mm	PNC 925002						
	Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003						
	Aluminum grill, GN 1/1	PNC 925004						
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005						
	Flat baking tray with 2 edges, GN 1/1	PNC 925006						
	Potato baker for 28 potatoes, GN 1/1	PNC 925008						
•	Compatibility kit for installation on previous base GN 2/1	PNC 930218						
F	Recommended Detergents							
	C25 Rinse & Descale tab 2in1 rinse aid and descaler in disposable tablets for Skyline ovens Professional 2in1 rinse aid and descaler in disposable tablets for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 50 30g tablets. each	PNC 0S2394						












SkyLine Premium Electric Combi Oven 10GN2/1



2 " 50 mm 11/16 ^a 26 7/16 CWI1 CWI2 EI 13/16 30 5/16 · 3 15/16 " 935 4 15/16 "

EI =


Electrical inlet (power)

CWII Cold Water inlet 1 (cleaning) CWI2

= Cold Water Inlet 2 (steam generator)

D

DO Overflow drain pipe



Electric

Front

Side

Supply voltage:

217813 (ECOE102B2C0) 220-240 V/3 ph/50-60 Hz 217823 (ECOE102B2A0) 380-415 V/3N ph/50-60 Hz

Electrical power, default: 37.4 kW

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

401 kW Electrical power max.:

Circuit breaker required

Water:

Water inlet connections "CWI1-

CWI2": 3/4" 1-6 bar Pressure, bar min/max:

Drain "D": 50mm

Max inlet water supply

30 °C temperature: Chlorides: <17 ppm Conductivity: >50 µS/cm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for

50 cm left hand side. service access:

Capacity:

Trays type: 10 - 2/1 Gastronorm

Max load capacity: 100 kg

Key Information:

Door hinges:

External dimensions, Width: 1090 mm External dimensions, Depth: 971 mm External dimensions, Height: 1058 mm 179 kg Net weight: Shipping weight: 204 kg Shipping volume: 1.59 m³

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards:

45001; ISO 50001









