

Crosswise Convection Gas Convection Oven, 6 GN1/1 -60Hz

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
71171	



260722 (FCG06160)

Gas Convection Oven 6x1/1GN, crosswise

Short Form Specification

Item No.

Main structure in stainless steel, with seamless joints in the oven cavity. Door with tempered glass. Cavity lighting. Unique air-flow channel

Cooking cycles: air convection, convection with 5 stage humidification. Max. temperature of 300°C.

Functional level: base, manual,

"Cross-wise" pan rack, 60 mm pitch, suitable for 6x1/1GN.

Main Features

- Racks can be easily removed without the need for special tools.
- Unique air-flow system guarantees perfect distribution of heat throughout the oven cavity.
- Maximum temperature of 300°C.
- Food temperature probe (available as accessory).
- Rapid cooling of oven cavity.
- Halogen lighting and "crosswise" pan supports allow clear and unobstructed view of the products being cooked.
- 5 Stage humidification control, to ensure perfect pastries and succulent roasts.
- Meets the requirements of CE, VDE and DVGW for safety.

Construction

- Access to all components from the front.
- Stainless steel oven cavity with rounded corners.
- External access door for electrical connections.
- All connections made on the left side below the oven.
- Integrated drain outlet.
- IPx4 water protection.

Optional Accessories Stacking kit for 6 GN 1/1 PNC 881528 🔲 convection oven on 15&25 kg blast chiller/freezer crosswise Pair of 1/1GN AISI 304 stainless PNC 921101 🗆 steel grids Support for 1/2GN pan (2pcs) PNC 921106 📮 Water softener with salt for ovens PNC 921305 🚨 with automatic regeneration of Flue condenser for gas ovens PNC 921701 🚨 10x1/1-2/1 PNC 921702 🗆 Probe for ovens 6 and 10x1/1GN • Guide kit for 1/1GN drain pan PNC 921713 🔲 Pair of grids for whole chicken (8 PNC 922036 🖵 per grid - 1,2kg each), GN 1/1 • Open base for 6 GN 1/1 PNC 922101 🔲 convection oven Shelf guides for 6x1/1GN, ovens PNC 922105 🗆 base PNC 922127 🔲 • Feet for ovens 6x1/1GN, 10x1/1 and 2/1GN • Retractable hose reel spray unit PNC 922170 🚨 External side spray unit (needs to PNC 922171 🚨 be mounted outside and

PNC 922239 🗆

PNC 922266 □

PNC 922325 🗆

includes support to be mounted

short skewers for Lengthwise and

Grid for whole chicken (8 per

grid - 1,2kg each), GN 1/1 Kit universal skewer rack and 6

on the oven) • Pair of frying baskets

Crosswise ovens

APPROVAL:





Crosswise Convection Gas Convection Oven, 6 GN1/1 -

PNC 922326 □ • Universal skewer rack

• Volcano Smoker for lengthwise and PNC 922338 🚨 crosswise oven













Crosswise Convection Gas Convection Oven, 6 GN1/1 -






CWI2

= Cold Water inlet 1 (cleaning) = Cold Water Inlet 2 (steam generator)

Drain

Electrical inlet (power)



Electric

Supply voltage:

260722 (FCG06160) 220-230 V/1 ph/60 Hz

Electrical power max.: 0.35 kW

Capacity:

Shelf capacity:

Key Information:

External dimensions, Width: 860 mm External dimensions, Depth: 746 mm External dimensions, Height: 701 mm Net weight: 92.1 kg Functional level: Basic

Type of grids: 1/1 Gastronorm

Runners pitch: 60 mm

Cooking cycles - air-convection:

300 °C

Heating-up time (hot air 215°C / 350s. cycle):







G = Gas connection

