

# Crosswise Convection Gas Convection Oven, 6 GN1/1

ITEM #	
MODEL #	
MODEL #	
NAME #	
SIS #	
AIA#	



260700 (FCG061)

Gas Convection Oven 6x1/1GN, crosswise

# **Short Form Specification**

### Item No.

Main structure in stainless steel, with seamless joints in the oven cavity. Single-glazed door with tempered glass. Cavity lighting. Unique airflow channel system. Semi-automatic cleaning cycle. Atmospheric burner.

Cooking cycles: air convection, convection/humidifier. Max. temperature of 300°C.

Functional level: base, manual.

"Cross-wise" pan rack, 60 mm pitch, suitable for 6x1/1GN.

### **Main Features**

- Racks can be easily removed without the need for special tools.
- Unique air-flow system guarantees perfect distribution of heat throughout the oven cavity.
- Maximum temperature of 300°C.
- Food temperature probe (available as accessory).
- Rapid cooling of oven cavity.
- Halogen lighting and "crosswise" pan supports allow clear and unobstructed view of the products being cooked.
- 5 Stage humidification control, to ensure perfect pastries and succulent roasts.
- Meets the requirements of CE, VDE and DVGW for safety.

### Construction

- Access to all components from the front.
- Stainless steel oven cavity with rounded corners.
- External access door for electrical connections.
- All connections made on the left side below the oven.
- Integrated drain outlet.
- IPx4 water protection.

#### APPROVAL:





# **Crosswise Convection** Gas Convection Oven, 6 GN1/1

### **Optional Accessories**

PNC 881528	
PNC 921101	
PNC 921106	
PNC 921305	
PNC 921701	
PNC 921702	
PNC 921713	
PNC 922036	
PNC 922101	
PNC 922105	
PNC 922127	
PNC 922170	
PNC 922171	
PNC 922239	
PNC 922266	
PNC 922325	
PNC 922326	
PNC 922338	
	PNC 921106 PNC 921305 PNC 921701 PNC 921702 PNC 921713 PNC 922036 PNC 922101 PNC 922105 PNC 922127 PNC 922170 PNC 922171 PNC 922171 PNC 922239 PNC 922325 PNC 922325













# **Crosswise Convection** Gas Convection Oven, 6 GN1/1






CWI2

= Cold Water inlet 1 (cleaning) = Cold Water Inlet 2 (steam generator)

Drain Electrical inlet (power)



### Electric

Supply voltage:

260700 (FCG061) 220-230 V/1 ph/50 Hz

Electrical power max.: 0.35 kW

Capacity:

Shelf capacity:

### **Key Information:**

External dimensions, Width: 860 mm External dimensions, Depth: 746 mm External dimensions, Height: 701 mm Net weight: 92.1 kg Functional level: Basic

Type of grids: 1/1 Gastronorm

Runners pitch: 60 mm

Cooking cycles - air-convection:

300 °C

Heating-up time (hot air 215°C / 350s. cycle):











G = Gas connection

