

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



229762 (ECOG101T3G0)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 10x1/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door

229792 (ECOG101T3G6)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 10x1/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door - 60Hz

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator, 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1GN, 67mm pitch

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants perfamily.

Cycles+:
- Regeneration (ideal for banqueting on plate or rethermalizing on tray),

- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,

- Proving cycle,

EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,

- Sous-vide cooking,

- Static Combi (to reproduce traditional cooking from static oven),

- Pasteurization of pasta,

Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood),

- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
 - Advanced Food Safe Control (to drive the cooking
- with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different catégories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking

APPROVAL:





cycles.

- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- USB port to download HACCP data, share cooking programs and configurations.
 USB port also allows to plug-in sous-vide probe (optional accessory)
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 10 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Triple thermo-glazed door with 2 hinged inside panels for easy cleaning and double LED lights line.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse

- aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste
- Zero Waste is a library of Automatic recipes that aims to:
 -give a second life to raw food close to expiration date (e. g.: from milk to yogurt)
- -obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g.: carrot peels).
- Energy Star 2.0 certified product.
- Optional Accessories External reverse osmosis filter for single PNC 864388 tank Dishwashers with atmosphere boiler and Ovens Water softener with cartridge and flow PNC 920003 meter (high steam usage) · Water filter with cartridge and flow PNC 920004 meter for 6 & 10 GN 1/1 ovens (lowmedium steam usage - less than 2hrs per day full steam) • Water softener with salt for ovens with PNC 921305 automatic regeneration of resin Wheel kit for 6 & 10 GN 1/1 and 2/1 GN PNC 922003 oven base (not for the disassembled one) · Pair of AISI 304 stainless steel grids, PNC 922017 GN 1/1 PNC 922036 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 AISI 304 stainless steel grid, GN 1/1 PNC 922062 • Grid for whole chicken (4 per grid -PNC 922086 1,2kg each), GN 1/2 • External side spray unit (needs to be PNC 922171 mounted outside and includes support to be mounted on the oven) Baking tray for 5 baguettes in PNC 922189 \Box perforated aluminum with silicon coating, 400x600x38mm • Baking tray with 4 edges in perforated PNC 922190 aluminum, 400x600x20mm
- Pair of frying baskets
 AISI 304 stainless steel bakery/pastry grid 400x600mm
 PNC 922239
 PNC 922264

Baking tray with 4 edges in aluminum,

400x600x20mm

- Double-step door opening kit
 Grid for whole chicken (8 per grid 1,2kg each), GN 1/1
 PNC 922265
 PNC 922266
- USB probe for sous-vide cooking
 Grease collection tray, GN 1/1, H=100
 PNC 922281
 PNC 922321
 PNC 922321
- Kit universal skewer rack and 4 long skewers for Lenghtwise ovens
- Universal skewer rack
 4 long skewers
 Multipurpose hook
 PNC 922326
 PNC 922327
 PNC 922348
 PNC 922348
- Multipurpose hook
 4 flanged feet for 6 & 10 GN , 2",
 100-130mm
 PNC 922348
 PNC 922351















PNC 922191

 \Box



•	Grid for whole duck (8 per grid - 1,8kg	PNC 922362		Kit to convert from natural gas to LPG PNC 922670 Kit to convert from LPC to a power large PNC 922671 PNC 922671	
	each), GN 1/1 Thermal cover for 10 GN 1/1 oven and	PNC 922364		 Kit to convert from LPG to natural gas Flue condenser for gas oven PNC 922671 PNC 922678 	
·	blast chiller freezer	1110 722504	_	• Fixed tray rack for 10 GN 1/1 and PNC 922685	
•	Tray support for 6 & 10 GN 1/1	PNC 922382		400x600mm grids	
	disassembled open base	DNC 022704		• Kit to fix oven to the wall PNC 922687	
	Wall mounted detergent tank holder USB single point probe	PNC 922386 PNC 922390		 Tray support for 6 & 10 GN 1/1 oven PNC 922690 base 	
	IoT module for OnE Connected and SkyDuo (one IoT board per appliance -	PNC 922421		 4 adjustable feet with black cover for 6 PNC 922693 & 10 GN ovens, 100-115mm 	
	to connect oven to blast chiller for Cook&Chill process). (only for 229762)			 Reinforced tray rack with wheels, lowest PNC 922694 support dedicated to a grease 	
•	Tray rack with wheels 10 GN 1/1, 65mm pitch	PNC 922601		collection tray for 10 GN 1/1 oven, 64mm pitch	
•	Tray rack with wheels, 8 GN 1/1, 80mm pitch	PNC 922602		Detergent tank holder for open base PNC 922699 Release (2004/2007) RNC 922699	
•	Bakery/pastry tray rack with wheels	PNC 922608		 Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base 	
	holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm			• Wheels for stacked ovens PNC 922704	
	pitch (8 runners)	DVIC 000/10		 Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens PNC 922709 	
•	Slide-in rack with handle for 6 & 10 GN 1/1 oven	PNC 922610		• Mesh grilling grid, GN 1/1 PNC 922713	
	Open base with tray support for 6 & 10	PNC 922612		• Probe holder for liquids PNC 922714	
	GN 1/1 oven	1110 722012	_	• Exhaust hood with fan for 6 & 10 GN 1/1 PNC 922728	
	& 10 GN 1/1 oven	PNC 922614		 exhaust hood with fan for stacking 6+6 exhaust hood with fan fan for stacking 6+6 exhaust hood with fan fan fan fan fan fan fan fan fan fan	
•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or 400x600mm trays	PNC 922615		• Exhaust hood without fan for 6&10 PNC 922733 1/1GN ovens	
•	External connection kit for liquid detergent and rinse aid	PNC 922618		• Exhaust hood without fan for stacking PNC 922737 6+6 or 6+10 GN 1/1 ovens	
•	Grease collection kit for GN 1/1-2/1	PNC 922619		• Fixed tray rack, 8 GN 1/1, 85mm pitch PNC 922741	
	cupboard base (trolley with 2 tanks,		_	• Fixed tray rack, 8 GN 2/1, 85mm pitch PNC 922742	
•	open/close device for drain) Stacking kit for 6 GN 1/1 oven placed	PNC 922623		 4 high adjustable feet for 6 & 10 GN PNC 922745 ovens, 230-290mm 	
•		PNC 922626		 Tray for traditional static cooking, H=100mm PNC 922746 	
•	oven and blast chiller freezer Trolley for mobile rack for 6 GN 1/1 on 6	PNC 922630		 Double-face griddle, one side ribbed and one side smooth, 400x600mm 	
	or 10 GN 1/1 ovens		_	• Trolley for grease collection kit PNC 922752	
•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636		• Water inlet pressure reducer PNC 922773	
_	Plastic drain kit for 6 & 10 GN oven,	PNC 922637		• Extension for condensation tube, 37cm PNC 922776	
•	dia=50mm	PNC 922037	_	 Non-stick universal pan, GN 1/1, H=20mm 	
•	Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain)	PNC 922639		• Non-stick universal pan, GN 1/1, PNC 925001 H=40mm	
•	Wall support for 10 GN 1/1 oven	PNC 922645		• Non-stick universal pan, GN 1/1, PNC 925002	
•	Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast	PNC 922648		 H=60mm Double-face griddle, one side ribbed PNC 925003 and one side smooth, GN 1/1 	
	chiller freezer, 65mm pitch	PNC 922649		• Aluminum grill, GN 1/1 PNC 925004	
•	Banquet rack with wheels 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch	PNC 922049	_	 Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 	
•	Dehydration tray, GN 1/1, H=20mm	PNC 922651		• Flat baking tray with 2 edges, GN 1/1 PNC 925006	
	Flat dehydration tray, GN 1/1	PNC 922652		• Baking tray for 4 baguettes, GN 1/1 PNC 925007	
	Open base for 6 & 10 GN 1/1 oven,	PNC 922653		• Potato baker for 28 potatoes, GN 1/1 PNC 925008	
	disassembled - NO accessory can be fitted with the exception of 922382	1.1.7.22000	_	 Non-stick universal pan, GN 1/2, H=20mm 	
•	Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and	PNC 922656		• Non-stick universal pan, GN 1/2, PNC 925010 H=40mm	
•	80mm pitch Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661		 Non-stick universal pan, GN 1/2, H=60mm 	
•	Heat shield for 10 GN 1/1 oven	PNC 922663			

















 Compatibility kit for installation on previous base GN 1/1

PNC 930217 🔲

Recommended Detergents

- C25 Rinse & Descale tab 2in1 rinse aid and descaler in disposable tablets for Skyline ovens Professional 2in1 rinse aid and descaler in disposable tablets for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 50 30g tablets. each
- C22 Cleaning Tab Disposable detergent tablets for SkyLine ovens Professional detergent for new generation ovens with automatic washing system. Suitable for all types of water. Packaging: 1 drum of 100 65g tablets. each

PNC 0S2395





















11/16 958 mm CWI1 CWI2 EI 13/16 a 15/16 "

Cold Water inlet 1 (cleaning) CWII CWI2

= Cold Water Inlet 2 (steam generator)

Drain

DO Overflow drain pipe



ΕI

Electrical inlet (power)

Gas connection

Electric

Front

Side

Supply voltage:

229762 (ECOG101T3G0) 220-240 V/1 ph/50 Hz 229792 (ECOG101T3G6) 220-230 V/1 ph/60 Hz

Electrical power, default:

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

11 kW Electrical power max.:

Circuit breaker required

Gas

Gas Power: 31 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

diameter: 1/2" MNPT

105679 BTU (31 kW) Total thermal load:

Water:

Water inlet connections "CWI1-

3/4" CWI2":

1-6 bar Pressure, bar min/max: Drain "D": 50mm

Max inlet water supply temperature:

30 °C Chlorides: <17 ppm Conductivity: >50 µS/cm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Trays type: 10 - 1/1 Gastronorm

Max load capacity: 50 kg

Key Information:

Door hinges:

867 mm External dimensions, Width: 775 mm External dimensions, Depth: External dimensions, Height: 1058 mm Net weight: 165 kg Shipping weight: 183 kg Shipping volume: 229762 (ECOG101T3G0) 1.06 m³

ISO Certificates

229792 (ECOG101T3G6)

ISO 9001; ISO 14001; ISO

ISO Standards: 45001; ISO 50001















1.04 m³