

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



#### 237064 (ECOG201T2GB)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 16 400x600mm, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, for bakery/pastry, pitch 80mm

### **Short Form Specification**

#### Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 pastry tray rack 400x600 mm, 80 mm pitch

#### **Main Features**

- Built-in steam generator for highly precise humidity and temperature control according to the chosen
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate
  - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants perfamily.
- Cycles+:
   Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
  - Advanced Food Safe Control (to drive the cooking
- with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking







#### cycles.

- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 16 GN 1/1 400x600mm trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

#### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.
- Supplied with n.1 pastry tray rack 400x600 mm, 80 mm pitch.

#### User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

#### Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.

- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste.
  - Zero Waste is a library of Automatic recipes that aims to:
    -give a second life to raw food close to expiration date (e. g.: from milk to yogurt)
- -obtain genuiné and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g. carrot peels).

SkyLine PremiumS Natural Gas Combi Oven 16 trays, 600x400mm Bakery



			External connection kit for liquid	PNC 922618	
Included Accessories			detergent and rinse aid	1110 722010	_
1 of Bakery/pastry trolley with rack     balding 400y/00mm gridg for 20 CN	PNC 922761		Dehydration tray, GN 1/1, H=20mm	PNC 922651	
holding 600x400mm grids for 20 GN oven and blast chiller freezer, 80mm			Flat dehydration tray, GN 1/1	PNC 922652	
pitch (16 runners)			Heat shield for 20 GN 1/1 oven	PNC 922659	
Optional Accessories			Kit to convert from natural gas to LPG	PNC 922670	
<ul> <li>External reverse osmosis filter for sin</li> </ul>	ala DNC 86/388		Kit to convert from LPG to natural gas	PNC 922671	
tank Dishwashers with atmosphere boiler and Ovens	gie 1110 004000	_	<ul> <li>Flue condenser for gas oven</li> <li>Trolley with tray rack, 15 GN 1/1, 84mm pitch</li> </ul>	PNC 922678 PNC 922683	
<ul> <li>Water filter with cartridge and flow</li> </ul>	PNC 920003		Kit to fix oven to the wall	PNC 922687	
meter for high steam usage (combi used mainly in steaming mode)			Adjustable wheels for 20 GN 1/1 and 20 GN 2/1 ovens		ā
Water filter with cartridge and flow meter for medium steam usage	PNC 920005		• 4 flanged feet for 20 GN , 2", 100-130mm	PNC 922707	
<ul> <li>Pair of AISI 304 stainless steel grids, GN 1/1</li> </ul>	PNC 922017		Mesh grilling grid, GN 1/1	PNC 922713	
<ul> <li>Pair of grids for whole chicken (8 per</li> </ul>	r PNC 922036		<ul> <li>Probe holder for liquids</li> </ul>	PNC 922714	
grid - 1,2kg each), GN 1/1			• Levelling entry ramp for 20 GN 1/1 oven		
<ul> <li>AISI 304 stainless steel grid, GN 1/1</li> </ul>	PNC 922062		<ul> <li>Exhaust hood with fan for 20 GN 1/1</li> </ul>	PNC 922730	
• Grid for whole chicken (4 per grid -	PNC 922086		<ul><li>e Exhaust hood without fan for 20 1/1GN</li></ul>	PNC 922735	
1,2kg each), GN 1/2 • External side spray unit (needs to be	PNC 922171		oven	FINC 922733	_
mounted outside and includes suppleto be mounted on the oven)		_	• Holder for trolley handle (when trolley is in the oven) for 20 GN oven	PNC 922743	
Baking tray for 5 baguettes in	PNC 922189		<ul> <li>Tray for traditional static cooking, H=100mm</li> </ul>	PNC 922746	
<ul><li>perforated aluminum with silicon coating, 400x600x38mm</li><li>Baking tray with 4 edges in perforate</li></ul>	ed PNC 922190		<ul> <li>Double-face griddle, one side ribbed and one side smooth, 400x600mm</li> </ul>	PNC 922747	
aluminum, 400x600x20mm			• Trolley with tray rack, 20 GN 1/1, 63mm	PNC 922753	
Baking tray with 4 edges in aluminur 400x600x20mm		_	pitch • Trolley with tray rack, 16 GN 1/1, 80mm	PNC 922754	
Pair of frying baskets	PNC 922239		pitch		_
AISI 304 stainless steel bakery/pasti grid 400x600mm			<ul> <li>Banquet trolley with rack holding 54 plates for 20 GN 1/1 oven and blast chiller freezer, 74mm pitch</li> </ul>	PNC 922756	
• Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922266		Bakery/pastry trolley with rack holding 600x400mm grids for 20 GN 1/1 oven	PNC 922761	
USB probe for sous-vide cooking	PNC 922281		and blast chiller freezer, 80mm pitch (16		
<ul> <li>Grease collection tray, GN 1/1, H=100 mm</li> </ul>			runners)  • Banquet trolley with rack holding 45	PNC 922763	
<ul> <li>Kit universal skewer rack and 4 long skewers for Lenghtwise ovens</li> </ul>			plates for 20 GN 1/1 oven and blast chiller freezer, 90mm pitch	FINC 722703	_
Universal skewer rack	PNC 922326		• Kit compatibility for aos/easyline trolley	PNC 922769	
<ul><li>4 long skewers</li><li>Volcano Smoker for lengthwise and</li></ul>	PNC 922327 PNC 922338		(produced till 2019) with SkyLine/ Magistar 20 GN 1/1 combi oven		
crosswise oven	FINC 922550	_	Kit compatibility for aos/easyline 20 GN	PNC 922771	
<ul> <li>Multipurpose hook</li> </ul>	PNC 922348		oven with SkyLine/Magistar trolleys		
• Grid for whole duck (8 per grid - 1,8k	g PNC 922362		Water inlet pressure reducer	PNC 922773	
each), GN 1/1  Thermal cover for 20 GN 1/1 oven ar	nd PNC 922365		• Extension for condensation tube, 37cm		
blast chiller freezer	IG FINC 722505	_	<ul> <li>Non-stick universal pan, GN 1/1, H=40mm</li> </ul>	PNC 925001	
<ul> <li>Wall mounted detergent tank holder</li> </ul>			<ul> <li>Non-stick universal pan, GN 1/1,</li> </ul>	PNC 925002	
USB single point probe	PNC 922390		H=60mm	DNIC 005007	
<ul> <li>Quenching system update for SkyLir Ovens 20GN</li> </ul>			Double-face griddle, one side ribbed and one side smooth, GN 1/1      Alvariance arith CN 1/1	PNC 925003	
<ul> <li>IoT module for OnE Connected and SkyDuo (one IoT board per appliand to connect oven to blast chiller for</li> </ul>	PNC 922421 ce -		<ul> <li>Aluminum grill, GN 1/1</li> <li>Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1</li> </ul>	PNC 925004 PNC 925005	
Cook&Chill process).		_	• Flat baking tray with 2 edges, GN 1/1	PNC 925006	
Connectivity router (WiFi and LAN)	PNC 922435		Baking tray for 4 baguettes, GN 1/1	PNC 925007	
<ul> <li>SkyDuo Kit - to connect oven and be chiller freezer for Cook&amp;Chill proces</li> <li>The kit includes 2 boards and cables</li> <li>Not for OnE Connected</li> </ul>	S.		Potato baker for 28 potatoes, GN 1/1	PNC 925008	















<ul> <li>Non-stick universal pan, GN 1/2, H=20mm</li> </ul>	PNC 925009	
<ul> <li>Non-stick universal pan, GN 1/2, H=40mm</li> </ul>	PNC 925010	
<ul> <li>Non-stick universal pan, GN 1/2, H=60mm</li> </ul>	PNC 925011	
Recommended Detergents		
	PNC 0S2394	













# Front 35 7/8 73 1/16 " 1855 mm 70 5/8 " 1794 mm 1/4 t 12 9/16 ' 319 mm 33 7/16 " 1 1/4 '

2 11/16 2 15/16 " 797 mm 74 mm 1604 mm 63 1/8 G D DO 291 4 7/8 "

Cold Water inlet 1 (cleaning) = Cold Water Inlet 2 (steam generator) CWI2

C E IEC TECEE

Drain

DO Overflow drain pipe

> Top 4 3/4 " 1 15/16 " 50 mm 19 11/16 13 3/4 '

ΕI

Electrical inlet (power)

Gas connection

#### **Electric**

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Circuit breaker required

Supply voltage: 220-240 V/1 ph/50 Hz

Electrical power, max: 1.8 kW 1.8 kW Electrical power, default:

Gas

Total thermal load: 184086 BTU (54 kW)

54 kW Gas Power:

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

diameter: 1" MNPT

Water:

Side

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWI1,

CWI2): 3/4" Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D":

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

Installation:

Clearance: 5 cm rear and

Clearance: right hand sides.

Suggested clearance for service access: 50 cm left hand side.

Capacity:

16 (400x600 mm) Travs type:

Max load capacity: 100 kg

**Key Information:** 

Right Side Door hinges: External dimensions, Width: 911 mm External dimensions, Depth: 864 mm 1794 mm External dimensions, Height: 301 kg Weight: Net weight: 301 kg Shipping weight: 334 kg Shipping volume: 1.83 m<sup>3</sup>

**ISO** Certificates

ISO 9001; ISO 14001; ISO

ISO Standards: 45001; ISO 50001

> SkyLine PremiumS Natural Gas Combi Oven 16 trays, 600x400mm Bakery

