

SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, **Green Version**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



229765 (ECOG202T3G0)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 20x2/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door

229795 (ECOG202T3G6)

SkyLine PremiumS combi boiler oven with touch screen control, 20x2/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator, 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 trolley rack 2/1 GN, 63 mm pitch.
- Adjustable levelling feet.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants perfamily.
- Cycles+:
 Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
 - Advanced Food Safe Control (to drive the cooking
- with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Automatic fast cool down and pre-heat function.







SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 20 GN 2/1 or 40 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.
- Supplied with n.1 trolley rack 2/1 GN, 63 mm pitch.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Pictures upload for full customization of cooking cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of

the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.

 Zero Waste provides chefs with useful tips for minimizing food waste.

Zero Waste is a library of Automatic recipes that aims to:

-give a second life to raw food close to expiration date (e. g.: from milk to yogurt)

-obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)

-promote the use of typically discarded food items (e.g.: carrot peels).

Included Accessories

 1 of Trolley with tray rack 20 GN 2/1, PNC 922757 63mm pitch

Optional Accessories

Optional Accessories		
 External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens 	PNC 864388	
Water filter with cartridge and flow meter for high steam usage (combi used mainly in steaming mode)	PNC 920003	
Water filter with cartridge and flow meter for medium steam usage	PNC 920005	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	
External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)	PNC 922171	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189	
• Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190	
 Baking tray with 4 edges in aluminum, 400x600x20mm 	PNC 922191	
 Pair of frying baskets 	PNC 922239	
 AISI 304 stainless steel bakery/pastry grid 400x600mm 	PNC 922264	
 Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922266	
 USB probe for sous-vide cooking 	PNC 922281	
 Universal skewer rack 	PNC 922326	
 6 short skewers 	PNC 922328	
 Volcano Smoker for lengthwise and crosswise oven 	PNC 922338	
 Multipurpose hook 	PNC 922348	
 Grease collection tray, GN 2/1, H=60 mm 	PNC 922357	
• Grid for whole duck (8 per grid - 1,8kg each), GN 1/1	PNC 922362	
 Thermal cover for 20 GN 2/1 oven and blast chiller freezer 	PNC 922367	
Wall mounted detergent tank holder	PNC 922386	
 USB single point probe 	PNC 922390	
IoT module for OnE Connected and	PNC 922421	

SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

SkyDuo (one IoT board per appliance -

to connect oven to blast chiller for

Connectivity router (WiFi and LAN)

Cook&Chill process).











PNC 922435

 \Box



SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

•	SkyDuo Kit - to connect oven and blast chiller freezer for Cook&Chill process. The kit includes 2 boards and cables.	PNC 922439	 C25 Rinse & Descale Tabs, phosphate- free, phosphorous-free, maleic acid- free, 50 tabs bucket C32 Classing Tabs, phosphate free 	PNC 0S2394 PNC 0S2395
•	Not for OnE Connected External connection kit for liquid detergent and rinse aid	PNC 922618	 C22 Cleaning Tabs, phosphate-free, phosphorous-free, 100 bags bucket 	PNC 032393
	Dehydration tray, GN 1/1, H=20mm	PNC 922651		
	Flat dehydration tray, GN 1/1	PNC 922652		
	Heat shield for 20 GN 2/1 oven	PNC 922658		
	•	PNC 922670		
	Kit to convert from natural gas to LPG	PNC 922671		
	Kit to convert from LPG to natural gas			
	Flue condenser for gas oven	PNC 922678		
	Trolley with tray rack, 15 GN 2/1, 84mm pitch	PNC 922686		
	Kit to fix oven to the wall	PNC 922687		
•	Adjustable wheels for 20 GN 1/1 and 20 GN 2/1 ovens	PNC 922701		
•	4 flanged feet for 20 GN , 2", 100-130mm	PNC 922707		
•	Mesh grilling grid, GN 1/1	PNC 922713		
•	Probe holder for liquids	PNC 922714		
•	Levelling entry ramp for 20 GN 2/1 oven	PNC 922716		
•	Holder for trolley handle (when trolley is in the oven) for 20 GN oven	PNC 922743		
•	Tray for traditional static cooking, H=100mm	PNC 922746		
•	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747		
•	Trolley with tray rack 20 GN 2/1, 63mm pitch	PNC 922757		
•	Trolley with tray rack, 16 GN 2/1, 80mm pitch	PNC 922758		
•	Banquet trolley with rack holding 92 plates for 20 GN 2/1 oven and blast chiller freezer, 85mm pitch	PNC 922760		
•	Bakery/pastry trolley with rack holding 400x600mm grids for 20 GN 2/1 oven and blast chiller freezer, 80mm pitch (16 runners)	PNC 922762		
•	Banquet trolley with rack holding 116 plates for 20 GN 2/1 oven and blast chiller freezer, 66mm pitch	PNC 922764		
•	Kit compatibility for aos/easyline trolley (produced till 2019) with SkyLine/ Magistar 20 GN 2/1 combi oven	PNC 922770		
•	Kit compatibility for aos/easyline 20 GN oven with SkyLine/Magistar trolleys	PNC 922771		
•	Water inlet pressure reducer	PNC 922773		
•	Extension for condensation tube, 37cm	PNC 922776		
	Non-stick universal pan, GN 1/1, H=40mm	PNC 925001		
•	Non-stick universal pan, GN 1/1, H=60mm	PNC 925002		
•	Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003		
•	Aluminum grill, GN 1/1	PNC 925004		
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005		
•	Flat baking tray with 2 edges, GN 1/1	PNC 925006		
	Potato baker for 28 potatoes, GN 1/1	PNC 925008		





Recommended Detergents










SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, **Green Version**

Front 45 3/4 ' 1162 mm 73 1/16 " 1856 mm 70 5/8 " 1794 mm 108 mm 4 1/4 14 9/16 370 mm 43 5/16 1 1/4 1100 mm Side




CWII Cold Water inlet 1 (cleaning) Cold Water Inlet 2 (steam nerator) CWI2

ΕI Electrical inlet (power) Gas connection

D Drain

DO Overflow drain pipe



Electric

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Circuit breaker required

Supply voltage:

229765 (ECOG202T3G0) 220-240 V/1 ph/50 Hz 220-230 V/1 ph/60 Hz 229795 (ECOG202T3G6)

2.5 kW Electrical power, max: Electrical power, default: 2.5 kW

340900 BTU (100 kW) Total thermal load:

Gas Power: 100 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection 1" MNPT diameter:

Water:

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWII,

3/4" CWI2): Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

Installation:

Clearance: 5 cm rear and

right hand sides. Clearance:

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Trays type: 20 (GN 2/1) Max load capacity: 200 kg

Key Information:

Door hinges: Right Side 1162 mm External dimensions, Width: External dimensions, Depth: 1066 mm External dimensions, Height: 1794 mm 408 kg Weight: Net weight: 408 kg Shipping weight: 446 kg Shipping volume: 2.77 m³

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards: 45001; ISO 50001











