

SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, **Green Version**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



229765 (ECOG202T3G0)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 20x2/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door

229795 (ECOG202T3G6)

SkyLine PremiumS combi boiler oven with touch screen control, 20x2/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, Green Version with 3-glass door

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator, 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Triple-glass door with double LED lights line
- Stainless steel construction throughout
- Supplied with n.1 trolley rack 2/1 GN, 63 mm pitch.
- Adjustable levelling feet.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants perfamily.
- Cycles:
 Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycle (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
 - Advanced Food Safe Control (to drive the cooking
- with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.







SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 20 GN 2/1 or 40 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX5 spray water protection certification for easy cleaning.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.
- Supplied with n.1 trolley rack 2/1 GN, 63 mm pitch.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) color-blind friendly panel.
- Pictures upload for full customization of cooking cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

Sustainability

- 10
- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.













- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste.
 - Zero Waste is a library of Automatic recipes that aims to:
 -give a second life to raw food close to expiration date (e.
- g., from milk to yogurt)-obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g., carrot peels).

Included Accessories

 1 of Trolley with tray rack 20 GN 2/1, PNC 922757 63mm pitch

Optional Accessories

• External reverse osmosis filter for single PNC 864388 tank Dishwashers with atmosphere boiler and Ovens PNC 920003 Water filter with cartridge and flow meter for high steam usage (combi used mainly in steaming mode) Water filter with cartridge and flow PNC 920005 \Box meter for medium steam usage Pair of AISI 304 stainless steel grids, PNC 922017 GN 1/1 • Pair of grids for whole chicken (8 per PNC 922036 grid - 1,2kg each), GN 1/1 PNC 922062 AISI 304 stainless steel grid, GN 1/1 External side spray unit (needs to be PNC 922171 mounted outside and includes support to be mounted on the oven) • Baking tray for 5 baguettes in PNC 922189 perforated aluminum with silicon coating, 400x600x38mm PNC 922190 Baking tray with 4 edges in perforated aluminum, 400x600x20mm • Baking tray with 4 edges in aluminum, PNC 922191 400x600x20mm PNC 922239 • Pair of frying baskets AISI 304 stainless steel bakery/pastry PNC 922264 grid 400x600mm Grid for whole chicken (8 per grid -PNC 922266 1,2kg each), GN 1/1 USB probe for sous-vide cooking PNC 922281 Universal skewer rack PNC 922326 · 6 short skewers PNC 922328 PNC 922338 • Volcano Smoker for lengthwise and crosswise oven PNC 922348 Multipurpose hook PNC 922357 Grease collection tray, GN 2/1, H=60 mm Grid for whole duck (8 per grid - 1,8kg PNC 922362 each), GN 1/1

> SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

Thermal cover for 20 GN 2/1 oven and

SkyDuo (one IoT board per appliance -

Wall mounted detergent tank holder

IoT module for OnE Connected and

to connect oven to blast chiller for

blast chiller freezer

USB single point probe

Cook&Chill process).

PNC 922367

PNC 922386

PNC 922390

PNC 922421



SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, Green Version

	Connectivity router (WiFi and LAN) SkyDuo Kit - to connect oven and blast	PNC 922435 PNC 922439		 C25 Rinse & Descale Tabs, phosphate- free, phosphorous-free, maleic acid- free, 50 tabs bucket 	PNC 0S2394
	chiller freezer for Cook&Chill process. The kit includes 2 boards and cables. Not for OnE Connected			C22 Cleaning Tabs, phosphate-free, phosphorous-free, 100 bags bucket	PNC 0S2395
•	External connection kit for liquid detergent and rinse aid	PNC 922618			
•	Dehydration tray, GN 1/1, H=20mm	PNC 922651			
	Flat dehydration tray, GN 1/1	PNC 922652			
	Heat shield for 20 GN 2/1 oven	PNC 922658			
	Kit to convert from natural gas to LPG	PNC 922670	ā		
	Kit to convert from LPG to natural gas	PNC 922671	ā		
	Flue condenser for gas oven	PNC 922678			
	Trolley with tray rack, 15 GN 2/1, 84mm pitch	PNC 922686	٥		
•	Kit to fix oven to the wall	PNC 922687			
•	Adjustable wheels for 20 GN 1/1 and 20 GN 2/1 ovens	PNC 922701			
•	4 flanged feet for 20 GN , 2", 100-130mm	PNC 922707			
•	Mesh grilling grid, GN 1/1	PNC 922713			
	Probe holder for liquids	PNC 922714			
•	Levelling entry ramp for 20 GN 2/1 oven	PNC 922716			
	Holder for trolley handle (when trolley is in the oven) for 20 GN oven				
•	Tray for traditional static cooking, H=100mm	PNC 922746			
•	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747			
	Trolley with tray rack 20 GN 2/1, 63mm pitch	PNC 922757			
•	Trolley with tray rack, 16 GN 2/1, 80mm pitch	PNC 922758			
•	Banquet trolley with rack holding 92 plates for 20 GN 2/1 oven and blast chiller freezer, 85mm pitch	PNC 922760			
•	Bakery/pastry trolley with rack holding 400x600mm grids for 20 GN 2/1 oven and blast chiller freezer, 80mm pitch (16 runners)	PNC 922762			
_	,	PNC 922764			
•	Banquet trolley with rack holding 116 plates for 20 GN 2/1 oven and blast chiller freezer, 66mm pitch	FINC 922704	J		
•	Kit compatibility for aos/easyline trolley (produced till 2019) with SkyLine/ Magistar 20 GN 2/1 combi oven	PNC 922770			
•	Kit compatibility for aos/easyline 20 GN oven with SkyLine/Magistar trolleys	PNC 922771			
•	Water inlet pressure reducer	PNC 922773			
	•	PNC 922776			
	Non-stick universal pan, GN 1/1,	PNC 925001			
-	H=40mm	1110 720001	_		
•	Non-stick universal pan, GN 1/1, H=60mm	PNC 925002			
	Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003	_		
	Aluminum grill, GN 1/1	PNC 925004			
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005	_		
	Flat baking tray with 2 edges, GN 1/1	PNC 925006			
•	Potato baker for 28 potatoes, GN 1/1	PNC 925008			

Recommended Detergents














SkyLine PremiumS Natural Gas Combi Oven 20GN2/1, **Green Version**

Front 45 3/4 ' 1162 mm 73 1/16 " 1856 mm 70 5/8 " 1794 mm 108 mm 4 1/4 14 9/16 370 mm 43 5/16 1 1/4 1100 mm




CWII Cold Water inlet 1 (cleaning) Cold Water Inlet 2 (steam nerator) CWI2

ΕI Electrical inlet (power) Gas connection

D Drain DO

Overflow drain pipe



Electric

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Circuit breaker required

Supply voltage:

229765 (ECOG202T3G0) 220-240 V/1 ph/50 Hz 220-230 V/1 ph/60 Hz 229795 (ECOG202T3G6)

2.5 kW Electrical power, max: Electrical power, default: 2.5 kW

340900 BTU (100 kW) Total thermal load:

Gas Power: 100 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection 1" MNPT diameter:

Water:

Side

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWII,

3/4" CWI2): Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

Installation:

Clearance: 5 cm rear and

right hand sides. Clearance:

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Trays type: 20 (GN 2/1) Max load capacity: 200 kg

Key Information:

Door hinges: Right Side 1162 mm External dimensions, Width: External dimensions, Depth: 1066 mm External dimensions, Height: 1794 mm 408 kg Weight: Net weight: 408 kg Shipping weight: 446 kg Shipping volume: 2.77 m³

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards: 45001; ISO 50001









