

SkyLine Premium Natural Gas Combi Oven 6GN1/1

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



217880 (ECOG61B2G0)

SkyLine Premium Combi Boiler Oven with digital control, 6x1/1GN, gas, programmable, automatic cleaning

225860 (ECOG61B2G6)

SkyLine Premium combi boiler oven with digital control, 6x1/1GN, gas, programmable, automatic cleaning

Short Form Specification

Item No.

Combi oven with digital interface with guided selection.

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 5 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Digital interface with LED backlight buttons with guided selection.
- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking.
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 6 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy







SkyLine Premium Natural Gas Combi Oven 6GN1/1

4 flanged feet for 6 & 10 GN, 2",

cleaning.

• Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

User Interface & Data Management

- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).

Sustainability

- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.

Optional Accessories

Optional Accessories		
 External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens 	PNC 864388	
 Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day) 	PNC 920004	
 Water filter with cartridge and flow meter for medium steam usage 	PNC 920005	
 Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) 	PNC 922003	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	
 Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 	PNC 922086	

to be mounted on the oven)	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189
 Baking tray with 4 edges in perforated aluminum, 400x600x20mm 	PNC 922190
 Baking tray with 4 edges in aluminum, 400x600x20mm 	PNC 922191
 Pair of frying baskets 	PNC 922239

• External side spray unit (needs to be

• AISI 304 stainless steel bakery/pastry

grid 400x600mm

mounted outside and includes support

<u> </u>	
Double-step door opening kit	PNC 922265
Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922266
Grease collection tray, GN 1/1, H=100	PNC 922321
	Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1

	mm	
•	Kit universal skewer rack and 4 long skewers for Lenghtwise ovens	PNC 922324

	skewers for Lengillwise overis	
•	Universal skewer rack	PNC 922326
•	4 long skewers	PNC 922327
•	Volcano Smoker for lengthwise and	PNC 922338

	crosswise oven	- 3				
•	Multipurpose hook			PNC 92	22348	

100-130mm	
Grid for whole duck (8 per grid - 1,8kg	PNC 922362
each) GN 1/1	

PNC 922351

•	Tray support for 6 & 10 GN 1/1	PNC 922382	
	disassembled open base		

•	Wall mounted detergent tank holder	PNC 922386	
•	USB single point probe	PNC 922390	

•	osb single point probe	PINC 922390
•	IoT module for OnE Connected and	PNC 922421
	SkyDuo (one IoT board per appliance -	
	to connect oven to blast chiller for	
	Cook&Chill process).	

•	Connectivity router (WiFi and LAN)	PNC 922435	
•	Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve	PNC 922438	

	with pipe for drain)		
•	Tray rack with wheels, 6 GN 1/1, 65mm	PNC 922600	

	pitch		
•	Tray rack with wheels, 5 GN 1/1, 80mm pitch	PNC 922606	

 Bakery/pastry tray rack with wheels 	PNC 922607
400x600mm for 6 GN 1/1 oven and	
blast chiller freezer, 80mm pitch (5	
runners)	

 Slide-in rack with handle for 6 & 10 GN 	PNC 922610
l/l oven	
• Open base with tray support for 6 & 10	PNC 922612

 Open base with tray support for 6 & 10 GN 1/1 oven 	PNC 922612	
 Cupboard base with tray support for 6 & 10 GN 1/1 oven 	PNC 922614	

•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or		
	400x600mm trays		
•	External connection kit for liquid	PNC 922618	

	detergent and rinse aid		
•	Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device for drain)	PNC 922619	
	op 0.1, 0.000 at 0.100 io. a. a		

on gas 6 GN 1/1 oven	
• Stacking kit for 6 GN 1/1 oven placed PNC 922623	3 🗆
on gas 10 GN 1/1 oven	
 Trolley for slide-in rack for 6 & 10 GN 1/1 PNC 922626 	5 🗆

• Stacking kit for 6 GN 1/1 oven placed

11011cy 101 311dc 111 1dck 101 0 & 10 011 1/1 1 110 722020	_
oven and blast chiller freezer	
• Trolley for mobile rack for 2 stacked 6 PNC 922628	
GN 1/1 ovens on riser	

Trolley for mobile rack for 6 GN 1/1 on 6 PNC 922630 or 10 GN 1/1 ovens	
 Riser on feet for 2 6 GN 1/1 ovens or a 6 PNC 922632 	

GN 1/1 oven on base	_
 Riser on wheels for stacked 2x6 GN 1/1 PNC 922635 ovens, height 250mm 	5 🗆

ovens, neight 250mm		
 Stainless steel drain kit for 6 & 10 GN oven, dia=50mm 	PNC 922636	
oven, dia-somm		
DI II I I I I I I I I I I I I I I I I I	D) 10 000 (77	

 Plastic drain kit for 6 &10 GN oven, dia=50mm 	PNC 922637	
• Grease collection kit for GN 1/1-2/1	PNC 922639	

•	Grease collection kit for GN 1/1-2/1	PNC 922639	
	open base (2 tanks, open/close device		
	for drain)		
•	Wall support for 6 GN 1/1 oven	PNC 922643	

 Dehydration tray, GN 1/1, H=20mm 	PNC 922651	
• Flat dehydration tray, GN 1/1	PNC 922652	













PNC 922171

PNC 922264



PNC 922622



SkyLine Premium Natural Gas Combi Oven 6GN1/1

•	Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382	PNC 922653		 Baking tray for 4 baguettes, GN 1/1 Potato baker for 28 potatoes, GN 1/1 Non-stick universal pan, GN 1/2, 	PNC 925007 PNC 925008 PNC 925009
•	Bakery/pastry rack kit for 6 GN 1/1 oven with 5 racks 400x600mm and 80mm pitch	PNC 922655		H=20mm • Non-stick universal pan, GN 1/2, H=40mm	PNC 925010
•	Stacking kit for 6 GN 1/1 combi or convection oven on 15&25kg blast	PNC 922657		Non-stick universal pan, GN 1/2, H=60mm	PNC 925011
•	chiller/freezer crosswise Heat shield for stacked ovens 6 GN 1/1	PNC 922660		 Compatibility kit for installation on previous base GN 1/1 	PNC 930217
•	on 6 GN 1/1 Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661		Recommended Detergents • C25 Rinse & Descale Tabs, phosphate-	PNC 0S2394
•	Heat shield for 6 GN 1/1 oven	PNC 922662		free, phosphorous-free, maleic acid-	1110 002071
	Kit to convert from natural gas to LPG	PNC 922670		free, 50 tabs bucket	
	Kit to convert from LPG to natural gas	PNC 922671		 C22 Cleaning Tabs, phosphate-free, 	PNC 0S2395
	Flue condenser for gas oven	PNC 922678		phosphorous-free, 100 bags bucket	
	Fixed tray rack for 6 GN 1/1 and 400x600mm grids	PNC 922684			
•	Kit to fix oven to the wall	PNC 922687			
•	Tray support for 6 & 10 GN 1/1 oven base	PNC 922690			
	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693			
	Detergent tank holder for open base	PNC 922699			
	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702			
	Wheels for stacked ovens	PNC 922704			
•	Chimney adaptor needed in case of conversion of 6 GN 1/1 or 6 GN 2/1 ovens from natural gas to LPG	PNC 922706			
•	Mesh grilling grid, GN 1/1	PNC 922713			
	Probe holder for liquids	PNC 922714			
	Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728	ū		
•	Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922732			
	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733			
	Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737			
	Fixed tray rack, 5 GN 1/1, 85mm pitch	PNC 922740			
	4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	_		
	Tray for traditional static cooking, H=100mm	PNC 922746			
	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747			
	Trolley for grease collection kit	PNC 922752			
	Water inlet pressure reducer	PNC 922773			
	Extension for condensation tube, 37cm	PNC 922776			
	Non-stick universal pan, GN 1/1, H=20mm	PNC 925000			
	Non-stick universal pan, GN 1/1, H=40mm	PNC 925001			
	Non-stick universal pan, GN 1/1, H=60mm	PNC 925002			
	Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003			
	Aluminum grill, GN 1/1	PNC 925004			
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005			
•	Flat baking tray with 2 edges, GN 1/1	PNC 925006			


















SkyLine Premium Natural Gas Combi Oven 6GN1/1

Front 34 1/8 ' D 1528 mm 60 3/16 " 14 3/16 12 11/16 " 360 mm 322 mm 5/16 185 mm 29 9/16 2 5/16 "




Cold Water inlet 1 (cleaning) CWII CWI2 Cold Water Inlet 2 (steam

ΕI Electrical inlet (power) Gas connection

generator)

Drain

DO Overflow drain pipe





Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Circuit breaker required

Supply voltage:

217880 (ECOG61B2G0) 220-240 V/1 ph/50 Hz 225860 (ECOG61B2G6) 220-230 V/1 ph/60 Hz

Electrical power, max: 11 kW Electrical power, default: 1.1 kW

Total thermal load: 64771 BTU (19 kW) Gas Power: 19 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection 1/2" MNPT diameter:

Water:

Side

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWI1,

3/4" CWI2): Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D":

Electrolux Professional recommends the use of treated water,

50mm

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

Installation:

Clearance: 5 cm rear and

right hand sides. Clearance:

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Trays type: 6 (GN 1/1) Max load capacity: 30 kg

Key Information:

Door hinges: Right Side 867 mm External dimensions, Width: External dimensions, Depth: 775 mm External dimensions, Height: 808 mm Weight:

217880 (ECOG61B2G0) 132 kg 225860 (ECOG61B2G6) 135 kg

Net weight:

217880 (ECOG61B2G0) 132 kg 225860 (ECOG61B2G6) 135 kg

Shipping weight:

217880 (ECOG61B2G0) 149 kg 225860 (ECOG61B2G6) 152 kg 0.85 m³ Shipping volume:

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards: 45001; ISO 50001

SkyLine Premium Natural Gas Combi Oven 6GN1/1













