



227782 (ECOG101T2GB)

SkyLine PremiumS Combi Boiler Oven with touch screen control, 8 400x600mm, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, for bakery/pastry, pitch 80mm

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator, 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 pastry tray rack 400x600 mm, 80 mm pitch.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate
 - Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants perfamily.
- Cycles+:
 Regeneration (ideal for banqueting on plate or rethermalizing on tray),
- Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family,
- Proving cycle,
- EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber,
- Sous-vide cooking,
- Static Combi (to reproduce traditional cooking from static oven),
- Pasteurization of pasta,
- Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood),
- Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family,
 - Advanced Food Safe Control (to drive the cooking
- with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking







cycles.

- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 8 GN 1/1 400x600mm trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 pastry tray rack 400x600 mm, 80 mm pitch.

User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

Sustainability



100-130mm

each), GN 1/1

- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler. Protected by registered design (EM003143551 and related family).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a

time and energy efficiency point of view.

- Zero Waste provides chefs with useful tips for minimizing food waste.
 - Zero Waste is a library of Automatic recipes that aims to:
 -give a second life to raw food close to expiration date (e. g.: from milk to yogurt)
 - -obtain genuine and tasty dishes from overripe fruit/ vegetables (usually considered not appropriate for sale)
- -promote the use of typically discarded food items (e.g.: carrot peels).
- Energy Star 2.0 certified product.


Included Accessories

 1 of Bakery/pastry rack kit for 10 GN 1/1 PNC 922656 oven with 8 racks 400x600mm and 80mm pitch

Optional Accessories

_			
•	External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens	PNC 864388	
	Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day)	PNC 920004	
•	Water filter with cartridge and flow meter for medium steam usage	PNC 920005	
	Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003	
•	Pair of AISI 304 stainless steel grids, GN 1/1	PNC 922017	
•	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922036	
•	AISI 304 stainless steel grid, GN 1/1	PNC 922062	
•	Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2	PNC 922086	
•	External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)	PNC 922171	
•	Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm	PNC 922189	
•	Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190	
•	Baking tray with 4 edges in aluminum, 400x600x20mm	PNC 922191	
•	Pair of frying baskets	PNC 922239	
•	AISI 304 stainless steel bakery/pastry grid 400x600mm	PNC 922264	
•	Double-step door opening kit	PNC 922265	
•	Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922266	
•	USB probe for sous-vide cooking	PNC 922281	
•	Grease collection tray, GN 1/1, H=100 mm	PNC 922321	
•	Kit universal skewer rack and 4 long skewers for Lenghtwise ovens	PNC 922324	
•	Universal skewer rack	PNC 922326	
•	4 long skewers	PNC 922327	
•	Multipurpose hook	PNC 922348	
	4 flanged feet for 6 & 10 GN , 2",	PNC 922351	

SkyLine PremiumS Natural Gas Combi Oven 8 trays, 400x600mm Bakery



• Grid for whole duck (8 per grid - 1,8kg



PNC 922362















•	Thermal cover for 10 GN 1/1 oven and blast chiller freezer	PNC 922364		0\	akery/pastry rack kit for 10 GN 1/1 ven with 8 racks 400x600mm and	PNC 922656	
•	Tray support for 6 & 10 GN 1/1 disassembled open base	PNC 922382		• He	· · · · · · · · · · · · · · · · · · ·	PNC 922661	
•	Wall mounted detergent tank holder	PNC 922386			n 10 GN 1/1		_
	USB single point probe	PNC 922390			eat shield for 10 GN 1/1 oven	PNC 922663	
	IoT module for OnE Connected and	PNC 922421		• Ki	it to convert from natural gas to LPG	PNC 922670	
•	SkyDuo (one IoT board per appliance -	1110 /22421	_	• Ki	it to convert from LPG to natural gas	PNC 922671	
	to connect oven to blast chiller for			• Flu	ue condenser for gas oven	PNC 922678	
	Cook&Chill process).				xed tray rack for 10 GN 1/1 and	PNC 922685	
•	Connectivity router (WiFi and LAN)	PNC 922435			00x600mm grids	1110 722000	_
	Grease collection kit for ovens GN 1/1 &				it to fix oven to the wall	PNC 922687	
	2/1 (2 plastic tanks, connection valve with pipe for drain)	7722-100	_	• Tr	ray support for 6 & 10 GN 1/1 oven	PNC 922690	_
•	SkyDuo Kit - to connect oven and blast	PNC 922439			adjustable feet with black cover for 6	PNC 922693	
	chiller freezer for Cook&Chill process.			&	10 GN ovens, 100-115mm		
	The kit includes 2 boards and cables. Not for OnE Connected			• Re	einforced tray rack with wheels, lowest	PNC 922694	
		DNC 000/01			upport dedicated to a grease		
•	Tray rack with wheels 10 GN 1/1, 65mm	PNC 922601			ollection tray for 10 GN 1/1 oven, 64mm		
	pitch	DNIC 000 (00			itch		
•	Tray rack with wheels, 8 GN 1/1, 80mm	PNC 922602			etergent tank holder for open base	PNC 922699	
	pitch	DV10 000 (0.0		 Bo 	akery/pastry runners 400x600mm for	PNC 922702	
•	Bakery/pastry tray rack with wheels	PNC 922608		6	& 10 GN 1/1 oven base		
	holding 400x600mm grids for 10 GN 1/1 oven and blast chiller freezer, 80mm			• W	heels for stacked ovens	PNC 922704	
	pitch (8 runners)			• Sp	oit for lamb or suckling pig (up to	PNC 922709	
_	Slide-in rack with handle for 6 & 10 GN	PNC 922610		12	kg) for GN 1/1 ovens		
•	1/1 oven	FINC 722010	_	• M	esh grilling grid, GN 1/1	PNC 922713	
_	•	PNC 922612			robe holder for liquids	PNC 922714	
•	GN 1/1 oven	FINC 722012	_		xhaust hood with fan for 6 & 10 GN 1/1		
_	Cupboard base with tray support for 6	PNC 922614			vens	1110 722720	_
•	& 10 GN 1/1 oven	FINC 722014	_			PNC 922732	
_	Hot cupboard base with tray support	PNC 922615			r 6+10 GN 1/1 ovens	1110 722702	_
•	for 6 & 10 GN 1/1 oven holding GN 1/1 or		_		khaust hood without fan for 6&10	PNC 922733	
	400x600mm trays				IGN ovens	1110 722700	_
•	External connection kit for liquid	PNC 922618		,	khaust hood without fan for stacking	PNC 922737	
	detergent and rinse aid	1110 /22010	_		+6 or 6+10 GN 1/1 ovens	1110 /22/0/	_
•	Grease collection kit for GN 1/1-2/1	PNC 922619			xed tray rack, 8 GN 1/1, 85mm pitch	PNC 922741	
	cupboard base (trolley with 2 tanks,				xed tray rack, 8 GN 2/1, 85mm pitch	PNC 922742	
	open/close device for drain)				high adjustable feet for 6 & 10 GN	PNC 922745	_
•	Stacking kit for 6 GN 1/1 oven placed	PNC 922623			vens, 230-290mm	1110 722743	_
	on gas 10 GN 1/1 oven				ay for traditional static cooking,	PNC 922746	
•	Trolley for slide-in rack for 6 & 10 GN 1/1	PNC 922626			=100mm	1110 722740	_
	oven and blast chiller freezer				ouble-face griddle, one side ribbed	PNC 922747	
•	Trolley for mobile rack for 6 GN 1/1 on 6	PNC 922630			nd one side smooth, 400x600mm	FINC 722/4/	_
	or 10 GN 1/1 ovens				olley for grease collection kit	PNC 922752	
•	Stainless steel drain kit for 6 & 10 GN	PNC 922636			ater inlet pressure reducer	PNC 922773	
	oven, dia=50mm				· · · · · · · · · · · · · · · · · · ·		
•	Plastic drain kit for 6 &10 GN oven,	PNC 922637			•	PNC 922776	
	dia=50mm				on-stick universal pan, GN 1/1,	PNC 925000	
•	Grease collection kit for GN 1/1-2/1	PNC 922639			=20mm	D. I O OO FOO!	
	open base (2 tanks, open/close device				on-stick universal pan, GN 1/1,	PNC 925001	
	for drain)		_		=40mm	DNIC 005000	
	Wall support for 10 GN 1/1 oven	PNC 922645			on-stick universal pan, GN 1/1, =60mm	PNC 925002	
•	Banquet rack with wheels holding 30	PNC 922648				DNC 025007	
	plates for 10 GN 1/1 oven and blast				ouble-face griddle, one side ribbed nd one side smooth, GN 1/1	PNC 925003	
	chiller freezer, 65mm pitch	DNIC 000770			· · · · · · · · · · · · · · · · · · ·	PNC 925004	
•	Banquet rack with wheels 23 plates for	PNC 922649			luminum grill, GN 1/1		
	10 GN 1/1 oven and blast chiller freezer, 85mm pitch			• Fr	rying pan for 8 eggs, pancakes,	PNC 925005	
_	-	DNC 022451			amburgers, GN 1/1	DNC 025007	
	Dehydration tray, GN 1/1, H=20mm	PNC 922651			at baking tray with 2 edges, GN 1/1	PNC 925006	
	Flat dehydration tray, GN 1/1	PNC 922652			aking tray for 4 baguettes, GN 1/1	PNC 925007	
•	Open base for 6 & 10 GN 1/1 oven,	PNC 922653		• Pc	otato baker for 28 potatoes, GN 1/1	PNC 925008	
	disassembled - NO accessory can be fitted with the exception of 922382						
	inted with the exception of 722302						











SkyLine PremiumS Natural Gas Combi Oven 8 trays, 400x600mm Bakery The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



PNC 925009								
PNC 925010								
PNC 925011								
PNC 930217								
Recommended Detergents								
PNC 0S2394								
PNC 0S2395								
	PNC 925010 PNC 925011 PNC 930217 PNC 0S2394							















D 70 " 1778 mm 12 11/16 " 14 3/16 322 mm

3 " 75 mm 11/16 958 mm CWI1 CWI2 EI 13/16 a 15/16 "


Cold Water inlet 1 (cleaning) CWII = Cold Water Inlet 2 (steam generator) CWI2

ΕI Electrical inlet (power)

Gas connection

Drain

DO Overflow drain pipe



Electric

Front

Side

Default power corresponds to factory test conditions. When supply voltage is declared as a range the test is performed at the average value. According to the country, the installed power may vary within the range.

Circuit breaker required

Supply voltage: 220-240 V/1 ph/50 Hz

Electrical power, max: 1.1 kW 1.1 kW Electrical power, default:

Gas

Total thermal load: 105679 BTU (31 kW)

Gas Power: 31 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

diameter: 1/2" MNPT

Water:

Inlet water temperature, max: 30 °C

Inlet water pipe size (CWI1,

CWI2): 3/4" Pressure, min-max: 1-6 bar Chlorides: <17 ppm Conductivity: 0 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

Installation:

Clearance: 5 cm rear and

right hand sides.

Suggested clearance for service access:

50 cm left hand side.

Capacity:

Clearance:

8 (400x600 mm) Travs type:

Max load capacity: 45 kg

Key Information:

Right Side Door hinges: External dimensions, Width: 867 mm External dimensions, Depth: 775 mm 1058 mm External dimensions, Height: 162 kg Weight: Net weight: 162 kg Shipping weight: 182 kg Shipping volume: 111 m³

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards:

45001; ISO 50001











