

Planetary Mixers

Planetary Mixer, 60 lt. with Hub

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


600279 (BMXM60AB3)

60 lt Planetary Mixer, bowl detection device and SOLID BPA free safety screen, with mechanical speed variator, timer and bowl lighting. Manual bowl movement. Equipped with stainless steel spiral hook, paddle and whisk. With H type accessory hub

Short Form Specification

Item No.

Floor model, suitable for all kneading, blending and whipping operations. Body in non-corrosive material with 18/8 (AISI 302) 60 litre stainless steel bowl. Powerful asynchronous motor (1500 W) with two level mechanical speed variator, with speeds ranging from 1 to 10 (20 to 180 rpm). Bowl detection device allows the mixer to switch on only when the bowl and the safety screen are properly installed and positioned together. Removable and dismantled solid safety screen - made of a bisphenol-A free (BPA) copolyester. Wire safety screen. Control panel with timer and bowl lighting. Manual bowl lifting system. Equipped with accessory drive hub type H (accessories are not included) Supplied with 3 tools: stainless steel spiral kneading hook, cast aluminium paddle and stainless steel wire whisk.

Main Features

- Professional beater mixer for kneading, mixing and whisking all types of food products.
- Delivered with:
 - Stainless steel spiral kneading hook, Cast aluminium paddle, 302 AISI stainless steel whisk and Mixing Bowl for 60 lt
 - Accessory drive hub (accessories are not included)
- Two level mechanical speed variator.
- Maximum capacity (flour, with 60% of hydration) 20 kg, suitable for 400-800 meals per service.
- Waterproof control panel with timer setting knob, speed setting handle and speed display.
- Wire safety screen fitted with a removable chute to add products while working, thus ensuring operator safety.
- Manual bowl lifting and lighting system.
- Safety device will automatically stop the machine if the screen is lifted.
- Solid BPA-free safety screen, covering the stainless steel wire one, limits the flour and unsafe dust particles when used in bakery and pastry preparation.
- Bowl detection device allows the mixer to switch on only when the bowl and the solid safety screen are properly installed and positioned together.

Construction

- Body in non-corrosive material.
- Sturdy construction with mechanically welded strong metal frame.
- 302 AISI Stainless steel bowl - 60 lt. capacity.
- Asynchronous motor with high start-up torque.
- 10 speeds from 20 to 180 rpm (planetary movement), to be set while machine is working, according to the tool and the mixture hardness.
- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- Planetary movement based on self lubricating gears, eliminating any risk of leaks.
- Power: 1500 watts.
- Overload protected planetary system and motor.
- Adjustable feet to perfect stability.

Included Accessories

- | | |
|--|------------|
| • 1 of Bowl 60 lt mixer | PNC 650129 |
| • 1 of Paddle 60 lt | PNC 653083 |
| • 1 of Stainless steel (AISI 303) Spiral Hook for 60 lt planetary mixers | PNC 653084 |
| • 1 of Whisk 60 lt | PNC 653086 |

Optional Accessories

- | | | |
|---|------------|--------------------------|
| • 40 lt reduction kit (bowl, spiral hook, paddle, whisk) for 60 lt and 80 lt planetary mixers | PNC 650127 | <input type="checkbox"/> |
| • Bowl 60 lt mixer | PNC 650129 | <input type="checkbox"/> |
| • Paddle 60 lt | PNC 653083 | <input type="checkbox"/> |


APPROVAL: _____



- Stainless steel (AISI 303) Spiral Hook PNC 653084
for 60 lt planetary mixers
- Whisk 60 lt PNC 653086
- Reinforced Whisk 60 lt (for heavy PNC 653097
duty use)
- Puree strainer for H hub supplied PNC 653187
with 1 screw and 3 grids of 1.5, 3 and
6 mm
- Vegetable cutter, attachment type PNC 653225
H, disconnectable drive, for
planetary mixers
- Bowl scraper 60 lt PNC 653442
- Bowl trolley for 40/60/80 lt planetary PNC 653585
mixers
- Aluminium external support for 82 PNC 653724
mm meat mincer (includes tray and
pusher) - H HUB - To be combined
with a meat mincer kit
- Stainless steel meat mincer kit 82 mm PNC 653725
- Enterprise cut, includes blade (3
discs, diam. 4.5 - 6 and 8 mm)
- Aluminium meat mincer kit 82 mm - PNC 653726
Enterprise cut, includes blade (3
discs, diam. 4.5 - 6 and 8 mm)
- Stainless steel meat mincer kit 82 mm PNC 653727
- 1/2 Unger cut, includes blade (4
discs, diam. 0, 3 - 4.5 and 8 mm)



Front


Electric
Supply voltage:

600279 (BMXM60AB3)

220-240/380-415 V/3 ph/50 Hz

Electrical power max.:

1.54 kW

Total Watts:

1.54 kW

Capacity:
Performance (up to):

 ISO 9001; ISO 14001 kg/
 Cycle

Capacity:

60 litres

Key Information:
External dimensions, Width: 685 mm

External dimensions, Depth: 1087 mm

External dimensions, Height: 1445 mm

Shipping weight:

337 kg


Cold water paste:

 ISO 9001; ISO 14001 kg with
 Spiral hook

Egg whites:

100 with Whisk

Side



EI = Electrical inlet (power)

Top

