

Warewashing

Small Pot & Pan Washer with Drain Pump & Detergent Dispenser

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


506048
 (EPPWESG)

Electric small pot&pan washer with electronic control, drain pump, detergent and rinse aid dispenser - 400V/3N/50Hz
 Electric small pot&pan washer with electronic control, drain pump, detergent and rinse aid dispenser - 400V/3N/60Hz

506049
 (EPPWESG60)

ELEC.POT&PAN WASH+DET-900MM-60HZ

Short Form Specification

Item No.

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned insulated door divided in 2 parts with 180° frontal opening. N. 4 washing cycles.

Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304 welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar).

High efficiency air gap (class A) in water inlet circuit to avoid water being syphoned back into the network as a result of a sudden drop in mains pressure. Fault auto-diagnosis system. Self-cleaning cycle. Drain pump, rinse aid and detergent dispenser included.

Pre-arrangements for connection to an Energy Management device and to an automatic detergent dispenser. WRC compliant components.

Cell dimensions mm670x710x570h.

Load capacity: n. 6 1/1GN trays or n. 3 2/1GN trays.

For front-feed loading. IPX5 water protection.

Supplied with: n. 1 basket in stainless steel and n. 1 rack for containers and trays.

Main Features

- Atmospheric insulated boiler combined with the rinse booster pump for perfect rinsing results (water temperature and pressure always constant during rinsing cycles), independent from the inlet water pressure.
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Open air gap in compliance with WRC regulations.
- 4 washing programs (one program is continual).
- Equipped with drain pump and built-in detergent dispenser for easy and quick installation without opening the machine.
- Easier access to the washing chamber thanks to the 180° frontal opening door.
- Requires limited space for opening thanks to the door divided in 2 sections.
- Self-cleaning cycle.
- Low noise level.
- Simple electronic control panel.
- Fault auto-diagnosis system.
- Simple service from the front.
- Green light of "WASH SAFE CONTROL" confirms that items have been rinsed properly. (only for 506049)

Construction

- 304 stainless steel boiler with higher welding protection to increase resistance to corrosion.
- External connecting board protected by a waterproof plastic box.
- Unit to feature smooth surfaces to facilitate cleaning.
- Easy to remove pump and tank filters.
- Large strainer box above the water surface for frequent cleaning operations.
- Double skin insulated door to reduce heat dispersion.
- Equipped with side washing arms in addition to upper and lower wash arms.
- Pre-arranged to be connected to Energy Management device.
- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- Unit to feature rinse aid dispenser pump.

Sustainability

- Available upon request, pre-arranged model for HACCP implementation (both basic as well as integrated system).

APPROVAL: _____


Included Accessories

- 1 of Extra rack for containers and trays PNC 864182
- 1 of Stainless steel basket for pot washer, 688mm PNC 864191


Optional Accessories

- Filter for partial demineralization PNC 864017
- Kit to measure total and partial water hardness PNC 864050
- Extra rack for containers and trays PNC 864182
- Stainless steel basket for pot washer, 688mm PNC 864191
- Filter for total demineralization PNC 864367
- Kit for trays in Potwashers PNC 864471

Front




Side



CWII = Cold Water inlet 1 (cleaning)	XD = Detergent connection
D = Drain	XR = Rinse aid connection
EI = Electrical inlet (power)	
EO = Electrical Outlet	
HWI = Hot water inlet	
WI = Water inlet	

Top



Electric

Supply voltage:

506048 (EPPWESG)	400 V/3N ph/50 Hz
506049 (EPPWESG60)	380-400 V/3N ph/60 Hz

Default Installed Power:

13 kW

Electrical power max.:

20 kW

Wash pump power:

2.5 kW

Water:

Pressure, bar min/max:

0.5-7 bar

Water supply temperature*:

50 °C

Washing tank capacity (lt):

95

Boiler Capacity (lt):

18

Washing cycle electrical elements:

7 kW

Hot rinse cycle duration (sec.):

ISO 9001; ISO 14001

Key Information:

Washing cycle temperature:

55-65 °C

Hot rinse cycle temperature:

84 °C

N° of working cycles:

4 (180/360/540/inf)

Cell dimensions - width:

670 mm

Cell dimensions - depth:

710 mm

Cell dimensions - height:

570 mm

External dimensions, Width:

876 mm

External dimensions, Depth:

900 mm

External dimensions, Height:

1791 mm

Net weight:

200 kg

Shipping weight:

506048 (EPPWESG)	244 kg
506049 (EPPWESG60)	230 kg

Shipping height:

2030 mm

Shipping width:

506048 (EPPWESG)	1010 mm
506049 (EPPWESG60)	1040 mm

Shipping depth:

506048 (EPPWESG)	1020 mm
506049 (EPPWESG60)	1040 mm

Shipping volume:

506048 (EPPWESG)	2.09 m ³
506049 (EPPWESG60)	2.2 m ³

Sustainability

Rinsing water consumption (per cycle):

7 lt