

Warewashing Small Pot & Pan Washer with Drain Pump & Detergent Dispenser

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



506048 (EPPWESG) Electric small pot&pan washer with electronic control, drain pump, detergent and rinse aid dispenser - 400V/3N/50Hz

Electric small pot&pan washer with electronic control, drain pump, detergent and rinse aid dispenser - 400V/3N/60Hz

506049 (EPPWESG60)

ELEC.POT&PAN WASH+DET-900MM-60HZ

Short Form Specification

Item No.

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned insulated door divided in 2 parts with 180° frontal opening. N. 4 washing cycles.

Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304 welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar).

High efficiency air gap (class A) in water inlet circuit to avoid water being syphoned back into the network as a result of a sudden drop in mains pressure. Fault auto-diagnosis system. Self-cleaning cycle. Drain pump, rinse aid and detergent dispenser included.

Pre-arrangements for connection to an Energy Management device and to an automatic detergent dispenser. WRC compliant components.

Cell dimensions mm670x710x570h.

Load capacity: n. 6 1/1GN trays or n. 3 2/1GN trays.

For front-feed loading. IPX5 water protection.

Supplied with: n.1 basket in stainless steel and n.1 rack for containers and trays.

Main Features

- Atmospheric insulated boiler combined with the rinse booster pump for perfect rinsing results (water temperature and pressure always constant during rinsing cycles), independent from the inlet water pressure.
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Open air gap in compliance with WRC regulations.
- 4 washing programs (one program is continual).
- Equipped with drain pump and built-in detergent dispenser for easy and quick installation without opening the machine.
- Easier access to the washing chamber thanks to the 180° frontal opening door.
- Requires limited space for opening thanks to the door divided in 2 sections.
- Self-cleaning cycle.
- Low noise level.
- Available upon request, pre-arranged model for HACCP implementation (both basic as well as integrated system).
- Simple electronic control panel.
- Fault auto-diagnosis system.
- Simple service from the front.
- Green light of "WASH SAFE CONTROL" confirms that items have been rinsed properly. (only for 506049)

Construction

- 304 stainless steel boiler with higher welding protection to increase resistance to corrosion.
- External connecting board protected by a waterproof plastic box.
- Unit to feature smooth surfaces to facilitate cleaning.
- Easy to remove pump and tank filters.
- Large strainer box above the water surface for frequent cleaning operations.
- Equipped with side washing arms in addition to upper and lower wash arms.
- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- Unit to feature rinse aid dispenser pump.

Sustainability



- Double skin insulated door to reduce heat dispersion.
- Pre-arranged to be connected to Energy Management device.







Warewashing Small Pot & Pan Washer with Drain **Pump & Detergent Dispenser**

Included Accessories

• 1 of Extra rack for containers and	PNC 864182
trays	
• 1 of Stainless steel basket for pot	PNC 864191

washer, 688mm Optional Accessories

Optional Accessories		
• Filter for partial demineralization	PNC 864017	
 Kit to measure total and partial water hardness 	PNC 864050	
• Extra rack for containers and trays	PNC 864182	
 Stainless steel basket for pot washer, 688mm 	PNC 864191	
 Filter for total demineralization 	PNC 864367	
 Kit for trays in Potwashers 	PNC 864471	












Warewashing Small Pot & Pan Washer with Drain Pump & Detergent Dispenser





Cold Water inlet 1 (cleaning) Drain FΙ Electrical inlet (power) EO Electrical Outlet

HWI Hot water inlet wı Water inlet



XR

Electric

Supply voltage:

506048 (EPPWESG) 400 V/3N ph/50 Hz 380-400 V/3N ph/60 Hz 506049 (EPPWESG60)

Electrical power, max: 20 kW **Default Installed Power:** 13 kW Wash pump power: 2.5 kW

Water:

Pressure, min-max: 0.5-7 bar

Washing cycle electrical

7 kW elements:

Hot rinse cycle duration

(sec.):

ISO 9001; ISO 14001

50 °C Water supply temperature*: 95 Washing tank capacity (It): 18 Boiler Capacity (It):

Key Information:

Rinsing water consumption (per cycle):

7 It

55-65 °C Washing cycle temperature: 84 °C Hot rinse cycle temperature:

N° of working cycles: 4 (180/360/540/inf)

Cell dimensions - width: 670 mm 710 mm Cell dimensions - depth: 570 mm Cell dimensions - height: External dimensions, Width: 876 mm 900 mm External dimensions, Depth: 1791 mm External dimensions, Height: Net weight: 200 kg

Shipping weight:

506048 (EPPWESG) 244 kg 506049 (EPPWESG60) 230 kg

Shipping height:

2030 mm

Shipping width:

506048 (EPPWESG) 1010 mm 506049 (EPPWESG60) 1040 mm

Shipping depth:

506048 (EPPWESG) 1020 mm 506049 (EPPWESG60) 1040 mm

Shipping volume:

506048 (EPPWESG) 2.09 m³ 506049 (EPPWESG60) 2.2 m³









Detergent connection

Rinse aid connection

Top