

## Planetary Mixers

### Stainless Steel Planetary Mixer, 60 lt. - Electronic

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**600284 (XBE60X3B)**

60 lt stainless steel Planetary Mixer, bowl detection device and SOLID BPA free safety screen, electronic speed variation with motorized bowl movement, timer and bowl lighting. Equipped with stainless steel spiral hook, paddle and whisk

### Short Form Specification

#### Item No.

Floor model, suitable for all kneading, blending and whipping operations. Stainless steel body and 18/8 (AISI 302) 60 litre stainless steel bowl. Powerful asynchronous motor (4000 W) with electronic speed variator (10 speed levels from 20 to 180 rpm). Motor and mechanism are protected against overloading. Heavy duty safety screen. Removable and dismantled solid safety screen - made of a bisphenol-A free (BPA) copolyester. Control panel with timer and bowl lighting. Geared motor drive system to raise and lower the bowl. Bowl detection device allows the mixer to switch on only when the bowl and the safety screen are properly installed and positioned together. Supplied with 3 tools: stainless steel spiral kneading hook, cast aluminium paddle and stainless steel wire whisk.

### Main Features

- Professional beater mixer for kneading, mixing and whisking all types of food products.
- Electronic speed variator.
- Maximum capacity (flour, with 60% of hydration) 20 kg, suitable for 400-800 meals per service.
- Waterproof control panel with timer and speed setting knobs.
- Wire safety screen fitted with a removable chute to add products while working, thus ensuring operator safety.
- Safety device will automatically stop the machine if the screen is lifted.
- Geared motor drive system activates the raising and lowering of the bowl and bowl lighting.
- Delivered with:
  - Stainless steel spiral kneading hook, Cast aluminum paddle, 302 AISI stainless steel whisk and Mixing Bowl for 60 lt
- Solid BPA-free safety screen, covering the stainless steel wire one, limits the flour and unsafe dust particles when used in bakery and pastry preparation.
- Bowl detection device allows the mixer to switch on only when the bowl and the solid safety screen are properly installed and positioned together.

### Construction

- Body entirely in stainless steel.
- 302 AISI Stainless steel bowl - 60 lt. capacity.
- Asynchronous motor with high start-up torque.
- 10 speeds form 20 to 180 rpm (planetary movement) to adjust to the selected tool and the mixture hardness.
- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- Height adjustable feet.
- Power: 4000 watts.
- Overload protected planetary system and motor.
- Adjustable feet to perfect stability.

### Included Accessories

- |  |            |
|--|------------|
| • 1 of Bowl 60 lt mixer  | PNC 650129 |
| • 1 of Paddle 60 lt  | PNC 653083 |
| • 1 of Stainless steel (AISI 303) Spiral Hook for 60 lt planetary mixers | PNC 653084 |
| • 1 of Whisk 60 lt   | PNC 653086 |

### Optional Accessories

- |   |            |                          |
|---|------------|--------------------------|
| • 40 lt reduction kit (bowl, spiral hook, paddle, whisk) for 60 lt and 80 lt planetary mixers | PNC 650127 | <input type="checkbox"/> |
| • Bowl 60 lt mixer  | PNC 650129 | <input type="checkbox"/> |
| • Paddle 60 lt  | PNC 653083 | <input type="checkbox"/> |
| • Stainless steel (AISI 303) Spiral Hook for 60 lt planetary mixers                           | PNC 653084 | <input type="checkbox"/> |
| • Whisk 60 lt   | PNC 653086 | <input type="checkbox"/> |

APPROVAL: \_\_\_\_\_


- Reinforced Whisk 60 lt (for heavy duty use) PNC 653097
- Bowl scraper 60 lt PNC 653442
- Bowl trolley for 40/60/80 lt planetary mixers PNC 653585




**Electrolux**  
PROFESSIONAL

## Planetary Mixers Stainless Steel Planetary Mixer, 60 lt. - Electronic

Front




Side



EI = Electrical inlet (power)

Top



### Electric

Supply voltage:

600284 (XBE60X3B) 380-440 V/3N ph/50/60 Hz

### Capacity:

Performance (up to):

ISO 9001; ISO 14001 kg/  
Cycle

Capacity:

60 litres

### Key Information:

External dimensions, Width: 685 mm

External dimensions, Depth: 1050 mm

External dimensions, Height: 1445 mm

Shipping weight: 324 kg

Cold water paste: ISO 9001; ISO 14001 kg with  
Spiral hook

Egg whites: 100 with Whisk



Planetary Mixers  
Stainless Steel Planetary Mixer, 60 lt. - Electronic

The company reserves the right to make modifications to the products  
without prior notice. All information correct at time of printing.

2025.02.14