

Planetary Mixers Stainless Steel Planetary Mixer, 60 It. - Electronic

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



600284 (XBE60X3B)

60 It stainless steel Planetary Mixer, bowl detection device and SOLID BPA free safety screen, electronic speed variation with motorized bowl movement, timer and bowl lighting. Equipped with stainless steel spiral hook, paddle and whisk

Short Form Specification

Item No.

Floor model, suitable for all kneading, blending and whipping operations. Stainless steel body and 18/8 (AISI 302) 60 litre stainless steel bowl. Powerful asynchronous motor (4000 W) with electronic speed variator (10 speed levels from 20 to 180 rpm). Motor and mechanism are protected against overloading. Heavy duty safety screen. Removable and dismantled solid safety screen - made of a bisphenol-A free (BPA) copolyester. Control panel with timer and bowl lighting. Geared motor drive system to raise and lower the bowl. Bowl detection device allows the mixer to switch on only when the bowl and the safety screen are properly installed and positioned together.

Supplied with 3 tools: stainless steel spiral kneading hook, cast aluminium paddle and stainless steel wire whisk.

Main Features

- Professional beater mixer for kneading, mixing and whisking all types of food products.
- Electronic speed variator.
- Maximum capacity (flour, with 60% of hydration) 20 kg, suitable for 400-800 meals per service.
- Waterproof control panel with timer and speed setting knobs.
- Wire safety screen fitted with a removable chute to add products while working, thus ensuring operator safety.
- Safety device will automatically stop the machine if the screen is lifted.
- Geared motor drive system activates the raising and lowering of the bowl and bowl lighting.
- Delivered with:
 - -Stainless steel spiral kneading hook, Cast aluminum paddle, 302 AISI stainless steel whisk and Mixing Bowl for 60 lt
- Solid BPA-free safety screen, covering the stainless steel wire one, limits the flour and unsafe dust particles when used in bakery and pastry preparation.
- Bowl detection device allows the mixer to switch on only when the bowl and the solid safety screen are properly installed and positioned together.

Construction

- Body entirely in stainless steel.
- 302 AISI Stainless steel bowl 60 lt. capacity.
- Asynchronous motor with high start-up torque.
- 10 speeds form 20 to 180 rpm (planetary movement) to adjust to the selected tool and the mixture hardness.
- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- Height adjustable feet.
- Power: 4000 watts.
- Overload protected planetary system and motor.
- Adjustable feet for perfect stability.

Included Accessories

• 1 of Bowl 60 It mixer	PNC 650129
• 1 of Paddle 60 lt	PNC 653083
1 of Stainless steel (AISI 303) Spiral Hook for 60 lt planetary mixers	PNC 653084

1 of Whisk 60 lt PNC 653086

Optional Accessories

40 It reduction kit (bowl, spiral PNC 650127 hook, paddle, whisk) for 60 It and 80 It planetary mixers

 Bowl 60 lt mixer
 Paddle 60 lt
 Stainless steel (AISI 303) Spiral Hook for 60 lt planetary mixers

PNC 650129 □
PNC 653083 □
PNC 653084 □

Whisk 60 lt
 PNC 653086 □

APPROVAL:






Planetary Mixers Stainless Steel Planetary Mixer, 60 It. - Electronic

•	Reinforced Whisk 60 It (for heavy duty use)	PNC 653097	
•	Bowl scraper 60 lt	PNC 653442	
•	Bowl trolley for 40/60/80 It planetary mixers	PNC 653585	





Planetary Mixers Stainless Steel Planetary Mixer, 60 It. - Electronic



Electric Supply voltage: 380-440 V/3N ph/50/60 Hz Capacity: Performance (up to): 20 kg/Cycle Capacity: 60 litres

Key Information:

External dimensions, Width: 685 mm External dimensions, Depth: 1050 mm External dimensions, Height: 1445 mm Shipping weight: 324 kg

ISO 9001; ISO 14001 kg with

Cold water paste: Spiral hook Egg whites: 100 with Whisk