

Planetary Mixers Stainless Steel Planetary Mixer for Bakery, 40 lt - Electronic

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



600273 (MBE40XB)

40 It stainless steel Planetary Mixer, bowl detection device and SOLID BPA free safety screen, with 3 fixed speeds and variable speed. Equipped with spiral hook, paddle and reinforced whisk. Suitable for bakery preparations

Short Form Specification

Item No.

Floor model, suitable for all kneading, blending and whipping operations. Stainless steel reinforced body for heavy duty use with 18/8 (AISI 302) 40 litre capacity stainless steel bowl. Powerful asynchronous motor (2200 W) with 3 fixed speeds (40,80,160 rpm) and electronic variable speed (from 30 to 175 rpm). Bowl detction device allows the mixer to switch on only when the bowl and the safety screen are properly installed and positioned together. Water proof (IP55) and flat touch button control panel with timer from 0-59 min. Pivoting and removable wire safety screen. Kneading: speed 1 or 2 with hook; Blending: speed with 2 paddle; Whipping: speed 3 with whisk. Supplied with 3 tools; spiral hook, paddle and reinforced whisk.

Main Features

- Professional beater mixer designed to withstand the strong demands of bakery and pastry making.
- Delivered with:
 - -Spiral Hook, Paddle, Reinforced Whisk and Mixing Bowl for 40 lt
- Kneading speed: "1" with hook.
- Mixing speed: "2" with paddle.
- Emulsifying speed: "3" with whisk.
- Wire safety screen fitted with a removable chute to add products while working, thus ensuring operator safety.
- Pivoting and removable wire safety screen for easier and better cleaning.
- Raising and lowering of the bowl controlled by lever with an automatic locking of the bowl when in the raised position.
- Waterproof touch button control panel with timer, speed setting and display.
- Safety device will automatically stop the machine when the bowl is lowered.
- Maximum capacity (flour, with 60% of hydration)
- Solid BPA-free safety screen, covering the stainless steel wire one, limits the flour and unsafe dust particles when used in bakery and pastry preparation.
- Bowl detection device allows the mixer to switch on only when the bowl and the solid safety screen are properly installed and positioned together.

Construction

- Body entirely in stainless steel.
- Reinforced body, feet and transmission for heavy duty operations.
- 302 AISI Stainless steel bowl 40 lt. capacity.
- Electronic speed variator (10 speeds available from 30 to 175 rpm)
- 3 fixed speeds: 40, 80 and 160 rpm.
- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- Power: 2200 walts.
- Asynchronous motor with high start-up torque.
- The solid safety screen and the stainless steel wire structure are both removable and dismantled for cleaning and are dishwasher safe.
- Adjustable feet to perfect stability.





Planetary Mixers Stainless Steel Planetary Mixer for Bakery, 40 lt - Electronic

Included Accessories

•	1 of Bowl 40 It	PNC	650128
•	1 of Spiral Hook 40 It	PNC	653092
•	1 of Paddle 40 It	PNC	653093
•	1 of Reinforced Whisk 40 lt (for heavy	PNC	653127
	duty use)		

mixers

PNC 650126	
PNC 650128	
PNC 653092	
PNC 653093	
PNC 653094	
PNC 653127	
PNC 653585	
	PNC 650128 PNC 653092 PNC 653093 PNC 653094









Planetary Mixers Stainless Steel Planetary Mixer for Bakery, 40 lt - Electronic

Front -650 Side ΕI Electrical inlet (power) Top

ONVEL CE UK ONVELOUS ON INTERFER

Electric

Supply voltage:

600273 (MBE40XB) 200-240 V/1N ph/50/60 Hz

Electrical power max.: 2.2 kW
Total Watts: 2.2 kW

Capacity:

ISO 9001; ISO 14001 kg/ Performance (up to): Cycle

Performance (up to): Cycle
Capacity: 40 litres

Key Information:

External dimensions, Width: 655 mm
External dimensions, Depth: 850 mm
External dimensions, Height: 1370 mm
Shipping weight: 199 kg

ISO 9001; ISO 14001 kg with

Cold water paste: Spiral hook Egg whites: 70 with Whisk

> Planetary Mixer Stainless Steel Planetary Mixer for Bakery, 40 lt - Electronic