

Planetary Mixers Stainless Steel Planetary Mixer, 30 It. - Electronic with Hub

		Main Features	
		<ul> <li>Professional beater mixer that provides all the basic mixer functions: kneading of all sort of paster mixing of semi-liquid products, emulsions are various sauces.</li> </ul>	es,
		Delivered with:     - Spiral Hook, Paddle, Whisk and Mixing Bowl for     30 It	
		-Accessory drive hub (accessories are not included)	ot
		<ul> <li>Waterproof touch button control panel with time speed setting and display.</li> <li>Electronic speed variator.</li> </ul>	er,
		• Maximum capacity (flour, with 60% of hydration)	7
	30 It stainless steel Planetary Mixer, bowl detection device and SOLID BPA free safety screen, with electronic speed variation. Equipped with spiral hook, paddle, whisk and H type accessory hub	<ul> <li>kg, suitable for 100-300 meals per service.</li> <li>Wire safety screen fitted with a removable chu to add products while working, thus ensurir operator safety.</li> </ul>	te ng
		<ul> <li>Pivoting and removable wire safety screen freese and better cleaning.</li> </ul>	or
600261 (XBE30AX)		<ul> <li>Raising and lowering of the bowl controlled to lever with an automatic locking of the bowl when in the raised position.</li> </ul>	
		<ul> <li>Safety device will automatically stop the machin when the bowl is lowered.</li> </ul>	ne
		<ul> <li>Solid BPA-free safety screen, covering the stainle- steel wire one, limits the flour and unsafe du particles when used in bakery and past preparation.</li> </ul>	st
		Bowl detection device allows the mixer to switch	
		on only when the bowl and the solid safety scree are properly installed and positioned together.	en
Short Form Speci	fication		en
	fication	are properly installed and positioned together. <b>Construction</b> • Body entirely in stainless steel.	en
Short Form Specil	fication	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> </ul> </li> </ul>	en
Item No. Floor model, suitable for all I operations. Body in stainless	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar</li> </ul> </li> </ul>	ry
Item No. Floor model, suitable for all l operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric</li> </ul> </li> </ul>	ry
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. W) with an electronic speed v 180 rpm). Water protected	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir</li> </ul> </li> </ul>	ry nd al
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester.	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> </ul> </li> </ul>	ry nd al
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. s the mixer to switch on only when	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel with the</li></ul></li></ul>	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester.	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel wi structure are both removable and dismantled for the selected for the selected for the selected for the selected for the stainless steel with structure are both removable and dismantled for the selected for</li></ul></li></ul>	ry nd al ng re
Item No. Floor model, suitable for all l operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel with the</li></ul></li></ul>	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bit Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine itinuous operation position. Start/	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 It. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> </ul>	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 It. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatin gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel with structure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> </ul>	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 It. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatir gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> </ul>	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatin gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> <li>Included Accessories <ul> <li>1 of Bowl 30 lt mixer</li> <li>PNC 650123</li> <li>1 of Spiral Hook 30 lt</li> <li>PNC 653165</li> </ul> </li> </ul>	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 It. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatin gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel winstructure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> <li>Included Accessories <ul> <li>1 of Bowl 30 It mixer</li> <li>PNC 650123</li> <li>1 of Spiral Hook 30 It</li> <li>PNC 653165</li> <li>1 of Whisk 30 It</li> </ul> </li> </ul>	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	<ul> <li>are properly installed and positioned together.</li> <li>Construction <ul> <li>Body entirely in stainless steel.</li> <li>302 AISI Stainless steel bowl - 30 lt. capacity.</li> <li>Asynchronous motor with high start-up torque.</li> <li>10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness.</li> <li>Water protected planetary system (IP55 electric controls, IP34 appliance overall).</li> <li>Planetary movement based on self lubricatin gears, eliminating any risk of leaks.</li> <li>Power: 1100 watts.</li> <li>The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe.</li> <li>Adjustable feet for perfect stability.</li> </ul> </li> <li>Included Accessories <ul> <li>1 of Bowl 30 lt mixer</li> <li>PNC 650123</li> <li>1 of Spiral Hook 30 lt</li> <li>PNC 653165</li> </ul> </li> </ul>	ry al ng re or

APPROVAL:

E



<ul> <li>10 It reduction kit (bowl, spiral hook, paddle, whisk) and removable spout for 30 It planetary mixers</li> </ul>	PNC 650124	
<ul> <li>20 It reduction kit (bowl, spiral hook, paddle, whisk) for 30 It planetary mixers</li> </ul>	PNC 650125	
• Spiral Hook 30 It	PNC 653161	
• Paddle 30 lt	PNC 653165	
• Whisk 30 lt	PNC 653166	
<ul> <li>Puree strainer for H hub supplied with 1 screw and 3 grids of 1.5, 3 and 6 mm</li> </ul>	PNC 653187	
<ul> <li>Vegetable cutter, attachment type H, disconnectable drive, for planetary mixers</li> </ul>	PNC 653225	
Reinforced Whisk 30 It (for heavy duty use)	PNC 653253	
<ul> <li>Kit wheels for 20/30/40 litre planetary mixers (only XB models)</li> </ul>	PNC 653552	
<ul> <li>Bowl trolley for 30 lt planetary mixers (cannot be used with wheel kit 653552)</li> </ul>	PNC 653562	
<ul> <li>Aluminium external support for 70 mm meat mincer (includes tray and pusher) - H HUB - To be combined with a meat mincer kit</li> </ul>	PNC 653720	
<ul> <li>Aluminium meat mincer kit 70 mm - Enterprise cut, includes blade (3 discs, diam. 4.5 - 6 and 8 mm)</li> </ul>	PNC 653721	
<ul> <li>Stainless steel meat mincer kit 70 mm</li> <li>Enterprise cut, includes blade (3 discs, diam. 4.5 - 6 and 8 mm)</li> </ul>	PNC 653722	
• Stainless steel meat mincer kit 70 mm	PNC 653723	

- 1/2 Unger cut, includes blade (4 discs, diam. 0, 3 - 4.5 and 8 mm)





## Planetary Mixers Stainless Steel Planetary Mixer, 30 It. - Electronic with Hub

