

Planetary Mixers Stainless Steel Planetary Mixer, 30 It. - Electronic with Hub

		Main Features	
		 Professional beater mixer that provides all the basic mixer functions: kneading of all sort of paster mixing of semi-liquid products, emulsions are various sauces. 	es,
	30 It stainless steel Planetary Mixer, bowl detection device and SOLID BPA free safety screen, with electronic speed variation. Equipped with spiral hook, paddle, whisk and H type accessory hub	 Delivered with: Spiral Hook, Paddle, Whisk and Mixing Bowl for 30 lt 	or
		-Accessory drive hub (accessories are not included)	ot
		 Waterproof touch button control panel with time speed setting and display. Electronic speed variator. 	er,
		• Maximum capacity (flour, with 60% of hydration)	7
		 kg, suitable for 100-300 meals per service. Wire safety screen fitted with a removable chu to add products while working, thus ensurir operator safety. 	te ng
		 Pivoting and removable wire safety screen freese and better cleaning. 	or
600261 (XBE30AX)		 Raising and lowering of the bowl controlled to lever with an automatic locking of the bowl when in the raised position. 	
		 Safety device will automatically stop the machin when the bowl is lowered. 	ne
		 Solid BPA-free safety screen, covering the stainle- steel wire one, limits the flour and unsafe du particles when used in bakery and past preparation. 	st
100		Bowl detection device allows the mixer to switch	
		on only when the bowl and the solid safety scree are properly installed and positioned together.	en
Short Form Speci	fication		en
	fication	are properly installed and positioned together. Construction • Body entirely in stainless steel.	en
Short Form Specil	fication	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. 	en
Item No. Floor model, suitable for all I operations. Body in stainless	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar 	ry
Item No. Floor model, suitable for all l operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric 	ry id
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. W) with an electronic speed v 180 rpm). Water protected	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir 	ry nd al
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester.	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. 	ry nd al
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. s the mixer to switch on only when	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel with the	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester.	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel wi structure are both removable and dismantled for the selected for the selected for the selected for the selected for the stainless steel with structure are both removable and dismantled for the selected for	ry nd al ng re
Item No. Floor model, suitable for all l operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed v 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel with the	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bit Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine itinuous operation position. Start/	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 It. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. 	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 It. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatin gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel with structure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. 	ry nd al ng re
Item No. Floor model, suitable for all I operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 It. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatir gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. 	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatin gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. Included Accessories 1 of Bowl 30 lt mixer PNC 650123 1 of Spiral Hook 30 lt PNC 653165 	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 It. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatin gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel winstructure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. Included Accessories 1 of Bowl 30 It mixer PNC 650123 1 of Spiral Hook 30 It PNC 653165 1 of Whisk 30 It 	ry nd al ng re
Item No. Floor model, suitable for all H operations. Body in stainless capacity stainless steel bowl. I W) with an electronic speed w 180 rpm). Water protected removable wire safety screen safety screen - made of a bi Bowl detection device allows the bowl and the safety sc positioned together. Water p control panel with timer (60 m at the end of the cycle. Con stop button. Adjustable fe accessory drive hub type H	kneading, blending and whipping steel with 18/8 (AISI 302) 30 litre Powerful asynchronous motor (1100 variator (10 speed levels from 30 to planetary system. Pivoting and a. Removable and dismantled solid sphenol-A free (BPA) copolyester. Is the mixer to switch on only when creen are properly installed and proof (IP55) and flat touch button in), which switches off the machine tinuous operation position. Start/ eet for stability. Equipped with d (accessories are not included).	 are properly installed and positioned together. Construction Body entirely in stainless steel. 302 AISI Stainless steel bowl - 30 lt. capacity. Asynchronous motor with high start-up torque. 10 speeds from 30 to 180 rpm (planeta movement), to adjust to the selected tool ar mixture hardness. Water protected planetary system (IP55 electric controls, IP34 appliance overall). Planetary movement based on self lubricatin gears, eliminating any risk of leaks. Power: 1100 watts. The solid safety screen and the stainless steel wi structure are both removable and dismantled for cleaning and are dishwasher safe. Adjustable feet for perfect stability. Included Accessories 1 of Bowl 30 lt mixer PNC 650123 1 of Spiral Hook 30 lt PNC 653165 	ry al ng re or

APPROVAL:

E



• 10 It reduction kit (bowl, spiral hook, paddle, whisk) and removable spout	PNC 650124	
 for 30 It planetary mixers 20 It reduction kit (bowl, spiral hook, paddle, whisk) for 30 It planetary mixers 	PNC 650125	
 Spiral Hook 30 lt Paddle 30 lt Whisk 30 lt Puree strainer for H hub supplied with 1 screw and 3 grids of 1.5, 3 and 6 mm 	PNC 653161 PNC 653165 PNC 653166 PNC 653187	
 Vegetable cutter, attachment type H, disconnectable drive, for planetary mixers 	PNC 653225	
Reinforced Whisk 30 It (for heavy duty use)	PNC 653253	
 Kit wheels for 20/30/40 litre planetary mixers (only XB models) 	PNC 653552	
 Bowl trolley for 30 lt planetary mixers (cannot be used with wheel kit 653552) 	PNC 653562	
 Aluminium external support for 70 mm meat mincer (includes tray and pusher) - H HUB - To be combined with a meat mincer kit 	PNC 653720	
 Aluminium meat mincer kit 70 mm - Enterprise cut, includes blade (3 discs, diam. 4.5 - 6 and 8 mm) 	PNC 653721	
 Stainless steel meat mincer kit 70 mm Enterprise cut, includes blade (3 discs, diam. 4.5 - 6 and 8 mm) 	PNC 653722	
• Stainless steel meat mincer kit 70 mm	PNC 653723	

- 1/2 Unger cut, includes blade (4 discs, diam. 0, 3 - 4.5 and 8 mm)





Planetary Mixers Stainless Steel Planetary Mixer, 30 It. - Electronic with Hub

