

Warewashing Utensil Dishwasher with Wash Safe Control, Drain Pump and Detergent Dispenser

ITEM #		
MODEL #		
MODEL #		
NAME #		
SIS #		
AIA #		



503026 (WTU40ADPD)

Utensil Dishwasher WTU40, 65b/h, with drain pump and atmospheric boiler, detergent dispenser, 1180 p/ h

Short Form Specification

Item No.

Multi-purpose dish/utensil washer. 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. 42 liter wash tank with rounded corners. Double skinned insulated walls and counterbalanced door with double stop. 450mm door clearance. 3 washing cycles. Self cleaning cycle. Digital control panel with display of wash and rinse temperatures. Built-in atmospheric, insulated water boiler (9 kW), 12-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304L welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar). Drain pump. Fault autodiagnosis system. Rinse aid dispenser, detergent dispenser, HACCP and Energy management device.

Hourly capacity: 1170 dishes/65 baskets 500x530mm.

Supplied with: n.1 basket for plates, n.1 wire basket for pizza plates, trays, and small utensils and n.2 cutlery containers.

Main Features

- Built-in atmospheric boiler sized to raise incoming 50 °C water to 84 °C minimum for sanitizing rinse. No external booster is required.
- Constant temperature of 84 °C thoughout the rinsing cycle regardless of the network's water pressure and temperature.
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Green light of "WASH SAFE CONTROL" confirms that items have been rinsed properly.
- Double rack support equipped with either a large 550x535mm rack for pizza plates, trays and utensils or a standard 500x500mm rack for plates, cups and cutlery.
- Equipped with drain pump for easy and quick installation without opening the machine.
- Fault auto-diagnosis system.
- Simple service from the front.
- Easy to remove wash/rinse arms and filter.
- Fully automatic self-cleaning cycle avoids the risk of bacteria proliferation.
- Detergent dispenser for easy connection to the external detergent source.
- Simple control panel, with digital display for wash and rinse temperature.
- Automatic boiler emptying function.
- 55/90/300 seconds cycles.
- Low noise level <65 dBA.

Construction

- Counter-balanced door to minimize impact when opening and closing.
- Unit to feature rinse aid dispenser pump.
- Unit to feature smooth surfaces to facilitate cleaning.
- Wash/rinse arms and nozzles in stainless steel.
- 304 AISI stainless steel front and side panels, wash tank and filter.
- Double skinned construction.
- Completely closed on the back by a cover plate.
- Double wash tank with rounded corners for easier cleaning operations.
- No pipes inside the washing chamber.

Sustainability



- Finished in top quality materials to ensure durability.
- Pre-arrangement for HACCP system implementation and Energy Management device.

APPROVAL:





Included Accessories

 2 of Yellow cutlery container 	PNC 864242
• 1 of Basket for 18 dinner plates -	PNC 867002
vellow	

• 1 of Wire basket for pizza plates, up PNC 867045 to 320mm diam. trays, utensils

Optional Accessories		
• 12lt external manual water softener	PNC 860412	
 Filter for partial demineralization 	PNC 864017	
 Kit to measure total and partial water hardness 	PNC 864050	
 Yellow cutlery container 	PNC 864242	
 Filter for total demineralization 	PNC 864367	
 External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens 	PNC 864388	
 Connectivity kit for Undercounter Dishwashers and Pot Washers (ECAP) 	PNC 864479	
 Kit 4 plastic boxes for cutlery - yellow 	PNC 865574	
Basket for 18 dinner plates - yellow	PNC 867002	
• Cover rack for small and light items (500x500 baskets)	PNC 867016	
 Basket for 16 vertical glasses (h 70 mm - diam 100 mm) - blue 	PNC 867023	
 Basket semi-professional 500x500x190mm 	PNC 867024	
 Wire basket for pizza plates, up to 320mm diam. trays, utensils 	PNC 867045	
 Wire basket (550x535mm) for utensils 	PNC 867046	
 Ethernet connector for ECAP protocol appliances 	PNC 922768	


















Drain

Electrical inlet (power) EO **Electrical Outlet**

HWI Hot water inlet

ΧD Detergent connection Rinse aid connection



Electric

Front

Side

Top

Supply voltage: 400 V/3N ph/50 Hz

16

Total Watts: 12.1 kW 0.8 kW Wash pump power:

Water:

Washing cycle electrical elements: 3 kW

Hot rinse cycle duration (sec.):

Min hot rinse water consumption (lt/cycle)**: 3.8 Water supply temperature*: 50 °C Washing tank capacity (It): 42 Boiler Capacity (It): 12

Key Information:

Washing cycle temperature: 55-65 °C Hot rinse cycle temperature: 84 °C

Working cycles time (sec.): 55/90/300 / / / /

Cell dimensions - width: 554 mm 570 mm Cell dimensions - depth: 450 mm Cell dimensions - height: External dimensions, Width: 642 mm 723 mm External dimensions, Depth: External dimensions, Height: 1477 mm Net weight: 97 kg Shipping weight: 105 kg 1700 mm Shipping height: Shipping width: 760 mm Shipping depth: 820 mm Shipping volume: 1.06 m³ Dishes capacity: 1170/hr Basket capacity: 65/h

