

Vacuum Packers Vacuum packer 20m3/h table top

| ITEM # | |
|--------------|--|
| MODEL # | |
| NAME # | |
| <u>SIS #</u> | |
| AIA # | |
| | |



Table top model with user friendly 5" touch screen control panel. 4 preset 'Gourmet' cycles (powders & spices, marinade in bags, marinade in containers, sauces). 3 preset cycles 'Gasplus' with inert gas injection (fragile foods). 4 vacuum cycle for jars. 2 preset cycles for preservation and sous vide cooking. 1 programmable deaeration program on eight vacuum phases and eight pause phases ('Degas'). 10 editable user programs (vacuum, extra vacuum, sealing time, gas percentage). "Softair' slow air return at the end of the cycle, more gentle on food (avoid deformation). With absolute-type vacuum sensor for vacuum level control, no calibration needed. Constructed in 304 AISI stainless steel with domed transparent PMMA Plexiglas lid. Pressure chamber with rounded corners for easy cleaning. External vacuum in bags or containers possible. Display shows alarm messages if malfunctions are detected (e.g. oil cleaning cycle needed). 3 PE filling plates included. Sealing barlength 410mm.5 display languages: EN, FR, IT, DE, ES. Easy access for service through hinged opening of the body. Optional Bluetooth label printer available, for HACCP compliance.

Main Features

- Table-top vacuum packer with oil lubricated vacuum pump.
- Vacuum level control through high-precision, absolute-type vacuum sensor, which does not require calibration.
- Pressure chamber made of constant thickness, hydroformed, stainless steel with rounded corners for easy cleaning.
- Sturdy, transparent PMMA (plexiglass) lid with rounded edges; opens automatically at the end of the cycle.
- User friendly interface thanks to a 5" touch screen control panel, made of tempered glass, resistant to liquids, humidity, dirt and dust.
- 5 display languages: EN, FR, IT, DE, ES.
- 10 editable user programs (vacuum, extra vacuum, sealing time, gas percentage).
- 4 preset (Gourmet) cycles for food processing.
- 3 preset cycles (Gasplus) with inert gas injection (for delicate/soft foods).
- 4 vacuum cycles for jars/containers.
- 2 preset cycles for preservation and sous vide cooking.
- 1 programmable deaeration program on eight vacuum phases and eight pause phases (Degas).
- Softair slow air return at the end of the cycle, more gentle on food (avoids deformation).
- Adjustable sealing time 0.1 to 6 seconds.
- Specific pump oil cleaning cycle (H2Out).
- Automatic warnings if food needs cooling down (hot), failure in the packing process, gas missing, oil change.
- Pre-arranged for external vacuum packing in containers by connecting a specific pipe to the air extraction nozzle (available as spare part).
- 3 PE filling plates included.
- Sealing bar 410 mm, easily removable for cleaning.
- Unit pre-arranged to be connected to an inert gas system.

Construction

packers

- Entirely constructed in 304 AISI stainless steel.
- Easy access for service through hinged opening of the body.

Optional Accessories

- Inclined shelf to vacuum liquids, 400mm (for models with 410mm sealing bar or multiples)
- Stainless steel trolley 570x630x700mm (H)
 Bluetooth printer for 50x60mm labels, display in English or block
- Italian. To be managed via dedicated app.
 UK power cord (2m) for vacuum PNC 650244

APPROVAL:

_____ I

Electrolux PROFESSIONAL

Vacuum Packers Vacuum packer 20m3/h table top



|--|--|

| Supply voltage: Total Watts: Plug type: | 220-240 V/1N ph/50-60 Hz 0.9 kW CE-SCHUKO |
|--|--|
| Key Information: | |
| Filling board nr: Gas nozzles: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Net weight (kg): Well Capacity: Pump: Sealing bar position: Sealing bar length: | 3 2 531 mm 594 mm 440 mm 62 25.2 lt 20 m ³ /h Front 410 mm |
| Max chamber (chamber + cover) dimensions: Chamber working dimensions: | 440 x 448 x 170 mm 387 x 448 x 130 mm |
| | |

Vacuum Packers Vacuum packer 20m3/h table top

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.