

Peelers Vegetable Peeler, 10 kg - Abrasive Plate (Marine)



from operating when the lid or unloading door is opened. Removable water jet device is fitted as standard to facilitate cleaning.

Supplied with abrasive plate.

ITEM # MODEL # NAME # SIS # AIA

Main Features

- Magnetic detectors will stop the machine from operating when the lid and/or door are opened.
- Suitable for 50-200 meals per service.
- Peels are reduced to small pieces to facilitate drainage process.
- Pulse function to control the unloading operation.
- Removable rotating plate covered in very resistant abrasive material (silicon carbide).
- Removable water inlet, clipped to the cover, designed to serve as a spray to clean the machine.
- Supplied with: -abrasive plate
- Transparent lid in damage-resistant plastic material allows visibility during peeling cycle.
- Timer with countdown display.

Construction

- Complete stainless steel construction.
- IP55 waterproof touch button control panel.
- Transparent BPA free cover incorporates a magnetic safety system which stops the machine if lid is not properly closed.

Included Accessories

• 1 of Abrasive plate for T10 or PNC 653203 T15

Optional Accessories

Brushing plate for T10 or T15 PNC 653058 🗅 (not for models with abrasive cylinder) Abrasive plate for small PNC 653184 🗅 onions, shallots and garlic T10 or T15, 388 mm diam. (not for models with abrasive cylinder) Abrasive plate for T10 or T15 PNC 653203 🗅 Knife plate for 10 and 15 ka PNC 653204 🗅 vegetable peelers (not for models with abrasive cylinder) PNC 653205 🗅 Abrasive plate for large onions T10 and T15 (not for models with abrasive cylinder) Drying basket for T10 PNC 653208 🗆 PNC 653620 🗅 Stainless steel seashell plate • for 10/15 kg vegetable peelers (not for models with abrasive cylinder) • Filter table with sliding shelf, PNC 653783 🗅 pre-assembled • Filter table with sliding shelf PNC 653784 🗅

APPROVAL:



Electrolux PROFESSIONAL

Peelers Vegetable Peeler, 10 kg - Abrasive Plate (Marine)

_ - -



Intertek

Intertek

Electric	
Supply voltage: Electrical power, max: Total Watts:	100-120 V/1N ph/60 Hz 0.37 kW 0.37 kW
Capacity:	
Performance (up to): Capacity:	160 kg/hour 10 litres
Key Information:	
External dimensions, Width: External dimensions, Depth: External dimensions, Height: Shipping weight:	440 mm 690 mm 680 mm 49 kg



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.