



## Digital Undercounter ecostore HP Refrigerated Counter - 2 Door (R290)



710405 (EJ2H7AA)

2-door Refrigerated Counter  
-2+10°C, AISI 304 (R290),  
without work top

### Short Form Specification

#### Item No.

AISI 304 stainless steel panels, AISI 430 bottom panel, galvanized back panel. N. 2 full doors. Built-in refrigeration unit. Operating temperature: -2+10°C. R290 gas in refrigeration circuit. Supplied with 1 grid for each door compartment

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_

### Main Features

- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Operating temperature can be adjusted from -2 to +10 °C to suit different food storage requirements.
- Complies with main international certification bodies and is CE marked.
- Kit 1/2 drawers available as accessory.
- Completely automatic defrosting and automatic evaporation of defrost water by hot gas.
- Forced air cooling system guaranteeing great uniformity of the temperature in the counter and excellent conservation of the food quality.
- Kit 1/3 drawers available as accessory.
- Tropicalized unit.

### Construction

- External back panel in galvanized steel.
- Built-in compressor to suit operating conditions.
- Legs in 304 AISI stainless steel (150 mm high, adjustable in height), with plastic interior.
- Internal and external doors, front and side panels in 304 AISI stainless steel.
- The door self-closes when opened less than at a 90° angle and is equipped with a door seal to guarantee perfect closure.
- High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids.

### Included Accessories

- 2 of Kit 1/1 grey rilsan grid and 2 PNC 881109 side runners for refrigerated counters

### Optional Accessories




• 1/1GN grey rilsan grid for refrigerated counters	PNC 881107	<input type="checkbox"/>
• 2 side runners for 1/1 GN ecostore refrigerated counters	PNC 881108	<input type="checkbox"/>
• Kit 1/1 grey rilsan grid and 2 side runners for refrigerated counters	PNC 881109	<input type="checkbox"/>
• 1/1 GN plastic container, H=65 mm	PNC 881110	<input type="checkbox"/>
• 1/1 GN plastic container, H=100 mm	PNC 881111	<input type="checkbox"/>
• Worktop for refrigerated counter, 2 compartments	PNC 881124	<input type="checkbox"/>
• Worktop with upstand for refrigerated counter, 2 compartments	PNC 881127	<input type="checkbox"/>
• 2x½ drawer kit for refrigerated counters - h650mm	PNC 881176	<input type="checkbox"/>
• 3x1/3 drawer kit for refrigerated counters - h650mm (only for refrigerated counters)	PNC 881177	<input type="checkbox"/>
• 1/3 and 2/3 bottle drawer kit for refrigerated counters - h650mm (only for refrigerated counters)	PNC 881178	<input type="checkbox"/>

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

- Kit 4 wheels, H=100 mm (2 with brakes) PNC 881191
- Kit 4 wheels, H=150 mm (2 with brakes) PNC 881193
- Lock for refrigerator/freezer counters with 2 compartments - h650mm (can be used in kit for Marine conversion) PNC 881245
- Kit 4 (45mm) spacers for wheels for refrigerator/freezer counters PNC 881277
- IoT module for refrigerated cabinets and counters PNC 881298


**Front**

**Side**
**EI** = Electrical inlet (power)

**Top**
**Electric**

**Supply voltage:** 220-240 V/1 ph/50 Hz  
**Electrical power, max:** 0.22 kW

**Key Information:**

**Net Volume:** 163.6 lt  
**Nº of doors:**  
**External dimensions, Width:** 1241 mm  
**External dimensions, Depth:** 700 mm  
**External dimensions, Height:** 800 mm  
**Internal Dimensions, Width:** 798 mm  
**Internal Dimensions, Depth:** 560 mm  
**Internal Dimensions, Height:** 510 mm  
**Net weight:** 90 kg  
**Shipping volume:** 1.03 m<sup>3</sup>  
**Depth with doors open:** 1310 mm  
**Gross capacity:** 290 lt

**Refrigeration Data**



**Control type:** Digital  
**Min/Max internal humidity:** 40/85  
**Operating temperature min.:** -2 °C  
**Operating temperature max.:** 10 °C  
**Compressor power:** 1/4 hp  
**Operating mode:** Ventilated  
**Insulation:** 90 mm (Cyclopentane)

**ISO Certificates**

**ISO Standards:** ISO 9001; ISO 14001; ISO 45001; ISO 50001

**Sustainability**

**Refrigerant type:** R290  
**GWP Index:** 3  
**Refrigeration power:** 320 W  
**Refrigerant weight (unit 1):** 45 g  
**Energy Class (EU Reg. 2015/1094):** B  
**Yearly and daily energy consumption (EU Reg. 2015/1094):** 560kWh/year - 2kWh/24h  
**Climate class (EU Reg. 2015/1094):** Heavy Duty (5)  
**Energy Efficiency Index-EEI (EU Reg. 2015/1094):** 25,36



### EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU.

These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

SI 2020 No. 1528.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.