

**Modular Cooking Range Line**  
**thermaline 80 - 400 mm Cupboard base**  
**with 1 door, GN conform, 1 Side (H2) -**  
**H=450**

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**588134 (MAIDCADO00)** Cupboard Base with 1 door,  
 one-side operated, GN - H2

### Short Form Specification

**Item No.** \_\_\_\_\_

400 mm wide cupboard base with 1 door with hygienic design and round edges. Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Cupboard storage space accepts GN 1/1 containers. IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

### Main Features


- IPX5 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth.
- Cupboard compartment for storage of pots, pans, sheet pans etc.

### Construction

- Hygienic design of the base cupboard with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance accepts GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.


**APPROVAL:** \_\_\_\_\_

Front



**Key Information:**

External dimensions, Width:	
588134 (MAIDCADO00)	400 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	340 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	715 mm
Net weight:	ISO 9001; ISO 14001 kg

Side



Top



### Optional Accessories

- |  |            |                          |  |
|--|------------|--------------------------|--|
| • Stainless steel side panel, 800x700mm, freestanding  | PNC 912509 | <input type="checkbox"/> | • Stainless steel side panel, 800x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)<br>PNC 913684 <input type="checkbox"/> |
| • Stainless steel front kicking strip, 400mm width   | PNC 912630 | <input type="checkbox"/> |  |
| • Stainless steel side kicking strip left and right, freestanding, 800mm width   | PNC 912655 | <input type="checkbox"/> |  |
| • Stainless steel side kicking strip left and right, against the wall, 800mm width   | PNC 912658 | <input type="checkbox"/> |  |
| • Stainless steel side kicking strip left and right, back-to-back, 1610mm width  | PNC 912661 | <input type="checkbox"/> |  |
| • Stainless steel plinth, against wall, 400mm width  | PNC 912840 | <input type="checkbox"/> |  |
| • Stainless steel plinth, freestanding, 400mm width  | PNC 912859 | <input type="checkbox"/> |  |
| • Stainless steel panel, 800x700mm, against wall, left side  | PNC 913093 | <input type="checkbox"/> |  |
| • Stainless steel panel, 800x700mm, against the wall, right side   | PNC 913097 | <input type="checkbox"/> |  |
| • Back panel, 400x450mm, for bases one-side operated   | PNC 913163 | <input type="checkbox"/> |  |
| • Stainless steel side panel, left, H=700  | PNC 913214 | <input type="checkbox"/> |  |
| • Stainless steel side panel, right, H=700   | PNC 913215 | <input type="checkbox"/> |  |
| • Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)                       | PNC 913233 | <input type="checkbox"/> |  |
| • Side reinforced panel only in combination with side shelf, for freestanding units  | PNC 913258 | <input type="checkbox"/> |  |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, left  | PNC 913263 | <input type="checkbox"/> |  |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, right   | PNC 913265 | <input type="checkbox"/> |  |
| • Side reinforced panel only in combination with side shelf, for back-to-back installations, left  | PNC 913271 | <input type="checkbox"/> |  |
| • Side reinforced panel only in combination with side shelf, for back-to-back installation, right  | PNC 913272 | <input type="checkbox"/> |  |
| • Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated  | PNC 913279 | <input type="checkbox"/> |  |
| • Stainless steel dividing panel, 800x700mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) | PNC 913668 | <input type="checkbox"/> |  |