

Modular Cooking Range Line
thermaline 80 - 400 mm Cupboard base
with 1 door, GN conform, 1 Side (H2) -
H=450

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



588134 (MAIDCADO00)

Cupboard Base with 1 door,
one-side operated, GN - H2

Short Form Specification

Item No. _____

400 mm wide cupboard base with 1 door with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Cupboard storage space accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features


- Cupboard compartment for storage of pots, pans, sheet pans etc.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.

Construction


- IPX5 water resistance certification.
- Hygienic design of the base cupboard with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance accepts GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL: _____


Front



Side



Top



Key Information:

External dimensions, Width:	
588134 (MA1DCAD000)	400 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	340 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	715 mm
Net weight:	20 kg

Optional Accessories

- | | | | | | |
|--|------------|--------------------------|---|------------|--------------------------|
| • Stainless steel side panel, 800x700mm, freestanding | PNC 912509 | ☐ | • Stainless steel side panel, 800x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) | PNC 913684 | ☐ |
| • Stainless steel front kicking strip, 400mm width | PNC 912630 | ☐ | | | |
| • Stainless steel side kicking strip left and right, freestanding, 800mm width | PNC 912655 | ☐ | | | |
| • Stainless steel side kicking strip left and right, against the wall, 800mm width | PNC 912658 | ☐ | | | |
| • Stainless steel side kicking strip left and right, back-to-back, 1610mm width | PNC 912661 | ☐ | | | |
| • Stainless steel plinth, against wall, 400mm width | PNC 912840 | ☐ | | | |
| • Stainless steel plinth, freestanding, 400mm width | PNC 912859 | ☐ | | | |
| • Stainless steel panel, 800x700mm, against wall, left side | PNC 913093 | ☐ | | | |
| • Stainless steel panel, 800x700mm, against the wall, right side | PNC 913097 | ☐ | | | |
| • Back panel, 400x450mm, for bases one-side operated | PNC 913163 | ☐ | | | |
| • Stainless steel side panel, left, H=700 | PNC 913214 | ☐ | | | |
| • Stainless steel side panel, right, H=700 | PNC 913215 | ☐ | | | |
| • Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913233 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for freestanding units | PNC 913258 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, left | PNC 913263 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913265 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for back-to-back installations, left | PNC 913271 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for back-to-back installation, right | PNC 913272 | ☐ | | | |
| • Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated | PNC 913279 | ☐ | | | |
| • Stainless steel dividing panel, 800x700mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) | PNC 913668 | ☐ | | | |