

Modular Cooking Range Line thermaline 80 - 900 mm Passthrough open base, 2 Sides (H2) - H=450

| ITEM #  |  |  |
|---------|--|--|
| MODEL # |  |  |
| NAME #  |  |  |
|         |  |  |
| SIS #   |  |  |
| AIA #   |  |  |



588141 (MA2ACCIOOO)

Passthrough Open Base, two-side operated - H2

## **Short Form Specification**

#### Item No.

900 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. IPX5 water resistant certification.

Configuration: Two-side operated freestanding base, hygienic class H2.

#### **Main Features**

- Open base compartment for storage of pots, pans, sheet pans, etc.
- IPX5 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth.

#### Construction


- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.


APPROVAL:






## Modular Cooking Range Line thermaline 80 - 900 mm Passthrough open base, 2 Sides (H2) - H=450








### **Key Information:**

External dimensions, Width:
588141 (MA2ACCIOOO)
900 mm
External dimensions, Depth:
800 mm
450 mm
Cupboard Cavity Dimensions (width):
680 mm
Cupboard Cavity Dimensions (height):
330 mm

 (depth):
 760 mm

 Net weight:
 21 kg







# **Optional Accessories**

| Stainless steel side panel,<br>800x700mm, freestanding   | PNC 912509 |  |
|--|------------|--|
| • Stainless steel front kicking strip, 900mm width   | PNC 912635 |  |
| <ul> <li>Stainless steel side kicking strip<br/>left and right, freestanding,<br/>800mm width</li> </ul>   | PNC 912655 |  |
| <ul> <li>Stainless steel plinth,<br/>freestanding, 900mm width</li> </ul>  | PNC 912864 |  |
| <ul> <li>Perforated shelf for warming<br/>cabinets and cupboard bases<br/>(one-side operated TL80-85-90<br/>and two-side operated for TL80)</li> </ul>   | PNC 913235 |  |
| <ul> <li>Side reinforced panel only in<br/>combination with side shelf, for<br/>freestanding units</li> </ul>  | PNC 913258 |  |
| <ul> <li>Shelf fixation for TL80-85-90 one-<br/>side operated, TL80 two-side<br/>operated</li> </ul>   | PNC 913283 |  |
| Stainless steel dividing panel,<br>800x700mm, (it should only be<br>used between Electrolux<br>Professional thermaline Modular<br>80 and thermaline C80)   | PNC 913668 |  |
| Stainless steel side panel,<br>800x700mm, flush-fitting (it<br>should only be used against the<br>wall, against a niche and in<br>between Electrolux Professional<br>thermaline and ProThermetic<br>appliances and external<br>appliances - provided that these<br>have at least the same<br>dimensions) | PNC 913684 |  |

