Electrolux PROFESSIONAL

Modular Cooking Range Line thermaline 80 - 1200 mm Passthrough base, 4 doors, GN conform, 2 Sides (H2) - H=450

ITEM #

MODEL #

NAME #

SIS #

AIA #

588152 (MA2FCCKOOO) Passthrough Cupboard Base, with 4 doors, two-side operated, GN - H2

Short Form Specification

Item No.

1200 mm wide passthrough base compartment with 4 doors, to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.
IPX5 water resistant certification.
Configuration: Two-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.

Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- Storage space in the base of the appliance that can accept GN1/1 containers.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:

Modular Cooking Range Line thermaline 80 - 1200 mm Passthrough base, 4 doors, GN conform, 2 Sides (H2) - H=450

Front



Side



Top

Key Information:

External dimensions, Width:	
588152 (MA2FCCKOOO)	1200 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	680 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	710 mm
Net weight:	36 kg

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.10.06

Optional Accessories

• Stainless steel side panel, 800x700mm, freestanding	PNC 912509	❑
• Stainless steel front kicking strip, 1200mm width	PNC 912638	❑
• Stainless steel side kicking strip left and right, freestanding, 800mm width	PNC 912655	❑
• Stainless steel plinth, freestanding, 1200mm width	PNC 912867	❑
• Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913235	❑
• Side reinforced panel only in combination with side shelf, for freestanding units	PNC 913258	❑
• Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated	PNC 913283	❑
• Stainless steel dividing panel, 800x700mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80)	PNC 913668	❑
• Stainless steel side panel, 800x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913684	❑

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.