

Modular Cooking Range Line thermaline 80 - 1500 mm Open base, 1 Side (H2) - H=550

| ITEM # | | |
|---------|--|--|
| MODEL # | | |
| NAME # | | |
| | | |
| SIS # | | |
| AIA # | | |



588219 (MAIADALOOO)

Open Base, one-side operated - H2

Short Form Specification

Item No.

1500 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- Open base compartment for storage of pots, pans, sheet pans, etc.
- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction


- Hygienic design of the open base compartment with large round edges.
- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:





Modular Cooking Range Line thermaline 80 - 1500 mm Open base, 1 Side (H2) - H=550



Key Information:

External dimensions, Width:

588219 (MAIADALOOO) 1500 mm **External dimensions, Depth:** 800 mm **External dimensions, Height:** 550 mm

Cupboard Cavity Dimensions (width):

840 mm

Cupboard Cavity Dimensions (height):

330 mm

Cupboard Cavity Dimensions

740 mm

(depth): Net weight:

29 kg





Modular Cooking Range Line thermaline 80 - 1500 mm Open base, 1 Side (H2) - H=550

PNC 913685

Optional Association

| Optional Accessories | | |
|--|------------|--|
| Stainless steel side panel, 800x800mm, freestanding | PNC 912508 | |
| Stainless steel front kicking strip, 1500mm width | PNC 912605 | |
| Stainless steel side kicking strips left and right, freestanding, 800mm width | PNC 912619 | |
| Stainless steel side kicking strips left and right, against the wall, 800mm width | PNC 912622 | |
| Stainless steel side kicking strips left and right, back-to-back, 1610mm width | PNC 912625 | |
| Stainless steel plinth, against wall, 1500mm width | PNC 912813 | |
| Stainless steel plinth, freestanding, 1500mm width | PNC 912832 | |
| Stainless steel panel, 800x800mm, against wall, left side | PNC 913094 | |
| Stainless steel panel, 800x800mm, flush-fitting, against wall, right side | PNC 913098 | |
| Back panel, 1500x450mm, for bases one-side operated | PNC 913189 | |
| • Stainless steel side panel, left, h=800 | PNC 913216 | |
| • Stainless steel side panel, right, h=800 | PNC 913217 | |
| Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913239 | |
| Side reinforced panel only in combination with side shelf, for freestanding units | PNC 913257 | |
| Side reinforced panel only in combination with side shelf for against the wall installations, left | PNC 913264 | |
| Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913266 | |
| Side reinforced panel only in combination with side shelf, for back-to-back installations, left | PNC 913273 | |
| Side reinforced panel only in combination with side shelf, for back-to-back installation, right | PNC 913274 | |
| Shelf fixation for TL80-85-90 one- side operated, TL80 two-side | PNC 913279 | |

• Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)



PNC 913669 📮

operated

Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux

80 and thermaline C80)

Professional thermaline Modular