

Modular Cooking Range Line thermaline 80 - 500 mm Open base, GN conform, 1 Side (H2) - H=550

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



588220 (MA1BDAEOOO)

Open Base, one-side operated, GN - H2

Short Form Specification

Item No.

500 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction


- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- Storage space in the base of the appliance that can accept GN1/1 containers.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:





Modular Cooking Range Line thermaline 80 - 500 mm Open base, GN conform, 1 Side (H2) - H=550



Key Information:

External dimensions, Width: 588220 (MAIBDAEOOO) 500 mm External dimensions, Depth: 800 mm External dimensions, Height: 550 mm **Cupboard Cavity Dimensions** 340 mm **Cupboard Cavity Dimensions** 330 mm **Cupboard Cavity Dimensions** 740 mm (depth): Net weight: 19 kg





Modular Cooking Range Line thermaline 80 - 500 mm Open base, GN conform, 1 Side (H2) - H=550

		Stainless steel side panel,	PNC 913685	
Optional Accessories	DV10 010500	800x800mm, flush-fitting (it should		
 Stainless steel side panel, 800x800mm, freestanding 	PNC 912508	only be used against the wall, against a niche and in between Electrolux Professional thermaline		
 Stainless steel front kicking strip, 500mm width 	PNC 912595	and ProThermetic appliances and external appliances - provided that		
 Stainless steel side kicking strips left and right, freestanding, 800mm width 	PNC 912619	these have at least the same dimensions)		
 Stainless steel side kicking strips left and right, against the wall, 800mm width 	PNC 912622			
 Stainless steel side kicking strips left and right, back-to-back, 1610mm width 	PNC 912625			
 Stainless steel plinth, against wall, 500mm width 	PNC 912803			
Stainless steel plinth, freestanding, 500mm width	PNC 912822			
Stainless steel panel, 800x800mm, against wall, left side	PNC 913094			
• Stainless steel panel, 800x800mm, flush-fitting, against wall, right side	PNC 913098			
Back panel, 500x550mm, for bases one-side operated	PNC 913179			
• Stainless steel side panel, left, h=800	PNC 913216			
• Stainless steel side panel, right, h=800	PNC 913217			
 Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) 	PNC 913233			
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913257			
 Side reinforced panel only in combination with side shelf for against the wall installations, left 	PNC 913264			
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913266			
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913273			
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913274			
 Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated 	PNC 913279			
Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular	PNC 913669			



80 and thermaline C80)