

Modular Cooking Range Line thermaline 80 - 600 mm Cupboard base with 1 door, GN conform, 1 Side (H2) -H=550

ITEM #
MODEL #
MODEL #
NAME #
CIC #
SIS #
AIA #



588225 (MAIDDAFOOO)

Cupboard Base with 1 door, one-side operated, GN - H2

Short Form Specification

Item No.

600 mm wide cupboard base with 1 door with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Cupboard storage space accepts GN 1/1 containers.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- Cupboard compartment for storage of pots, pans, sheet pans etc.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.

Construction


- IPX5 water resistance certification.
- Hygienic design of the base cupboard with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Storage space in the base of the appliance accepts GN1/1 containers.
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:









Key Information:

External dimensions, Width:	
588225 (MAIDDAFOOO)	600 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	550 mm
Cupboard Cavity Dimensions (width):	340 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth): Net weight:	715 mm 24 kg





Modular Cooking Range Line thermaline 80 - 600 mm Cupboard base with 1 door, GN conform, 1 Side (H2) - H=550

		Stainless steel side panel,	PNC 913685	
Optional Accessories	DNIC 010500	800x800mm, flush-fitting (it should only be used against the wall,		
 Stainless steel side panel, 800x800mm, freestanding 	PNC 912508	against a niche and in between Electrolux Professional thermaline		
 Stainless steel front kicking strip, 600mm width 	PNC 912596	and ProThermetic appliances and external appliances - provided that		
 Stainless steel side kicking strips left and right, freestanding, 800mm width 	PNC 912619	these have at least the same dimensions)		
 Stainless steel side kicking strips left and right, against the wall, 800mm width 	PNC 912622			
 Stainless steel side kicking strips left and right, back-to-back, 1610mm width 	PNC 912625			
 Stainless steel plinth, against wall, 600mm width 	PNC 912804			
 Stainless steel plinth, freestanding, 600mm width 	PNC 912823			
Stainless steel panel, 800x800mm, against wall, left side	PNC 913094			
 Stainless steel panel, 800x800mm, flush-fitting, against wall, right side 	PNC 913098			
Back panel, 600x450mm, for bases one-side operated	PNC 913180			
• Stainless steel side panel, left, h=800	PNC 913216			
• Stainless steel side panel, right, h=800	PNC 913217			
 Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) 	PNC 913233			
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913257			
Side reinforced panel only in combination with side shelf for against the wall installations, left	PNC 913264			
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913266			
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913273			
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913274			
 Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated 	PNC 913279			
 Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) 	PNC 913669			

