Electrolux PROFESSIONAL

Modular Cooking Range Line thermaline 80 - 1500 mm Passthrough open base, 2 Sides (H2) - H=550

ITEM #

MODEL #

NAME #

SIS #

AIA #

588233 (MA2ADCLOOO) Passthrough Open Base, two-side operated - H2

Short Form Specification

Item No.

1500 mm wide open passthrough base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.
IPX5 water resistant certification.
Configuration: Two-side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:

Modular Cooking Range Line thermaline 80 - 1500 mm Passthrough open base, 2 Sides (H2) - H=550

Front



Side



Top



Key Information:

External dimensions, Width:	
588233 (MA2ADCLOOO)	1500 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	550 mm
Cupboard Cavity Dimensions (width):	840 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	760 mm
Net weight:	29 kg

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.02.23

Optional Accessories

• Stainless steel side panel, 800x800mm, freestanding	PNC 912508	❑
• Stainless steel front kicking strip, 1500mm width	PNC 912605	❑
• Stainless steel side kicking strips left and right, freestanding, 800mm width	PNC 912619	❑
• Stainless steel plinth, freestanding, 1500mm width	PNC 912832	❑
• Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913239	❑
• Side reinforced panel only in combination with side shelf, for freestanding units	PNC 913257	❑
• Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated	PNC 913279	❑
• Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80)	PNC 913669	❑
• Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913685	❑

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.