



**Modular Cooking Range Line**  
**thermaline 80 - 1200 mm Passthrough**  
**base, 4 doors, GN conform, 2 Sides (H2)**  
**- H=550**


ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**588241 (MA2FDCKOOO)** Passthrough Open Base, with 4 doors, two-side operated, GN - H2

### Short Form Specification

**Item No.** \_\_\_\_\_

1200 mm wide passthrough base compartment with 4 doors, to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers. IPX5 water resistant certification. Configuration: Two-side operated freestanding base, hygienic class H2.

### Main Features

- All major components may be easily accessed from the front.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.


### Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- Storage space in the base of the appliance that can accept GN1/1 containers.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.
- [NOT TRANSLATED]


**APPROVAL:** \_\_\_\_\_




Front



Side



Top


**Key Information:**

|   |         |
|---|---------|
| <b>External dimensions, Width:</b>          |         |
| 588241 (MA2FDCKOOO)                         | 1200 mm |
| <b>External dimensions, Depth:</b>          | 800 mm  |
| <b>External dimensions, Height:</b>         | 550 mm  |
| <b>Cupboard Cavity Dimensions (width):</b>  | 680 mm  |
| <b>Cupboard Cavity Dimensions (height):</b> | 330 mm  |
| <b>Cupboard Cavity Dimensions (depth):</b>  | 710 mm  |
| <b>Net weight:</b>                          | 38 kg   |

## Optional Accessories

- Stainless steel side panel, 800x800mm, freestanding PNC 912508
- Stainless steel front kicking strip, 1200mm width PNC 912602
- Stainless steel side kicking strips left and right, freestanding, 800mm width PNC 912619
- Stainless steel plinth, freestanding, 1200mm width PNC 912829
- Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) PNC 913235
- Side reinforced panel only in combination with side shelf, for freestanding units PNC 913257
- Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated PNC 913283
- Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) PNC 913669
- Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) PNC 913685