

Modular Cooking Range Line thermaline 80 - Automatic water mixing tap, 1 Side with Backsplash - H=800

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



588267 (MAMAHBB3BO)

Water mixing tap Unit for automatic refilling, one-side operated with backsplash

# **Short Form Specification**

#### Item No.

Automatic water mixing tap for hot and cold water with electronic control of water quantity. Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. IPX5 water resistant certification.

Configuration: Freestanding, one-side operated with backsplash.

#### **Main Features**

- Water mixing unit for hot and cold water.
- IPX5 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Large stainless steel tap.


### Construction


- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:




## Modular Cooking Range Line thermaline 80 - Automatic water mixing tap, 1 Side with Backsplash - H=800





CWI1 = Cold Water inlet 1 (cleaning)
EI = Electrical inlet (power)
HWI = Hot water inlet



### Electric

Supply voltage:

**588267 (MAMAHBB3BO)** 230 V/1N ph/50/60 Hz

Total Watts: 0.1 kW

Water:

Inlet water line size: 3/4"

Incoming Cold/hot Water line

size: 3/4"

**Key Information:** 

External dimensions, Width: 200 mm
External dimensions, Depth: 800 mm
External dimensions, Height: 800 mm
Net weight: 25 kg

Sustainability

Current consumption: 0.5 Amps





### Modular Cooking Range Line thermaline 80 - Automatic water mixing tap, 1 Side with Backsplash - H=800

PNC 913685

# **Optional Accessories**

•		
• Connecting rail kit for appliances with backsplash, 800mm	PNC 912497	
<ul> <li>Portioning shelf, 200mm width</li> </ul>	PNC 912520	
<ul> <li>Portioning shelf, 200mm width</li> </ul>	PNC 912550	
<ul> <li>Folding shelf, 300x800mm</li> </ul>	PNC 912577	
<ul> <li>Folding shelf, 400x800mm</li> </ul>	PNC 912578	
• Fixed side shelf, 200x800mm	PNC 912583	
<ul> <li>Fixed side shelf, 300x800mm</li> </ul>	PNC 912584	
• Fixed side shelf, 400x800mm	PNC 912585	
<ul> <li>Stainless steel plinth, against wall, 200mm width</li> </ul>	PNC 912800	
• Connecting rail kit for appliances with backsplash: modular 80 (on	PNC 912977	

Connecting rail kit for appliances Pt with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)

Connecting rail kit for appliances PNC 912978 with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)

Back panel, 200x800mm, for units PNC 913020 ☐ with backsplash

PNC 913094 📮

PNC 913114

 Stainless steel panel, 800x800mm, against wall, left side

• Stainless steel panel, PNC 913098 ☐

800x800mm, flush-fitting, against wall, right side

 Endrail kit, flush-fitting, with backsplash, left

PNC 913113
D

 Endrail kit, flush-fitting, with backsplash, right

Endrail kit (12.5mm) for thermaline PNC 913204 □

80 units with backsplash, left

Endrail kit (12.5mm) for thermaline PNC 913205
 80 units with backsplash, right

U-clamping rail for back-to-back PNC 913226 ☐ installations with backsplash

Insert profile D=800mm
 Side reinforced panel only in
 PNC 913230 □
 PNC 913264 □

 Side reinforced panel only in combination with side shelf for against the wall installations, left

Side reinforced panel only in PNC 913266 
 combination with side shelf for

combination with side shelf, for against the wall installations, right

Professional thermaline Modular

80 and thermaline C80)

 Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux  Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)

