

**Modular Cooking Range Line
 thermaline 80 - 25 lt Well Freestanding
 Electric Pasta Cooker, 1 Side with
 Backsplash, H=800**

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



588292 (MAKCFBDDAO)

20lt electric Pasta Cooker,
 one-side operated with
 backsplash

Short Form Specification

Item No. _____

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Appliance which can also be used to cook noodles of every kind, rice, dumplings and vegetables. Water basin in 1.4435 (AISI 316L) stainless steel, with automatic constant water level re-fill and water temperature regulation via sensors. Integrated drip tray to drain baskets. Compatible with automatic basket lifting system to facilitate lifting operations. Safety systems and automatic low-water level shut-off protect against overheating. All-round basin raised edges to protect against soil infiltration. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistant certification.

Configuration: Freestanding, one-side operated with backsplash.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Constant water level refill.
- Automatic low-water level shut-off: no accidental over-heating.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Easy to clean basin with rounded corners.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Safety systems protect against overtemperature and can be manually reset.
- Automatic two-speed water refill regulated by water level sensor at maxim or minimum volume.
- Water temperature controlled by electronic sensor and can be selected as either temperature or power levels.
- Possibility of food re-generation thanks to electronic temperature control.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- IPX5 water resistance certification.
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability

- Standby function for energy saving and fast

APPROVAL: _____

recovery of maximum power.

Optional Accessories


• Connecting rail kit for appliances with backsplash, 800mm	PNC 912497	☐	• Side reinforced panel only in combination with side shelf for against the wall installations, left	PNC 913264	☐
• Portioning shelf, 400mm width	PNC 912522	☐	• Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913266	☐
• Portioning shelf, 400mm width	PNC 912552	☐	• Filter W=400mm	PNC 913663	☐
• Folding shelf, 300x800mm	PNC 912577	☐	• Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80)	PNC 913669	☐
• Folding shelf, 400x800mm	PNC 912578	☐	• Electric mains switch 25A 4mm ² NM for modular H800 electric units (factory fitted)	PNC 913676	☐
• Fixed side shelf, 200x800mm	PNC 912583	☐	• Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913685	☐
• Fixed side shelf, 300x800mm	PNC 912584	☐			
• Fixed side shelf, 400x800mm	PNC 912585	☐			
• Stainless steel front kicking strip, 400mm width	PNC 912594	☐			
• Stainless steel side kicking strips left and right, against the wall, 800mm width	PNC 912622	☐			
• Stainless steel side kicking strips left and right, back-to-back, 1610mm width	PNC 912625	☐			
• Stainless steel plinth, against wall, 400mm width	PNC 912802	☐			
• Connecting rail kit for appliances with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912977	☐			
• Connecting rail kit for appliances with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912978	☐			
• Back panel, 400x800mm, for units with backsplash	PNC 913022	☐			
• 1 basket for 20lt pasta cooker	PNC 913036	☐			
• Stainless steel panel, 800x800mm, against wall, left side	PNC 913094	☐			
• Stainless steel panel, 800x800mm, flush-fitting, against wall, right side	PNC 913098	☐			
• Endrail kit, flush-fitting, with backsplash, left	PNC 913113	☐			
• Endrail kit, flush-fitting, with backsplash, right	PNC 913114	☐			
• 2 baskets for 20lt pasta cooker	PNC 913135	☐			
• 4 baskets for 20lt pasta cooker	PNC 913136	☐			
• 2 baskets for 20lt pasta cooker	PNC 913137	☐			
• Support frame for 4 baskets for 20lt pasta cooker	PNC 913138	☐			
• Lid for 20lt pasta cooker	PNC 913148	☐			
• Endrail kit (12.5mm) for thermaline 80 units with backsplash, left	PNC 913204	☐			
• Endrail kit (12.5mm) for thermaline 80 units with backsplash, right	PNC 913205	☐			
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226	☐			
• Insert profile D=800mm	PNC 913230	☐			
• Energy optimizer kit 14A - factory fitted	PNC 913244	☐			




Electrolux
PROFESSIONAL

Modular Cooking Range Line
thermaline 80 - 25 lt Well Freestanding Electric
Pasta Cooker, 1 Side with Backsplash, H=800

Front




Side



D = Drain
EI = Electrical inlet (power)
EQ = Equipotential screw
WI = Water inlet

Top



Electric

Supply voltage: 400 V/3N ph/50/60 Hz
Electrical power, max: 6 kW
Total Watts: 6 kW

Water:

Incoming Cold/hot Water line size: 3/4"
Drain line size: 1"

Key Information:

Number of wells: 1
Usable well dimensions (width): 250 mm
Usable well dimensions (height): 330 mm
Usable well dimensions (depth): 400 mm
Well capacity: 18 lt MIN; 24.5 lt MAX
Thermostat Range: 40 °C MIN; 90 °C MAX
External dimensions, Width: 400 mm
External dimensions, Depth: 800 mm
External dimensions, Height: 800 mm
Net weight: 63 kg
Configuration: On Base; One-Side Operated

Sustainability

Current consumption: 8.7 Amps



Modular Cooking Range Line
thermaline 80 - 25 lt Well Freestanding Electric Pasta Cooker, 1 Side
with Backsplash, H=800
The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2025.10.04

Optional Accessories

- | | | | | | |
|---|------------|--------------------------|---|------------|--------------------------|
| • Connecting rail kit for appliances with backsplash, 800mm | PNC 912497 | ☐ | • U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) | PNC 913226 | ☐ |
| • Portioning shelf, 400mm width | PNC 912522 | ☐ | • Insert profile D=800mm | PNC 913230 | ☐ |
| • Portioning shelf, 400mm width | PNC 912552 | ☐ | • Energy optimizer kit 14A - factory fitted | PNC 913244 | ☐ |
| • Folding shelf, 300x800mm | PNC 912577 | ☐ | • Side reinforced panel only in combination with side shelf for against the wall installations, left | PNC 913264 | ☐ |
| • Folding shelf, 400x800mm | PNC 912578 | ☐ | • Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913266 | ☐ |
| • Fixed side shelf, 200x800mm | PNC 912583 | ☐ | • Filter W=400mm | PNC 913663 | ☐ |
| • Fixed side shelf, 300x800mm | PNC 912584 | ☐ | • Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) | PNC 913669 | ☐ |
| • Fixed side shelf, 400x800mm | PNC 912585 | ☐ | • Electric mainswitch 25A 4mm ² NM for modular H800 electric units (factory fitted) | PNC 913676 | ☐ |
| • Stainless steel front kicking strip, 400mm width | PNC 912594 | ☐ | • Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) | PNC 913685 | ☐ |
| • Stainless steel side kicking strips left and right, against the wall, 800mm width | PNC 912622 | ☐ | | | |
| • Stainless steel side kicking strips left and right, back-to-back, 1610mm width | PNC 912625 | ☐ | | | |
| • Stainless steel plinth, against wall, 400mm width | PNC 912802 | ☐ | | | |
| • Connecting rail kit for appliances with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right) | PNC 912977 | ☐ | | | |
| • Connecting rail kit for appliances with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left) | PNC 912978 | ☐ | | | |
| • Back panel, 400x800mm, for units with backsplash | PNC 913022 | ☐ | | | |
| • 1 basket for 20lt pasta cooker | PNC 913036 | ☐ | | | |
| • Stainless steel panel, 800x800mm, against wall, left side | PNC 913094 | ☐ | | | |
| • Stainless steel panel, 800x800mm, flush-fitting, against wall, right side | PNC 913098 | ☐ | | | |
| • Endrail kit, flush-fitting, with backsplash, left | PNC 913113 | ☐ | | | |
| • Endrail kit, flush-fitting, with backsplash, right | PNC 913114 | ☐ | | | |
| • 2 baskets for 20lt pasta cooker | PNC 913135 | ☐ | | | |
| • 4 baskets for 20lt pasta cooker | PNC 913136 | ☐ | | | |
| • 2 baskets for 20lt pasta cooker | PNC 913137 | ☐ | | | |
| • Support frame for 4 baskets for 20lt pasta cooker | PNC 913138 | ☐ | | | |
| • Lid for 20lt pasta cooker | PNC 913148 | ☐ | | | |
| • Endrail kit (12.5mm) for thermaline 80 units with backsplash, left | PNC 913204 | ☐ | | | |
| • Endrail kit (12.5mm) for thermaline 80 units with backsplash, right | PNC 913205 | ☐ | | | |