

Modular Cooking Range Line thermaline 80 - Sink unit on closed base, 1 Side, Backsplash, H=800

ITEM #	
MODEL "	
MODEL #	
NAME #	
CIC "	
SIS #	
AIA#	



588300 (MAZAHBD3OO)

Sink Unit on Closed Base, one-side operated with backsplash

Short Form Specification

Item No.

Sink unit on closed base, with a large stainless steel tap, constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating.

IPX5 water resistant certification.

Configuration: Freestanding, one-side operated with backsplash.

Main Features

- Large stainless steel tap.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.

Construction

- IPX5 water resistance certification.
- Fitted on a closed base.
- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL:



Modular Cooking Range Line thermaline 80 - Sink unit on closed base, 1 Side, Backsplash, H=800

Front Side

CWI1 = Cold Water inlet 1 (cleaning)


150

500

D = Drain

HWI = Hot water inlet

9000 8000



Water:

Inlet water line size:

588300 (MAZAHBD3OO) 3/4" Drain line size: 1" Incoming Cold/hot Water line size: 3/4"

Key Information:

External dimensions, Width: 400 mm
External dimensions, Depth: 800 mm
External dimensions, Height: 800 mm
Net weight: 28 kg





Modular Cooking Range Line thermaline 80 - Sink unit on closed base, 1 Side, Backsplash, H=800

Stainless steel dividing panel, 800x800mm, (it should only be used PNC 913669 **Optional Accessories** between Electrolux Professional • Connecting rail kit for appliances PNC 912497 🚨 thermaline Modular 80 and with backsplash, 800mm thermaline C80) • Portioning shelf, 400mm width PNC 912522 🚨 • Stainless steel side panel, PNC 913685 • Portioning shelf, 400mm width PNC 912552 🔲 800x800mm, flush-fitting (it should only be used against the wall, • Folding shelf, 300x800mm PNC 912577 📮 Folding shelf, 400x800mm PNC 912578 🔲 against a niche and in between Electrolux Professional thermaline • Fixed side shelf, 200x800mm PNC 912583 📮 and ProThermetic appliances and • Fixed side shelf, 300x800mm PNC 912584 🔲 external appliances - provided that • Fixed side shelf, 400x800mm PNC 912585 🔲 these have at least the same PNC 912594 📮 • Stainless steel front kicking strip, dimensions) 400mm width • Stainless steel side kicking strips PNC 912622 🔲 left and right, against the wall, 800mm width • Stainless steel side kicking strips PNC 912625 🔲 left and right, back-to-back, 1610mm width PNC 912802 📮 • Stainless steel plinth, against wall, 400mm width Connecting rail kit for appliances PNC 912977 □ with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right) Connecting rail kit for appliances PNC 912978 □ with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left) Back panel, 400x800mm, for units PNC 913022 with backsplash Stainless steel panel, PNC 913094 📮 800x800mm, against wall, left side Stainless steel panel, PNC 913098 📮 800x800mm, flush-fitting, against wall, right side PNC 913113 • Endrail kit, flush-fitting, with backsplash, left • Endrail kit, flush-fitting, with PNC 913114 backsplash, right • Endrail kit (12.5mm) for thermaline PNC 913204 □ 80 units with backsplash, left • Endrail kit (12.5mm) for thermaline PNC 913205 80 units with backsplash, right U-clamping rail for back-to-back PNC 913226 □ installations with backsplash PNC 913230 📮 Insert profile D=800mm • Side reinforced panel only in PNC 913264 📮 combination with side shelf for against the wall installations, left PNC 913266 🚨 Side reinforced panel only in combination with side shelf, for against the wall installations, right

