



**Modular Cooking Range Line  
thermaline 80 - Half Module  
Freestanding Electric Fry Top, 1 Side,  
with Backsplash H=700**

ITEM # \_\_\_\_\_  
MODEL # \_\_\_\_\_  
NAME # \_\_\_\_\_  
SIS # \_\_\_\_\_  
AIA # \_\_\_\_\_



**588363 (MAHAEBDDAO)** Electric Fry Top with smooth chrome Plate, one-side operated with backsplash

**588367 (MAHCEBDDAO)** Electric Fry Top with ribbed chrome Plate, one-side operated with backsplash

### Short Form Specification

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Powerblock heating system for optimal temperature distribution. Stainless steel high splash guards on the rear and sides. Large drain hole allows draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistant certification.

Configuration: Freestanding, one-side operated with backsplash.

### Main Features

- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Powerblock heating system for optimal temperature distribution.

### Construction

- Cooking surface to be completely smooth or completely ribbed.
- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- Internal frame for heavy duty sturdiness in stainless steel.

### Sustainability

- Standby function for energy saving and fast recovery of maximum power.



### APPROVAL:



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

**Optional Accessories**

• Connecting rail kit for appliances with backsplash, 800mm	PNC 912497	• Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913263	<input type="checkbox"/>
• Portioning shelf, 400mm width	PNC 912522	• Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913265	<input type="checkbox"/>
• Portioning shelf, 400mm width	PNC 912552	• Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated	PNC 913279	<input type="checkbox"/>
• Folding shelf, 300x800mm	PNC 912577	• Filter W=400mm	PNC 913663	<input type="checkbox"/>
• Folding shelf, 400x800mm	PNC 912578	• Stainless steel dividing panel, 800x700mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80)	PNC 913668	<input type="checkbox"/>
• Fixed side shelf, 200x800mm	PNC 912583	• Stainless steel side panel, 800x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913684	<input type="checkbox"/>
• Fixed side shelf, 300x800mm	PNC 912584			
• Fixed side shelf, 400x800mm	PNC 912585			
• Stainless steel front kicking strip, 400mm width	PNC 912630			
• Stainless steel side kicking strip left and right, against the wall, 800mm width	PNC 912658			
• Stainless steel side kicking strip left and right, back-to-back, 1610mm width	PNC 912661			
• Stainless steel plinth, against wall, 400mm width	PNC 912840			
• Connecting rail kit for appliances with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912977			
• Connecting rail kit for appliances with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912978			
• Back panel, 400x700mm, for units with backsplash	PNC 913009			
• Stainless steel panel, 800x700mm, against wall, left side	PNC 913093			
• Stainless steel panel, 800x700mm, against the wall, right side	PNC 913097			
• Endrail kit, flush-fitting, with backsplash, left	PNC 913113			
• Endrail kit, flush-fitting, with backsplash, right	PNC 913114			
• Scraper for smooth plates (only for 588363)	PNC 913119			
• Scraper for ribbed plates (only for 588367)	PNC 913120			
• Endrail kit (12.5mm) for thermaline 80 units with backsplash, left	PNC 913204			
• Endrail kit (12.5mm) for thermaline 80 units with backsplash, right	PNC 913205			
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226			
• Insert profile D=800mm	PNC 913230			
• Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913233			
• Energy optimizer kit 14A - factory fitted	PNC 913244			

**Recommended Detergents**

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.)

 PNC 0S2292



Modular Cooking Range Line  
thermaline 80 - Half Module Freestanding  
Electric Fry Top, 1 Side, with Backsplash H=700

## Electric

Supply voltage: 400 V/3N ph/50/60 Hz  
Total Watts: 5.1 kW

## Key Information:

Cooking Surface Depth: 615 mm  
Cooking Surface Width: 300 mm  
Working Temperature MIN: 80 °C  
Working Temperature MAX: 280 °C  
External dimensions, Width: 400 mm  
External dimensions, Depth: 800 mm  
External dimensions, Height: 700 mm  
Storage Cavity Dimensions (width): 340 mm  
Storage Cavity Dimensions (height): 330 mm  
Storage Cavity Dimensions (depth): 740 mm  
Net weight: 91 kg  
Configuration: One-Side Operated  
Cooking surface type:  
588363 (MAHAEBDDAO) Smooth  
588367 (MAHCEBDDAO) Ribbed  
Cooking surface - material: Chromium Plated mild steel mirror

## Sustainability

Current consumption: 7.4 Amps

