

Modular Cooking Range Line thermaline 80 - 500 mm Freestanding Electric Free-cooking Top, Smooth Plate, 1 Side, H=700

ITEM #	
MODEL #	
NAME #	
SIS #	_
AIA #	_



588378 (MATDEAEDAO)

Electric Free-Cooking Top, one-side operated

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth electrically-heated solid plate made of 20 mm thick steel with a wide rounded cleaning zone around the plate. Rapid plate heat up, continuously ready to use; maximum reachable surface temperature of 350°C. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX5 water resistance certification.

Configuration: Free standing, one-side operated.

Main Features

- For direct and indirect cooking.
- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Wide rounded cleaning zone around the plates for easier cleaning.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Surface temperature up to 350°C

Construction

- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Cooking surface is an electrically heated solid plate made from 20 mm thick stainless steel AISI 316 - DIN 1.4404.
- IPX5 water resistance certification.
- 2mm thick top in stainless steel AISI 304 DIN 1.4301.
- Internal frame for heavy duty sturdiness in stainless steel.

Optional Accessories

	•			
•	Connecting rail kit, 800mm	PNC	912500	
•	Stainless steel side panel, 800x700mm, freestanding	PNC	912509	
•	Portioning shelf, 500mm width	PNC	912523	
•	Portioning shelf, 500mm width	PNC	912553	
•	Folding shelf, 300x800mm	PNC	912577	
•	Folding shelf, 400x800mm	PNC	912578	
•	Fixed side shelf, 200x800mm	PNC	912583	
•	Fixed side shelf, 300x800mm	PNC	912584	

APPROVAL:







Modular Cooking Range Line thermaline 80 - 500 mm Freestanding Electric Free-cooking Top, Smooth Plate, 1 Side, H=700

Fixed side shelf, 400x800mm	PNC 912585		Stainless steel dividing panel, 800×700mm (it should only be used)	PNC 913668	
 Stainless steel front kicking strip, 500mm width 	PNC 912631	_	800x700mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline		
 Stainless steel side kicking strip left and right, freestanding, 800mm width 	PNC 912655		C80) • Stainless steel side panel, 800x700mm,	PNC 913684	
 Stainless steel side kicking strip left and right, back-to-back, 1610mm width 	PNC 912661		flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional		
 Stainless steel plinth, freestanding, 500mm width 	PNC 912860		thermaline and ProThermetic appliances and external appliances - provided that these have at least the		
 Connecting rail kit: modular 80 (on the left) to ProThermetic tilting (on 	PNC 912971		same dimensions)		
the right), ProThermetic stationary (on the left) to ProThermetic (on the right)			 Recommended Detergents C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.) 	PNC 0S2292	
 Connecting rail kit: modular 80 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic (on the left) 	PNC 912972				
• Endrail kit, flush-fitting, left	PNC 913109				
• Endrail kit, flush-fitting, right	PNC 913110				
• Scraper for smooth plates	PNC 913119				
• Endrail kit (12.5mm) for thermaline 80 units, left					
• Endrail kit (12.5mm) for thermaline 80 units, right	PNC 913201				
• Stainless steel side panel, left, H=700					
Stainless steel side panel, right, H=700	PNC 913215				
 T-connection rail for back-to-back installations without backsplash (to be ordered as S-code) 	PNC 913227				
Insert profile D=800mm	PNC 913230				
 Perforated shelf for warming cabinets and cupboard bases (one- side operated TL80-85-90 and two- side operated for TL80) 	PNC 913233				
• Energy optimizer kit 14A - factory fitted	PNC 913244				
• Endrail kit, (12.5mm), for back-to- back installation, left	PNC 913249				
• Endrail kit, (12.5mm), for back-to- back installation, right	PNC 913250				
• Endrail kit, flush-fitting, for back-to- back installation, left	PNC 913253				
• Endrail kit, flush-fitting, for back-to- back installation, right	PNC 913254				
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913258				
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913271				
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913272				
 Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated 	PNC 913279				
Filter W=500mm	PNC 913664				










Electrical inlet (power) Equipotential screw





Supply voltage: 400 V/3N ph/50/60 Hz

Total Watts: 6 kW

Key Information:

80 °C Working Temperature MIN: Working Temperature MAX: 350 °C External dimensions, Width: 500 mm External dimensions, Depth: 800 mm External dimensions, Height: 700 mm Net weight: 100 kg

On Base;One-Side Operated Configuration:

Sustainability

Top

Current consumption: 13 Amps





Modular Cooking Range Line thermaline 80 - 500 mm Freestanding Electric Free-cooking Top, Smooth Plate, 1 Side, H=700

Optional Accessories			Side reinforced panel only in combination with side shelf, for back-to-	PNC 913271	
 Connecting rail kit, 800mm 	PNC 912500		back installations, left		
 Stainless steel side panel, 800x700mm, freestanding 	PNC 912509		combination with side shelf, for back-to-	PNC 913272	
 Portioning shelf, 500mm width 	PNC 912523		back installation, right		
 Portioning shelf, 500mm width 	PNC 912553			PNC 913279	
 Folding shelf, 300x800mm 	PNC 912577		operated, TL80 two-side operated		_
• Folding shelf, 400x800mm	PNC 912578			PNC 913664	
• Fixed side shelf, 200x800mm	PNC 912583			PNC 913668	
• Fixed side shelf, 300x800mm	PNC 912584	_	800x700mm, (it should only be used		
• Fixed side shelf, 400x800mm	PNC 912585		between Electrolux Professional thermaline Modular 80 and thermaline		
•			C80)		
Stainless steel front kicking strip, 500mm width	PNC 912631		•	PNC 913684	
 Stainless steel side kicking strip left and right, freestanding, 800mm width 	PNC 912655		against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic		
 Stainless steel side kicking strip left and right, back-to-back, 1610mm width 	PNC 912661		appliances and external appliances - provided that these have at least the same dimensions)		
 Stainless steel plinth, freestanding, 500mm width 	PNC 912860		Recommended Detergents		
 Connecting rail kit: modular 80 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic (on the right) 	PNC 912971		_	PNC 0S2292	
Connecting rail kit: modular 80 (on the right) to ProThermetic tilling (on the left), ProThermetic stationary (on the right) to ProThermetic (on the left)	PNC 912972				
Endrail kit, flush-fitting, left	PNC 913109				
Endrail kit, flush-fitting, right	PNC 913110				
	PNC 913119				
• Scraper for smooth plates					
 Endrail kit (12.5mm) for thermaline 80 units, left 	PNC 913200				
• Endrail kit (12.5mm) for thermaline 80 units, right	PNC 913201				
• Stainless steel side panel, left, H=700	PNC 913214				
• Stainless steel side panel, right, H=700	PNC 913215				
 T-connection rail for back-to-back installations without backsplash (to be ordered as S-code) 	PNC 913227				
• Insert profile D=800mm	PNC 913230				
 Perforated shelf for warming cabinets and cupboard bases (one- side operated TL80-85-90 and two- side operated for TL80) 	PNC 913233				
Energy optimizer kit 14A - factory fitted	PNC 913244				
Endrail kit, (12.5mm), for back-to- back installation, left	PNC 913249				
Endrail kit, (12.5mm), for back-to- back installation, right	PNC 913250				
Endrail kit, flush-fitting, for back-to- back installation, left	PNC 913253				
Endrail kit, flush-fitting, for back-to- back installation, right	PNC 913254				
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913258				

