



Electrolux
PROFESSIONAL

**Modular Cooking Range Line
thermaline 80 - Water mixing tap
with lever, 1 Side - H=800**

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



588390 (MAEAHAB300)

Water mixing tap with one
lever, one-side operated

Short Form Specification

Item No. _____

Water mixing tap with lever for hot and cold water. Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. IPX5 water resistant certification. Configuration: Freestanding, one-side operated.

Main Features

- Water mixing unit for hot and cold water.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Large stainless steel tap.

Construction

- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

APPROVAL: _____




Experience the Excellence
www.electroluxprofessional.com




Electrolux
PROFESSIONAL

Modular Cooking Range Line thermaline 80 - Water mixing tap with lever, 1 Side - H=800

Front




Side



CWI1 = Cold Water inlet 1 (cleaning)
HWI = Hot water inlet

Top



Water:

Inlet water line size: 3/4"
Incoming Cold/hot Water line size: 3/4"

Key Information:

External dimensions, Width: 200 mm
External dimensions, Depth: 800 mm
External dimensions, Height: 800 mm
Net weight: 25 kg



Modular Cooking Range Line
thermaline 80 - Water mixing tap with lever, 1 Side - H=800

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.08.05

Optional Accessories

- | | | | | | |
|--|------------|--------------------------|---|------------|--------------------------|
| • Connecting rail kit, 800mm | PNC 912500 | ☐ | • Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80) | PNC 913669 | ☐ |
| • Stainless steel side panel, 800x800mm, freestanding | PNC 912508 | ☐ | | | |
| • Portioning shelf, 200mm width | PNC 912520 | ☐ | • Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) | PNC 913685 | ☐ |
| • Portioning shelf, 200mm width | PNC 912550 | ☐ | | | |
| • Folding shelf, 300x800mm | PNC 912577 | ☐ | | | |
| • Folding shelf, 400x800mm | PNC 912578 | ☐ | | | |
| • Fixed side shelf, 200x800mm | PNC 912583 | ☐ | | | |
| • Fixed side shelf, 300x800mm | PNC 912584 | ☐ | | | |
| • Fixed side shelf, 400x800mm | PNC 912585 | ☐ | | | |
| • Stainless steel plinth, freestanding, 200mm width | PNC 912819 | ☐ | | | |
| • Connecting rail kit: modular 80 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic (on the right) | PNC 912971 | ☐ | | | |
| • Connecting rail kit: modular 80 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic (on the left) | PNC 912972 | ☐ | | | |
| • Endrail kit, flush-fitting, left | PNC 913109 | ☐ | | | |
| • Endrail kit, flush-fitting, right | PNC 913110 | ☐ | | | |
| • Endrail kit (12.5mm) for thermaline 80 units, left | PNC 913200 | ☐ | | | |
| • Endrail kit (12.5mm) for thermaline 80 units, right | PNC 913201 | ☐ | | | |
| • Stainless steel side panel, left, h=800 | PNC 913216 | ☐ | | | |
| • Stainless steel side panel, right, h=800 | PNC 913217 | ☐ | | | |
| • T-connection rail for back-to-back installations without backsplash (to be ordered as S-code) | PNC 913227 | ☐ | | | |
| • Insert profile D=800mm | PNC 913230 | ☐ | | | |
| • Endrail kit, (12.5mm), for back-to-back installation, left | PNC 913249 | ☐ | | | |
| • Endrail kit, (12.5mm), for back-to-back installation, right | PNC 913250 | ☐ | | | |
| • Endrail kit, flush-fitting, for back-to-back installation, left | PNC 913253 | ☐ | | | |
| • Endrail kit, flush-fitting, for back-to-back installation, right | PNC 913254 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for freestanding units | PNC 913257 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for back-to-back installations, left | PNC 913273 | ☐ | | | |
| • Side reinforced panel only in combination with side shelf, for back-to-back installation, right | PNC 913274 | ☐ | | | |