

## Modular Cooking Range Line thermaline 80 - 4 Zone Electric Solid Top on Oven, 1 Side-Ecotop H=700

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**588414 (MALMEAH8AO)**

Electric Solid Top, 4 zones,  
 ecoTop coating, one-side  
 operated, on Oven

### Short Form Specification

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. ECOTOP model with a 20 mm thick steel cooking surface with heat retaining coating. 4 independently controlled heating zones with 2 electronic sensors per zone for temperature surface control and 8 power levels. Rapid plate heat up, continuously ready to use. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning. Electric static oven base with 40 mm thick oven door and ribbed enamelled steel base plate. Constructed according to 1.4301 (AISI 304). Oven chamber with 2 levels of runners for 2/1 GN shelves to enable simultaneous and faster cooking. Heavy duty thermostat with temperature range up to 300°C, electronic sensor for precise temperature control and manual humidity control in the cooking chamber. Upper heating element can also be used for grilling, with or without ventilating mode. Flat surface construction, easily cleanable. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs and oven handles ergonomically designed with embedded hygienic silicon "soft" grip enable easier handling and cleaning. IPX5 water resistance certification.

### Main Features

- 4 heating zones independently controlled.
- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: a temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- Wide rounded cleaning zone around the plates for easier cleaning.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Two electronic sensors per zone to control surface temperature and to protect cooking plate from overheating.
- 8 power levels.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- 40 mm thick oven door for heat insulation.
- Handles are ergonomically designed with silicon "soft" grip for easy handling and cleaning.
- Oven chamber to have 2 levels of runners to accommodate 2/1 GN trays and ribbed enamelled steel base plate.
- Heavy duty thermostat with temperature range up to 300°C.
- The upper heating element of the oven can also be used for grilling.
- Manual control of humidity in cooking chamber.
- Electronic sensor for precise temperature control.
- Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth.
- Oven temperature up to 300 °C
- ECOTOP model has a 20 mm thick steel DIN 1.7335 nickel coated cooking surface.

### Construction

- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top.
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- IPX5 water resistance certification.

**APPROVAL:** \_\_\_\_\_

- Internal frame for heavy duty sturdiness in stainless steel.

### Sustainability



- Standby function for energy saving and fast recovery of maximum power.

### Included Accessories

- 1 of Grid, chromium plated, for ovens PNC 910652  
2/1 GN

### Optional Accessories

- |                                                                                                                                                                          |            |                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------|
| • Baking sheet 2/1 GN for ovens                                                                                                                                          | PNC 910651 | <input type="checkbox"/> |
| • Bottom steel plate 2/1 GN for fire<br>clay plate 800&900 with baking<br>oven                                                                                           | PNC 910655 | <input type="checkbox"/> |
| • Fire clay plate 2/1 GN for ovens                                                                                                                                       | PNC 910656 | <input type="checkbox"/> |
| • Connecting rail kit, 800mm                                                                                                                                             | PNC 912500 | <input type="checkbox"/> |
| • Stainless steel side panel,<br>800x700mm, freestanding                                                                                                                 | PNC 912509 | <input type="checkbox"/> |
| • Portioning shelf, 800mm width                                                                                                                                          | PNC 912526 | <input type="checkbox"/> |
| • Portioning shelf, 800mm width                                                                                                                                          | PNC 912556 | <input type="checkbox"/> |
| • Folding shelf, 300x800mm                                                                                                                                               | PNC 912577 | <input type="checkbox"/> |
| • Folding shelf, 400x800mm                                                                                                                                               | PNC 912578 | <input type="checkbox"/> |
| • Fixed side shelf, 200x800mm                                                                                                                                            | PNC 912583 | <input type="checkbox"/> |
| • Fixed side shelf, 300x800mm                                                                                                                                            | PNC 912584 | <input type="checkbox"/> |
| • Fixed side shelf, 400x800mm                                                                                                                                            | PNC 912585 | <input type="checkbox"/> |
| • Stainless steel front kicking strip,<br>800mm width                                                                                                                    | PNC 912634 | <input type="checkbox"/> |
| • Stainless steel side kicking strip left<br>and right, freestanding, 800mm<br>width                                                                                     | PNC 912655 | <input type="checkbox"/> |
| • Stainless steel plinth, freestanding,<br>800mm width                                                                                                                   | PNC 912863 | <input type="checkbox"/> |
| • Connecting rail kit: modular 80 (on<br>the left) to ProThermetic tilting (on<br>the right), ProThermetic stationary<br>(on the left) to ProThermetic (on the<br>right) | PNC 912971 | <input type="checkbox"/> |
| • Connecting rail kit: modular 80 (on<br>the right) to ProThermetic tilting (on<br>the left), ProThermetic stationary (on<br>the right) to ProThermetic (on the<br>left) | PNC 912972 | <input type="checkbox"/> |
| • Endrail kit, flush-fitting, left                                                                                                                                       | PNC 913109 | <input type="checkbox"/> |
| • Endrail kit, flush-fitting, right                                                                                                                                      | PNC 913110 | <input type="checkbox"/> |
| • Endrail kit (12.5mm) for thermaline 80<br>units, left                                                                                                                  | PNC 913200 | <input type="checkbox"/> |
| • Endrail kit (12.5mm) for thermaline 80<br>units, right                                                                                                                 | PNC 913201 | <input type="checkbox"/> |
| • Stainless steel side panel, left, H=700                                                                                                                                | PNC 913214 | <input type="checkbox"/> |
| • Stainless steel side panel, right,<br>H=700                                                                                                                            | PNC 913215 | <input type="checkbox"/> |
| • T-connection rail for back-to-back<br>installations without backsplash (to<br>be ordered as S-code)                                                                    | PNC 913227 | <input type="checkbox"/> |
| • Insert profile D=800mm                                                                                                                                                 | PNC 913230 | <input type="checkbox"/> |
| • Energy optimizer kit 32A - factory<br>fitted                                                                                                                           | PNC 913247 | <input type="checkbox"/> |
| • Endrail kit, (12.5mm), for back-to-<br>back installation, left                                                                                                         | PNC 913249 | <input type="checkbox"/> |
| • Endrail kit, (12.5mm), for back-to-<br>back installation, right                                                                                                        | PNC 913250 | <input type="checkbox"/> |
| • Endrail kit, flush-fitting, for back-to-<br>back installation, left                                                                                                    | PNC 913253 | <input type="checkbox"/> |


- Endrail kit, flush-fitting, for back-to-back installation, right PNC 913254 ☐
- Side reinforced panel only in combination with side shelf, for freestanding units PNC 913258 ☐
- Side reinforced panel only in combination with side shelf, for back-to-back installations, left PNC 913271 ☐
- Side reinforced panel only in combination with side shelf, for back-to-back installation, right PNC 913272 ☐
- Filter W=800mm PNC 913665 ☐




**Electrolux**  
PROFESSIONAL

**Modular Cooking Range Line  
thermaline 80 - 4 Zone Electric Solid  
Top on Oven, 1 Side-Ecotop H=700**

Front




Side



EI = Electrical inlet (power)  
EQ = Equipotential screw

Top



**Modular Cooking Range Line  
thermaline 80 - 4 Zone Electric Solid Top on Oven, 1 Side-Ecotop H=700**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.06.05

**Electric**

Supply voltage: 400 V/3N ph/50/60 Hz  
Electrical power, max: 17.3 kW

**Key Information:**

Working Temperature MIN: 100 °C  
Working Temperature MAX: 450 °C  
External dimensions, Width: 800 mm  
External dimensions, Depth: 800 mm  
External dimensions, Height: 700 mm  
Net weight: 208 kg  
Configuration: On Oven; One-Side Operated  
Front Plates Power: 3 - 3 kW  
Back Plates Power: 3 - 3 kW  
Solid top usable surface (width): 670 mm  
Solid top usable surface (depth): 650 mm

**Sustainability**

Current consumption: 31.7 Amps