

Modular Cooking Range Line thermaline 85 - 900 mm Open base, 1 Side (H2)

ITEM #		
MODEL #		
NAME #		
_		
SIS #		
AIA #		



588573 (MB1ACAIOOO)

Open Base, one-side operated - H2

Short Form Specification

Item No.

900 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.

IPX5 water resistant certification.

Configuration: One side operated freestanding base, hygienic class H2.

Main Features

- All major components may be easily accessed from the front.
- Open base compartment for storage of pots, pans, sheet pans, etc.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

Construction

- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

Optional Accessories

_	paroman / toooboomoo		
•	Stainless steel front kicking strip, 900mm width	PNC 912635	
•	Stainless steel side kicking strip left and right, wall mounted, 850mm width	PNC 912659	
•	Stainless steel side kicking strip left and right, back-to-back, 1700mm width	PNC 912662	
•	Stainless steel side panel, 850x700mm, right side, against wall	PNC 913003	
•	Stainless steel side panel, 850x700mm, left side, against wall	PNC 913004	
•	Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913235	
•	Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913261	
•	Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913262	
•	Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated	PNC 913283	
•	Stainless steel dividing panel, 850x700mm, (it should only be used between Electrolux	PNC 913670	

Professional thermaline Modular

85 and thermaline C85)

APPROVAL:







Modular Cooking Range Line thermaline 85 - 900 mm Open base, 1 Side (H2)


• Stainless steel side panel, 850x700mm, PNC 913686 flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)



Modular Cooking Range Line thermaline 85 - 900 mm Open base, 1 Side (H2)







Key Information:

External dimensions, Width:

588573 (MBIACAIOOO) 900 mm **External dimensions, Depth:** 850 mm **External dimensions, Height:** 450 mm

Cupboard Cavity Dimensions

680 mm

Cupboard Cavity Dimensions

330 mm

Cupboard Cavity Dimensions (depth):

740 mm

Net weight: 22 kg