Electrolux PROFESSIONAL

# Modular Cooking Range Line thermaline 85 - 1500 mm Open base, 1 Side (H2)

ITEM #

MODEL #

NAME #

SIS #

AIA #

| | |
|---|---|
| **588576 (MB1ACALOOO)** | Open Base, one-side operated - H2 |

## Short Form Specification

**Item No.**

1500 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.
IPX5 water resistant certification.
Configuration: One side operated freestanding base, hygienic class H2.

**APPROVAL:**

## Main Features

- All major components may be easily accessed from the front.
- Open base compartment for storage of pots, pans, sheet pans, etc.
- Unit to be placed below modular top appliances to store pots, pans, sheet pans, etc.

## Construction

- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

## Optional Accessories

| | | |
|---|---|---|
| • Stainless steel front kicking strip, 1500mm width | PNC 912641 | ❑ |
| • Stainless steel side kicking strip left and right, wall mounted, 850mm width | PNC 912659 | ❑ |
| • Stainless steel side kicking strip left and right, back-to-back, 1700mm width | PNC 912662 | ❑ |
| • Stainless steel side panel, 850x700mm, right side, against wall | PNC 913003 | ❑ |
| • Stainless steel side panel, 850x700mm, left side, against wall | PNC 913004 | ❑ |
| • Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) | PNC 913239 | ❑ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, right | PNC 913261 | ❑ |
| • Side reinforced panel only in combination with side shelf, for against the wall installations, left | PNC 913262 | ❑ |
| • Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated | PNC 913279 | ❑ |
| • Stainless steel dividing panel, 850x700mm, (it should only be used between Electrolux Professional thermaline Modular 85 and thermaline C85) | PNC 913670 | ❑ |

| | | |
|---|---|---|
| • Stainless steel side panel, 850x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions) | PNC 913686 | ❑ |



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# Modular Cooking Range Line thermaline 85 - 1500 mm Open base, 1 Side (H2)

Front




Side




Top

## Key Information:

| | |
|---|---|
| **External dimensions, Width:** | |
| **588576 (MB1ACALOOO)** | 1500 mm |
| **External dimensions, Depth:** | 850 mm |
| **External dimensions, Height:** | 450 mm |
| **Cupboard Cavity Dimensions (width):** | 840 mm |
| **Cupboard Cavity Dimensions (height):** | 330 mm |
| **Cupboard Cavity Dimensions (depth):** | 740 mm |
| **Net weight:** | 28 kg |



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2024.10.06