

Modular Cooking Range Line thermaline 85 - 800 mm Open base, GN conform, 1 Side (H2)

ITEM #		
MODEL #		
NAME #		
SIS #		
313 #		
AIA #		



588579 (MB1BCAHOOO)

Open Base, one-side operated, GN - H2

### **Short Form Specification**

#### Item No.

800 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable. Open storage space in the base accepts GN 1/1 containers. IPX5 water resistant certification.

Configuration: One side operated freestanding base, hygienic class H2

#### **Main Features**

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- IPX5 water resistance certification.
- Unit constructed according to DIN 18860\_2 with 70 mm recessed plinth.

#### Construction

- Storage space in the base of the appliance that can accept GN1/1 containers.
- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

### **Optional Accessories**

85 and thermaline C85)

•	phonoi Accessories		
•	Stainless steel front kicking strip, 800mm width	PNC 912634	
•	Stainless steel side kicking strip left and right, wall mounted, 850mm width	PNC 912659	
•	Stainless steel side kicking strip left and right, back-to-back, 1700mm width	PNC 912662	
•	Stainless steel side panel, 850x700mm, right side, against wall	PNC 913003	
•	Stainless steel side panel, 850x700mm, left side, against wall	PNC 913004	
•	Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)	PNC 913234	
•	Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913261	
•	Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913262	
•	Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated	PNC 913281	
•	Stainless steel dividing panel, 850x700mm, (it should only be used between Electrolux Professional thermaline Modular	PNC 913670	

#### APPROVAL:







# Modular Cooking Range Line thermaline 85 - 800 mm Open base, GN conform, 1 Side (H2)


• Stainless steel side panel, 850x700mm, PNC 913686 flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)



# Modular Cooking Range Line thermaline 85 - 800 mm Open base, GN conform, 1 Side (H2)







### **Key Information:**

External dimensions, Width:

**588579 (MBIBCAHOOO)** 800 mm External dimensions, Depth: 850 mm External dimensions, Height: 450 mm

**Cupboard Cavity Dimensions** 

580 mm

**Cupboard Cavity Dimensions** 

330 mm

Cupboard Cavity Dimensions (depth):

740 mm

Net weight: 21 kg