

Modular Cooking Range Line thermaline 85 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side with Backsplash

ITEM #		
MODEL #		
MODEL #		
NAME #		
SIS #		
AIA #		



588626 (MBKDGBDDPO) 24,5-lt gas Pasta Cooker, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860 2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Appliance which can also be used to cook noodles of every kind, rice, dumplings and vegetables. Water basin in 1.4435 (AISI 316L) stainless steel, with automatic constant water level re-fill regulation via sensor. High efficiency burners in AISI 430 stainless steel with flame failure device. Safety thermostat and thermostatic control. Energy Control for fine power adjustment to control boiling level and optimize energy consumption. Integrated drip tray to drain baskets. Compatible with automatic basket lifting system to facilitate lifting operations. Safety systems and automatic low-water level shut-off protect against overheating. All-round basin raised edges to protect against soil infiltration. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX4 water resistant certification.

Configuration: Freestanding, one side operated with backsplash.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Easy to clean basin with rounded corners.
- Raised edge all around the well to protect from infiltration of dirt from worktop.
- Safety systems protect against overtemperature and can be manually reset.
- Safety thermostat and thermostatic control.
- Electrical ignition powered by battery with thermocouple for added safety.

Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Water basin in 1.4435 (AISI 316L) stainless steel is seamlessly welded into the top of the appliance.
- High efficiency burners in AISI 430 stainless steel with flame failure device.
- IPx4 water protection.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability



 EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.

APPROVAL:






Modular Cooking Range Line thermaline 85 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side with Backsplash


Optional Accessories			Stainless steel dividing panel, 850x700mm, (it should only be used)	PNC 913670	
Connecting rail kit for appliances with backsplash, 850mm	PNC 912498		between Electrolux Professional thermaline Modular 85 and thermaline		
Portioning shelf, 400mm width	PNC 912522		C85)		
Portioning shelf, 400mm width	PNC 912552		• Stainless steel side panel, 850x700mm,	PNC 913686	
	PNC 912579	_	flush-fitting (it should only be used		
• Folding shelf, 300x850mm			against the wall, against a niche and in		
• Folding shelf, 400x850mm	PNC 912580		between Electrolux Professional		
 Fixed side shelf, 200x850mm 	PNC 912586		thermaline and ProThermetic		
 Fixed side shelf, 300x850mm 	PNC 912587		appliances and external appliances -		
 Fixed side shelf, 400x850mm 	PNC 912588		provided that these have at least the same dimensions)		
 Stainless steel front kicking strip, 400mm width 	PNC 912630		same aimensions)		
 Stainless steel side kicking strip left and right, wall mounted, 850mm width 	PNC 912659				
 Stainless steel side kicking strip left and right, back-to-back, 1700mm width 	PNC 912662				
 Stainless steel plinth, against wall, 400mm width 	PNC 912878				
 Stainless steel side panel, 850x700mm, right side, against wall 	PNC 913003				
 Stainless steel side panel, 850x700mm, left side, against wall 	PNC 913004				
 Back panel, 400x700mm, for units with backsplash 	PNC 913009				
 1 basket for 20lt pasta cooker 	PNC 913036				
 Endrail kit, flush-fitting, with backsplash, left 	PNC 913115				
 Endrail kit, flush-fitting, with backsplash, right 	PNC 913116				
 2 baskets for 20lt pasta cooker 	PNC 913135				
 4 baskets for 20lt pasta cooker 	PNC 913136				
 2 baskets for 20lt pasta cooker 	PNC 913137				
Support frame for 4 baskets for 20lt pasta cooker	PNC 913138				
 Lid for 20lt pasta cooker 	PNC 913148				
Endrail kit (12.5mm) for thermaline 85 units with backsplash, left					
• Endrail kit (12.5mm) for thermaline 85 units with backsplash, right	PNC 913207				
 U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) 	PNC 913226				
 Insert profile, d=850mm 	PNC 913231				
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913261				
Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913262				
Additional wall mounting fixation - US	PNC 913640				
Stainless steel lower side panel (12,5mm), 850x300mm, left side, wall mounted	PNC 913641				
 Stainless steel lower side panel (12,5mm), 850x300mm, right side, wall mounted 	PNC 913642				
• Wall mounting kit for units - TL85/90 - Factory Fitted (H=700)	PNC 913655				






Modular Cooking Range Line thermaline 85 - 20 It Well Freestanding Gas Pasta Cooker, 1 Side with Backsplash





D = Drain

DO = Overflow drain pipe EQ = Equipotential screw G = Gas connection WI = Water inlet



Gas

Gas Power: 11.5 kW

Gas Type Option:

Gas Inlet: 1/2"

Water:

Side

Top

Incoming Cold/hot Water line

size: 3/4"
Drain line size: 1"

Key Information:

Number of wells:

Usable well dimensions

(width): 250 mm Usable well dimensions (height): 330 mm

(height): Usable well dimensions

(depth): 400 mm

Well capacity: 18 It MIN; 24.5 It MAX Thermostat Range: 40 °C MIN; 90 °C MAX

External dimensions, Width: 400 mm
External dimensions, Depth: 850 mm
External dimensions, Height: 700 mm
Net weight: 68 kg

On Base;One-Side

Configuration: Operated

