

Modular Cooking Range Line thermaline 85 - Sink unit on closed base, 1 Side with Backsplash



recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. IPX5 water resistant certification.

Configuration: Freestanding, one side operated with backsplash.

ITEM #	
MODEL #	
NAME #	
SIS #	
<u>AIA #</u>	

# **Main Features**

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Large stainless steel tap.

# Construction

- Fitted on a closed base.
- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

## **Optional Accessories**

- Connecting rail kit for appliances PNC 912498 with backsplash, 850mm
- Portioning shelf, 400mm width
   PNC 912522
- Portioning shelf, 400mm width PNC 912552
- Folding shelf, 300x850mm PNC 912579 □
- Folding shelf, 400x850mm
   PNC 912580 □
- Fixed side shelf, 200x850mm PNC 912586
- Fixed side shelf, 300x850mm PNC 912587
- Fixed side shelf, 400x850mm PNC 912588 🗅
- Stainless steel front kicking strip, PNC 912630 400mm width
- Stainless steel side kicking strip PNC 912659 left and right, wall mounted, 850mm width
- Stainless steel side kicking strip PNC 912662 left and right, back-to-back, 1700mm width
- Stainless steel plinth, against wall, PNC 912878 400mm width
- Stainless steel side panel, 850x700mm, right side, against wall
   PNC 913003
- Stainless steel side panel, 850x700mm, left side, against wall
   PNC 913004
- Back panel, 400x700mm, for units PNC 913009 with backsplash
- Endrail kit, flush-fitting, with PNC 913115 🗅 backsplash, left
- Endrail kit, flush-fitting, with PNC 913116 Dacksplash, right
- Endrail kit (12.5mm) for thermaline PNC 913206 85 units with backsplash, left

### APPROVAL:



<ul> <li>Endrail kit (12.5mm) for thermaline 85 units with backsplash, right</li> <li>U-clamping rail for back-to-back installations with backsplash (to be</li> </ul>	PNC 913207 PNC 913226	
<ul> <li>ordered as S-code)</li> <li>Insert profile, d=850mm</li> <li>Side reinforced panel only in combination with side shelf, for against the wall installations, right</li> </ul>	PNC 913231 PNC 913261	
• Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913262	
<ul> <li>Stainless steel dividing panel, 850x700mm, (it should only be used between Electrolux Professional thermaline Modular 85 and thermaline C85)</li> </ul>	PNC 913670	
<ul> <li>Stainless steel side panel, 850x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)</li> </ul>	PNC 913686	

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# Electrolux PROFESSIONAL

# Modular Cooking Range Line thermaline 85 - Sink unit on closed base, 1 Side with Backsplash



CE

# Water:

Inlet water line size:	3/4"
Drain line size:	]"
Incoming Cold/hot Water line size:	3/4"
	- /

# Key Information:

External dimensions, Width:400 mmExternal dimensions, Depth:850 mmExternal dimensions, Height:700 mmNet weight:33 kg

Modular Cooking Range Line thermaline 85 - Sink unit on closed base, 1 Side with Backsplash

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.