

# Modular Cooking Range Line thermaline 85 - Half Module Freestanding Gas Fry Top, 1 Side with Backsplash

ITEM #
MODEL #
MODEL #
NAME #
SIS #
AIA#



588667 (MBHAGBDDPO) Gas Fry Top with smooth chrome Plate, oneside operated with backsplash

588671 (MBHCGBDDPO) Gas Fry Top with ribbed chrome Plate, oneside operated with backsplash

# **Short Form Specification**

#### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth chromiumplated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Features safety thermostat, thermostatic control and led indication of pilot flame. Electrical ignition powered by battery with thermocouple for added safety. Large drain hole enables draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX4 water resistant certification.

Configuration: Freestanding, one side operated with backsplash.

## **Main Features**

- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "softtouch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Electrical ignition powered by battery with thermocouple for added safety.
- Led indication of pilot flame

# Construction

- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- IPx4 water protection.
- Internal frame for heavy duty sturdiness in stainless steel.
- Cooking surface to be completely smooth or completely ribbed.

#### APPROVAL:





# Modular Cooking Range Line thermaline 85 - Half Module Freestanding Gas Fry Top, 1 Side with Backsplash

Optional Accessories  Connecting rail kit for appliances with backsplash, 850mm  Portioning shelf, 400mm width  Portioning shelf, 400mm width  Folding shelf, 300x850mm  Folding shelf, 400x850mm	PNC 912498  PNC 912522  PNC 912552  PNC 912579  PNC 912580		Stainless steel side panel, 850x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)	PNC 913686	
• Fixed side shelf, 200x850mm	PNC 912586		Recommended Detergents		
• Fixed side shelf, 300x850mm	PNC 912587	ш,	C41 HI-TEMP RAPID DEGREASER, P	NC 0S2292	
<ul> <li>Fixed side shelf, 400x850mm</li> <li>Stainless steel front kicking strip, 400mm width</li> </ul>	PNC 912588 PNC 912630		1 pack of six 1 lt. bottles (trigger incl.)		
<ul> <li>Stainless steel side kicking strip left and right, wall mounted, 850mm width</li> </ul>	PNC 912659				
• Stainless steel side kicking strip left and right, back-to-back, 1700mm width	PNC 912662				
• Stainless steel plinth, against wall, 400mm width	PNC 912878				
<ul> <li>Stainless steel side panel, 850x700mm, right side, against wall</li> </ul>	PNC 913003				
• Stainless steel side panel, 850x700mm, left side, against wall	PNC 913004				
<ul> <li>Back panel, 400x700mm, for units with backsplash</li> </ul>	PNC 913009				
<ul> <li>Endrail kit, flush-fitting, with backsplash, left</li> </ul>	PNC 913115				
<ul> <li>Endrail kit, flush-fitting, with backsplash, right</li> </ul>	PNC 913116				
• Scraper for smooth plates (only for 588667)	PNC 913119				
<ul> <li>Scraper for ribbed plates (only for 588671)</li> </ul>	PNC 913120				
<ul> <li>Endrail kit (12.5mm) for thermaline 85 units with backsplash, left</li> </ul>	PNC 913206				
• Endrail kit (12.5mm) for thermaline 85 units with backsplash, right	PNC 913207				
<ul> <li>U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)</li> </ul>	PNC 913226				
<ul> <li>Insert profile, d=850mm</li> </ul>	PNC 913231				
<ul> <li>Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)</li> </ul>	PNC 913233				
Side reinforced panel only in combination with side shelf, for against the wall installations, right	PNC 913261				
<ul> <li>Side reinforced panel only in combination with side shelf, for against the wall installations, left</li> </ul>	PNC 913262				
<ul> <li>Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated</li> </ul>	PNC 913279				
<ul> <li>Stainless steel dividing panel, 850x700mm, (it should only be used between Electrolux Professional thermaline Modular 85 and thermaline C85)</li> </ul>	PNC 913670				



# **Modular Cooking Range Line** thermaline 85 - Half Module Freestanding Gas Fry Top, 1 Side with Backsplash

### Gas

Gas Power: 10 kW Gas Type Option: Natural Gas Gas Inlet: 1/2"

# **Key Information:**

Cooking Surface Depth: 615 mm Cooking Surface Width: 300 mm Working Temperature MIN: 110 °C Working Temperature MAX: 270 °C External dimensions, Width: 400 mm External dimensions, Depth: 850 mm External dimensions, Height: 700 mm

**Storage Cavity Dimensions** 

(width):

340 mm

**Storage Cavity Dimensions** 

(height):

330 mm

**Storage Cavity Dimensions** 

(depth): Net weight: 740 mm

87 kg

On Base;One-Side Configuration:

Operated

Cooking surface type:

588667 (MBHAGBDDPO) 588671 (MBHCGBDDPO)

Smooth Ribbed

Chromium Plated mild

Cooking surface - material: steel mirror



# Modular Cooking Range Line thermaline 85 - Half Module Freestanding Gas Fry Top, 1 Side with Backsplash



