Electrolux PROFESSIONAL

Modular Cooking Range Line thermaline 90 - 1 Zone Induction Wok, 1 Side with Backsplash

ITEM #

MODEL #

NAME #

SIS #

AIA #

589035 (MCIHABEOAO)	Induction Wok, 1 zone, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Smooth glass ceramic surface without any "dead" spots allows for quick and easy cleaning. The surface is not directly heated to avoid any burnings. Fast deployment with full heating power immediately and very low heat dissipation to the kitchen. Power to the zone can be set with progressive output. Overheat protection switches off the supply in case of overheating. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.
IPX5 water resistant certification.
Configuration: One-side operated top with backsplash. The base is supplied by the factory

APPROVAL:

Main Features

- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Fast deployment with full heating power immediately.
- Low heat dissipation to the kitchen.
- Power to the zone can be set with progressive output i.e. fine regulation at the lower levels and larger progress at the upper levels.
- The smooth, glass ceramic plate is not directly heated, so there is no burning on cooking surface.

Construction

- 2 mm top in 1.4301 (AISI 304).
- IPX5 water resistance certification.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.

Sustainability

- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Optional Accessories

• Scraper for cook tops	PNC 910601	❑
• Induction Wok pan with wooden handle (diam. 360mm)	PNC 910613	❑
• Stainless steel wok pan, design in line with wok cuvette	PNC 911000	❑
• Non-stick wok pan, design in line with wok cuvette	PNC 911003	❑
• Inducton Wok pan with stainless steel handle (diam. 360mm)	PNC 911587	❑
• Connecting rail kit for appliances with backsplash, 900mm	PNC 912499	❑
• Portioning shelf, 500mm width	PNC 912523	❑
• Portioning shelf, 500mm width	PNC 912553	❑
• Folding shelf, 300x900mm	PNC 912581	❑
• Folding shelf, 400x900mm	PNC 912582	❑
• Fixed side shelf, 200x900mm	PNC 912589	❑
• Fixed side shelf, 300x900mm	PNC 912590	❑
• Fixed side shelf, 400x900mm	PNC 912591	❑
• Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981	❑
• Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982	❑
• Back panel, 500x700mm, for units with backsplash	PNC 913010	❑
• Back panel, 500x800mm, for units with backsplash	PNC 913023	❑
• Endrail kit, flush-fitting, with backsplash, left	PNC 913117	❑
• Endrail kit, flush-fitting, with backsplash, right	PNC 913118	❑
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208	❑
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209	❑
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226	❑
• Insert profile d=900	PNC 913232	❑
• Filter W=500mm	PNC 913664	❑
• Electric mainswitch 25A 4mm2 NM for modular H800 electric units (factory fitted)	PNC 913676	❑

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Modular Cooking Range Line thermaline 90 - 1 Zone Induction Wok, 1 Side with Backsplash

Front



Side



EI = Electrical inlet (power)
EQ = Equipotential screw

Top



Electric

Supply voltage:	400 V/3N ph/50/60 Hz
Total Watts:	5 kW

Key Information:

External dimensions, Width:	500 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	250 mm
Net weight:	18 kg
Configuration:	One-Side Operated;Top
Back Plates Power:	5 - kW
Back Plates dimensions:	Ø 300
Induction Top Dimensions (width):	500 mm
Induction Top Dimensions (depth):	900 mm

Sustainability

Current consumption:	7.5 Amps

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.