



Modular Cooking Range Line thermaline 90 - Full Module Electric Fry Top, 1 Side with Backsplash



589091 (MCHMABHOAO)

Electric Fry Top with smooth chrome Plate, one-side operated with backsplash

589099 (MCHNABHOAO)

Electric Fry Top with ribbed chrome Plate, one-side operated with backsplash

Short Form Specification

Item No.

Unit constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating. Chromium-plated mild steel cooking surface with non-stick finishing for optimal grilling. Stainless steel high splash guards on the rear and sides. Powerblock heating system for optimal temperature distribution. Large drain hole allows draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic silicon "soft" grip enable easier handling and cleaning.

IPX5 water resistant certification.

Configuration: One-side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

Main Features

- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Powerblock heating system for optimal temperature distribution.

Construction

- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Cooking surface in chromium-plated mild steel with non-stick finishing for optimum grilling results.
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Cooking surface to be completely smooth or completely ribbed.

Sustainability

- Standby function for energy saving and fast recovery of maximum power.



APPROVAL:



Experience the Excellence
www.electroluxprofessional.com



Electrolux
PROFESSIONAL

Modular Cooking Range Line thermaline 90 - Full Module Electric Fry Top, 1 Side with Backsplash

Optional Accessories

• Connecting rail kit for appliances with backsplash, 900mm	PNC 912499
• Portioning shelf, 800mm width	PNC 912526
• Portioning shelf, 800mm width	PNC 912556
• Folding shelf, 300x900mm	PNC 912581
• Folding shelf, 400x900mm	PNC 912582
• Fixed side shelf, 200x900mm	PNC 912589
• Fixed side shelf, 300x900mm	PNC 912590
• Fixed side shelf, 400x900mm	PNC 912591
• Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981
• Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982
• Back panel, 800x700mm, for units with backsplash	PNC 913013
• Back panel, 800x800mm, for units with backsplash	PNC 913026
• Endrail kit, flush-fitting, with backsplash, left	PNC 913117
• Endrail kit, flush-fitting, with backsplash, right	PNC 913118
• Scraper for smooth plates (only for 589091)	PNC 913119
• Scraper for ribbed plates (only for 589099)	PNC 913120
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226
• Insert profile d=900	PNC 913232
• Energy optimizer kit 24A - factory fitted	PNC 913246
• Stainless steel side panel (12.5mm), 900x400mm, left side, wall mounted	PNC 913636
• Stainless steel side panel (12.5mm), 900x400mm, right side, wall mounted	PNC 913637
• Stainless steel side panel, 900x400mm, flush-fitting, left side, wall mounted	PNC 913638
• Stainless steel side panel, 900x400mm, flush-fitting, right side, wall mounted	PNC 913639
• Additional wall mounting fixation - US	PNC 913640
• Wall mounting kit top - TL85/90 - Factory Fitted	PNC 913652
• Filter W=800mm	PNC 913665
• Electric mainswitch 25A 4mm ² NM for modular H800 electric units (factory fitted)	PNC 913676

Electric

<input type="checkbox"/> Supply voltage:	400 V/3N ph/50/60 Hz
<input type="checkbox"/> Total Watts:	15.3 kW
Key Information:	
<input type="checkbox"/> Cooking Surface Depth:	615 mm
<input type="checkbox"/> Cooking Surface Width:	700 mm
<input type="checkbox"/> Working Temperature MIN:	80 °C
<input type="checkbox"/> Working Temperature MAX:	280 °C
<input type="checkbox"/> External dimensions, Width:	800 mm
<input type="checkbox"/> External dimensions, Depth:	900 mm
<input type="checkbox"/> External dimensions, Height:	250 mm
Net weight:	120 kg
Configuration:	One-Side Operated;Top
<input type="checkbox"/> Cooking surface type:	
589091 (MCHMABHOAO)	Smooth
589099 (MCHNABHOAO)	Ribbed
<input type="checkbox"/> Cooking surface material:	Chromium Plated mild steel mirror

Sustainability

Current consumption: 221 Amps

Recommended Detergents

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1lt. bottles (trigger incl.) PNC 0S2292




Electrolux
PROFESSIONAL

Modular Cooking Range Line

thermaline 90 - Full Module Electric

Fry Top, 1 Side with Backsplash



Modular Cooking Range Line
thermaline 90 - Full Module Electric Fry Top, 1 Side with Backsplash

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.01.27