



Electrolux
PROFESSIONAL

Modular Cooking Range Line thermaline 90 - 1000 mm Closed Work top, 1 Side with Backsplash

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



589169 (MCNABBJO00)

Closed Work Top, one-side
operated with backsplash

Short Form Specification

Item No.

Closed work top, 1000 mm wide, constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating.

IPX5 water resistant certification.

Configuration: One-side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.

Construction

- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.

Optional Accessories

- Connecting rail kit for appliances with backsplash, 900mm PNC 912499 ☐
- Portioning shelf, 1000mm width PNC 912528 ☐
- Portioning shelf, 1000mm width PNC 912558 ☐
- Folding shelf, 300x900mm PNC 912581 ☐
- Folding shelf, 400x900mm PNC 912582 ☐
- Fixed side shelf, 200x900mm PNC 912589 ☐
- Fixed side shelf, 300x900mm PNC 912590 ☐
- Fixed side shelf, 400x900mm PNC 912591 ☐
- Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermatic tilting (on the right), ProThermatic stationary (on the left) to ProThermatic tilting (on the right) PNC 912981 ☐
- Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermatic tilting (on the left), ProThermatic stationary (on the right) to ProThermatic tilting (on the left) PNC 912982 ☐
- Back panel, 1000x700mm, for units with backsplash PNC 913015 ☐
- Back panel, 1000x800mm, for units with backsplash PNC 913028 ☐
- Endrail kit, flush-fitting, with backsplash, left PNC 913117 ☐
- Endrail kit, flush-fitting, with backsplash, right PNC 913118 ☐
- Endrail kit (12.5mm) for thermaline 90 units with backsplash, left PNC 913208 ☐
- Endrail kit (12.5mm) for thermaline 90 units with backsplash, right PNC 913209 ☐
- U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code) PNC 913226 ☐
- Insert profile d=900 PNC 913232 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com



Electrolux
PROFESSIONAL

**Modular Cooking Range Line
thermaline 90 - 1000 mm Closed
Work top, 1 Side with Backsplash**


- | | | |
|--|------------|--------------------------|
| • Stainless steel side panel (12,5mm), 900x400mm, left side, wall mounted | PNC 913636 | ☐ |
| • Stainless steel side panel (12,5mm), 900x400mm, right side, wall mounted | PNC 913637 | ☐ |
| • Stainless steel side panel, 900x400mm, flush-fitting, left side, wall mounted | PNC 913638 | ☐ |
| • Stainless steel side panel, 900x400mm, flush-fitting, right side, wall mounted | PNC 913639 | ☐ |
| • Additional wall mounting fixation - US | PNC 913640 | ☐ |
| • Wall mounting kit top - TL85/90 - Factory Fitted | PNC 913654 | ☐ |

**Modular Cooking Range Line
thermaline 90 - 1000 mm Closed Work top, 1 Side with Backsplash**


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.10.04


Front



Side



Top

**Key Information:**

External dimensions, Width:

589169 (MCNABBJ000) 1000 mm

External dimensions, Depth: 900 mm

External dimensions, Height: 250 mm

Net weight: 34 kg