



Modular Cooking Range Line thermaline 90 - 1200 mm Closed Work top, 1 Side with Backsplash



589171 (MCNABBK000)

Closed Work Top, one-side
operated with backsplash

Short Form Specification

Item No.

Closed work top, 1200 mm wide, constructed according to DIN 18860_2 with 20 mm drop nose top. Internal frame for heavy duty sturdiness in stainless steel. 2 mm top in 1.4301 (AISI 304). Flat surface construction, easily cleanable. THERMODUL connection system enables seamless worktop when units are connected and avoids soil penetrating.

IPX5 water resistant certification.

Configuration: One-side operated top with backsplash. The base needs to be supplied by the factory. Please include appropriate base.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.

Construction

- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.


Optional Accessories

• Connecting rail kit for appliances with backsplash, 900mm	PNC 912499 <input type="checkbox"/>
• Portioning shelf, 1200mm width	PNC 912530 <input type="checkbox"/>
• Portioning shelf, 1200mm width	PNC 912560 <input type="checkbox"/>
• Folding shelf, 300x900mm	PNC 912581 <input type="checkbox"/>
• Folding shelf, 400x900mm	PNC 912582 <input type="checkbox"/>
• Fixed side shelf, 200x900mm	PNC 912589 <input type="checkbox"/>
• Fixed side shelf, 300x900mm	PNC 912590 <input type="checkbox"/>
• Fixed side shelf, 400x900mm	PNC 912591 <input type="checkbox"/>
• Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912981 <input type="checkbox"/>
• Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912982 <input type="checkbox"/>
• Back panel, 1200x700mm, for units with backsplash	PNC 913017 <input type="checkbox"/>
• Back panel, 1200x800mm, for units with backsplash	PNC 913030 <input type="checkbox"/>
• Endrail kit, flush-fitting, with backsplash, left	PNC 913117 <input type="checkbox"/>
• Endrail kit, flush-fitting, with backsplash, right	PNC 913118 <input type="checkbox"/>
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, left	PNC 913208 <input type="checkbox"/>
• Endrail kit (12.5mm) for thermaline 90 units with backsplash, right	PNC 913209 <input type="checkbox"/>
• U-clamping rail for back-to-back installations with backsplash (to be ordered as S-code)	PNC 913226 <input type="checkbox"/>
• Insert profile d=900	PNC 913232 <input type="checkbox"/>

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com



Key Information:

External dimensions, Width:
589171 (MCNABBKOOO) 1200 mm
External dimensions, Depth: 900 mm
External dimensions, Height: 250 mm
Net weight: 40 kg