

Modular Cooking Range Line thermaline 90 - 1200 mm Open base, 1 Side (H2) - H=450

ITEM #	
MODEL #	
MODEL #	
NAME #	
SIS #	
AIA#	



589177 (MC1ACAKOOO)

Open Base, one-side operated - H2

Short Form Specification

Item No.

1200 mm wide open base compartment to store pots, pans, sheet pans, etc. with hygienic design and round edges. Unit constructed according to DIN 18860_2 with 70 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. Flat surface construction, easily cleanable.

IPX5 water resistant certification.

Configuration: One-side operated freestanding base, hygienic class H2.

Main Features

- Open base compartment for storage of pots, pans, sheet pans, etc.
- IPX5 water resistance certification.
- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.

Construction


- Hygienic design of the open base compartment with large round edges.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.


APPROVAL:






Modular Cooking Range Line thermaline 90 - 1200 mm Open base, 1 Side (H2) - H=450







Key Information:

External dimensions, Width: 589177 (MC1ACAKOOO)

1200 mm External dimensions, Depth: 900 mm External dimensions, Height: 450 mm

Cupboard Cavity Dimensions (width):

840 mm

Cupboard Cavity Dimensions (height):


330 mm

Cupboard Cavity Dimensions

740 mm

(depth): Net weight:

26 kg







Modular Cooking Range Line thermaline 90 - 1200 mm Open base, 1 Side (H2) - H=450

Optional Accessories			 Stainless st 900x700mr
 Stainless steel side panel, 900x700mm, freestanding 	PNC 912512		only be use against a n Electrolux F and ProThe external ap these have dimensions
 Stainless steel front kicking strip, 1200mm width 	PNC 912638		
 Stainless steel side kicking strip left and right, freestanding, 900mm width 	PNC 912657		
 Stainless steel side kicking strips left and right, against the wall, 900mm width 	PNC 912660		
 Stainless steel side kicking strip left and right, back-to-back, 1810mm width 	PNC 912663		
 Stainless steel plinth, against wall, 1200mm width 	PNC 912943		
 Stainless steel plinth, freestanding, 1200mm width 	PNC 912962		
 Stainless steel panel, 900x700mm, against wall, left side 	PNC 913101		
 Stainless steel panel, 900x700mm, against wall, right side 	PNC 913105		
 Back panel, 1200x450mm, for bases one-side operated 	PNC 913171		
• Stainless steel side panel, left, H=700	PNC 913222		
 Stainless steel side panel, right, H=700 	PNC 913223		
 Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80) 	PNC 913239		
 Side reinforced panel only in combination with side shelf, for freestanding units 	PNC 913260		
Side reinforced panel only in combination with side shelf, for against the wall installations, left	PNC 913267		
 Side reinforced panel only in combination with side shelf, for against the wall installations, right 	PNC 913269		
 Side reinforced panel only in combination with side shelf, for back-to-back installations, left 	PNC 913275		
 Side reinforced panel only in combination with side shelf, for back-to-back installation, right 	PNC 913276		
Shelf fixation for TL80-85-90 one- side operated, TL80 two-side operated	PNC 913279		
Stainless steel dividing panel, 900x700mm, (it should only be used between Electrolux Professional thermaline Modular	PNC 913672		

Stainless steel side panel, 900x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)



Professional thermaline Modular

90 and thermaline C90)